



## Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) Piezo Ink Jet Ink 6786 Light Cyan  
**MANUFACTURER:** 3M  
**DIVISION:** Commercial Graphics

**ADDRESS:** 3M Center  
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 08/16/2005  
**Supersedes Date:** 06/08/2003

**Document Group:** 16-5845-9

#### Product Use:

Specific Use: Piezo Ink Jet Ink

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
2-BUTOXYETHYL ACETATE	112-07-2	50 - 60
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	88917-22-0	20 - 30
CYCLOHEXANONE	108-94-1	10 - 20
VINYL CHLORIDE-VINYL ACETATE POLYMER	9003-22-9	1 - 5
ETHYL ACRYLATE-METHYL METHACRYLATE POLYMER	9010-88-2	1 - 5

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Liquid

**Odor, Color, Grade:** Solvent Odor, Cyan Color

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects.

#### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

May be absorbed through skin and cause target organ effects.

**Inhalation:**

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney Effects: Signs/symptoms may include reduced or absent urine production, increased serum creatinine, lower back pain, increased protein in urine, and increased blood urea nitrogen (BUN).

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	> 610 °F
Flash Point	145 °F [ <i>Test Method:</i> Closed Cup]
Flammable Limits - LEL	0.99 %
Flammable Limits - UEL	7.26 %
OSHA Flammability Classification:	Class IIIA Combustible Liquid

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid prolonged or repeated skin contact. Avoid eye contact with vapors, mists, or spray. For industrial or professional use only. Avoid contact with oxidizing agents.

## 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from oxidizing agents.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide local exhaust ventilation at transfer points. Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles. (Goggles recommended when a splash potential exists.)

### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber.

### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
2-BUTOXYETHYL ACETATE	ACGIH	TWA	20 ppm	Table A3
2-BUTOXYETHYL ACETATE	CMRG	TWA	25 ppm	Skin Notation*
COPPER COMPOUNDS	ACGIH	TWA, as Cu dust or mist	1 mg/m3	
COPPER COMPOUNDS	OSHA	TWA, as dust or mist	1 mg/m3	Table Z-1A
CYCLOHEXANONE	ACGIH	TWA	20 ppm	Skin Notation*; Table A3
CYCLOHEXANONE	ACGIH	STEL	50 ppm	Skin Notation*; Table A3
CYCLOHEXANONE	OSHA	TWA, Vacated	25 ppm	Skin Notation*
CYCLOHEXANONE	OSHA	TWA	50 ppm	Table Z-1
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	3M	TWA	100 ppm	Skin Notation*
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	3M	STEL	150 ppm	Skin Notation*

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

**SOURCE OF EXPOSURE LIMIT DATA:**

ACGIH: American Conference of Governmental Industrial Hygienists  
 CMRG: Chemical Manufacturer Recommended Guideline  
 OSHA: Occupational Safety and Health Administration  
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Solvent Odor, Cyan Color
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	> 610 °F
<b>Flash Point</b>	145 °F [ <i>Test Method:</i> Closed Cup]
<b>Flammable Limits - LEL</b>	0.99 %
<b>Flammable Limits - UEL</b>	7.26 %
<b>Boiling point</b>	> 310 °F
<b>Density</b>	0.98 g/ml
<b>Vapor Density</b>	> 1 [ <i>Details:</i> Air = 1]
<b>Vapor Pressure</b>	< 1 mmHg [ <i>@ 20 °C</i> ]
<b>Specific Gravity</b>	0.98 [ <i>Details:</i> Water = 1]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Solubility in Water</b>	Moderate
<b>Volatile Organic Compounds</b>	907 g/l
<b>Percent volatile</b>	85 - 95 %
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	907 g/l

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:** Strong oxidizing agents

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste. Combustion products will include HCl. Facility must be capable of handling halogenated materials.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**  
75-3470-3007-6

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
-------------------	------------------	----------------

2-BUTOXYETHYL ACETATE (GLYCOL  
ETHERS) 112-07-2 50 - 60

## STATE REGULATIONS

Contact 3M for more information.

## CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health:** 1 **Flammability:** 2 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### Revision Changes:

Section 16: NFPA hazard classification heading was modified.  
Section 3: Other potential health effects heading was modified.  
Copyright was modified.  
Section 8: Exposure guidelines data source legend was modified.  
Section 3: Immediate physical hazard(s) was modified.  
Section 3: Potential effects from skin contact information was modified.  
Section 5: Fire fighting procedures information was modified.  
Section 5: Unusual fire and explosion hazard information was modified.  
Section 7: Handling information was modified.  
Section 7: Storage information was modified.  
Section 8: Engineering controls information was modified.  
Section 15: 311/312 hazard categories heading was modified.  
Section 15: International regulations information was modified.

Section 15: State regulations information was modified.  
Section 15: US federal regulations information was modified.  
Section 10: Hazardous polymerization heading was modified.  
Section 2: Ingredient table was modified.  
Section 3: Other health effects information was modified.  
Section 16: NFPA explanation was modified.  
Section 15: Inventories information was modified.  
Section 15: EPCRA 313 text was modified.  
Section 12: Ecotoxicological information heading was modified.  
Section 12: Chemical fate information heading was modified.  
Section 8: Exposure guidelines ingredient information was modified.  
Section 8: Exposure guidelines legend was modified.  
Section 8: Exposure guideline note was modified.  
Section 16: NFPA hazard classification for special hazards was modified.  
Section 2: Ingredient phrase was added.  
Section 12: Ecotoxicological phrase was added.  
Section 12: Chemical Fate phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**