



## Material Safety Data Sheet

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) SCREEN PRINTING INK 9714UV DARK GREEN  
**MANUFACTURER:** 3M  
**DIVISION:** Commercial Graphics

**ADDRESS:** 3M Center  
 St. Paul, MN 55144-1000

**EMERGENCY PHONE:** 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 02/05/2004  
**Supersedes Date:** 09/29/2003

**Document Group:** 11-7127-1

**Product Use:**  
 Specific Use: UV SCREEN PRINTING INK

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
VINYLCAPROLACTAM	2235-00-9	20 - 30
URETHANE ACRYLATE OLIGOMER	230302-77-9	20 - 30
2-PROPENOIC ACID,2-[[[BUTYLAMINO)CARBONYL]OXY]ETHYL ESTER	63225-53-6	7 - 13
ISOOCTYL ACRYLATE	29590-42-9	5 - 10
COPPER PHTHALOCYANINE GREEN	1328-53-6	5 - 10
AMINE ADDUCT (NJTSRN 04499600-6466)	Trade Secret	3 - 7
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	3 - 7
1,6-HEXANEDIOL DIACRYLATE	13048-33-4	3 - 7
2,2-DIMETHOXY-2-PHENYLACETOPHENONE	24650-42-8	1 - 5
VINYL CHLORIDE-VINYL ACETATE POLYMER	9003-22-9	1 - 5
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	41556-26-7	1 - 5
ALIPHATIC KETONE (NJTSRN 04499600-6466)	Trade Secret	1 - 5
POLY(DIMETHYLSILOXANE)	63148-62-9	0.5 - 1.5
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	82919-37-7	0.5 - 1.5
MICHLER'S KETONE	90-94-8	0.1 - 1
4-METHOXYPHENOL	150-76-5	0.1 - 1

## SECTION 3: HAZARDS IDENTIFICATION

### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** Dark green, acrylate odor

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Hazardous polymerization may occur. May cause severe eye irritation. May cause severe skin irritation. May cause allergic skin reaction. May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Skin Contact:**

Severe Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Inhalation:**

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney Effects: Signs/symptoms may include reduced or absent urine production, increased serum creatinine, lower back

pain, increased protein in urine, and increased blood urea nitrogen (BUN).

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
MICHLER'S KETONE	90-94-8	Anticipated human carcinogen	National Toxicology Program Carcinogens

**SECTION 4: FIRST AID MEASURES**

**4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**5.1 FLAMMABLE PROPERTIES**

<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 200 °F [ <i>Test Method:</i> Tagliabue Closed Cup]
<b>Flammable Limits - LEL</b>	<i>No Data Available</i>
<b>Flammable Limits - UEL</b>	<i>No Data Available</i>
<b>OSHA Flammability Classification:</b>	Class IIIB Combustible Liquid

**5.2 EXTINGUISHING MEDIA**

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

**5.3 PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Not applicable. Non-flammable: ordinary combustible material.

**Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.**

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. Avoid breathing of vapors, mists or spray. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. For industrial or professional use only. Avoid contact with oxidizing agents. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment.

### 7.2 STORAGE

Store out of direct sunlight. Store away from oxidizing agents. Keep container in well-ventilated area. Store away from heat.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray. Avoid eye contact. The following eye protection(s) are recommended: Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber, Polyethylene/Ethylene Vinyl Alcohol.

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

**8.2.4 Prevention of Swallowing**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

**8.3 EXPOSURE GUIDELINES**

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
1,6-HEXANEDIOL DIACRYLATE	AIHA	TWA	1 mg/m3	Sensitizer
4-METHOXYPHENOL	ACGIH	TWA	5 mg/m3	
4-METHOXYPHENOL	OSHA	TWA	5 mg/m3	Table Z-1A
ANTIMONY COMPOUNDS	ACGIH	TWA - specific form	0.5 mg/m3	as Sb
ANTIMONY COMPOUNDS	OSHA	TWA - specific form	0.5 mg/m3	as Sb; Table Z-1A
ALIPHATIC KETONE (NJTSRN 04499600-6466)	AIHA	TWA	0.5 mg/m3	
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	CMRG	TWA	1 mg/m3	
COPPER COMPOUNDS	ACGIH	TWA - specific form	1 mg/m3	as Cu dust or mist
COPPER COMPOUNDS	OSHA	TWA - specific form	1 mg/m3	as dust or mist; Table Z-1A
ISOOCTYL ACRYLATE	3M	TWA	5 ppm	
ISOOCTYL ACRYLATE	AIHA	TWA	5 ppm	
MERCURY NON-ALKYL, VAPOR	ACGIH	TWA - specific form	0.05 mg/m3	as Hg; Skin Notation*
MERCURY NON-ALKYL, VAPOR	OSHA	TWA - specific form	0.05 mg/m3	as Hg; Skin Notation*;Table Z-1A
MERCURY, ARYL & INORGANIC COMPOUNDS	OSHA	CEIL - specific form	0.1 mg/m3	as Hg; Skin Notation*;Table Z-1A
MERCURY, INORGANIC COMPOUNDS	ACGIH	TWA - specific form	0.025 mg/m3	as Hg; Skin Notation*;Table A4
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	CMRG	TWA	1 mg/m3	
SELENIUM COMPOUNDS	ACGIH	TWA - specific form	0.2 mg/m3	as Se
SELENIUM COMPOUNDS	OSHA	TWA - specific form	0.2 mg/m3	as Se; Table Z-1
VINYLCAPROLACTAM	3M	TWA	0.1 ppm	

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

**SOURCE OF EXPOSURE LIMIT DATA:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Guideline
- OSHA: Occupational Safety and Health Administration
- AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Odor, Color, Grade:</b>	Dark green, acrylate odor
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 200 °F [ <i>Test Method:</i> Tagliabue Closed Cup]
<b>Flammable Limits - LEL</b>	<i>No Data Available</i>
<b>Flammable Limits - UEL</b>	<i>No Data Available</i>
<b>Boiling point</b>	> 200 °F
<b>Density</b>	1.3 g/ml
<b>Vapor Density</b>	>=1 [ <i>Ref Std:</i> AIR=1]
<b>Vapor Pressure</b>	< 10 mmHg [@ 20 °C]
<b>Specific Gravity</b>	1.3 [ <i>Test Method:</i> ASTM METHOD] [ <i>Ref Std:</i> WATER=1]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Solubility in Water</b>	Moderate
<b>Evaporation rate</b>	<=1 [ <i>Ref Std:</i> BUOAC=1]
<b>Volatile Organic Compounds</b>	< 5 g/l
<b>Percent volatile</b>	<i>Not Applicable</i>
<b>VOC Less H2O &amp; Exempt Solvents</b>	< 5 g/l
<b>Viscosity</b>	1000 - 5500 centipoise [ <i>Test Method:</i> ASTM METHOD]

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable.

**Materials and Conditions to Avoid:** Strong oxidizing agents; Heat  
Additional Information: Ultraviolet light and metal containers.

**Hazardous Polymerization:** Hazardous polymerization may occur. upon depletion of inhibitor or exposure to heat.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

**SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

**SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION**

Not determined.

**CHEMICAL FATE INFORMATION**

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of waste product in a permitted hazardous waste facility.

Since regulations vary, consult applicable regulations or authorities before disposal.

**SECTION 14: TRANSPORT INFORMATION**

**ID Number(s):**  
75-3466-8568-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

**SECTION 15: REGULATORY INFORMATION**

**US FEDERAL REGULATIONS**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
DIETHYLENE GLYCOL ETHYL ETHER	7328-17-8	3 - 7
ACRYLATE (GLYCOL ETHERS)		
MICHLER'S KETONE	90-94-8	0.1 - 1

## STATE REGULATIONS

Contact 3M for more information.

## CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
MICHLER'S KETONE	90-94-8	**Carcinogen

\*\* WARNING: contains a chemical which can cause cancer.

## CHEMICAL INVENTORIES

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**Additional Information:** Non-photochemically reactive per SCAQMD Rule 102. New Jersey registry # 04499600-6466 \* Non-hazardous per WHMIS

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

Health: 3 Flammability: 1 Reactivity: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to

be generated in significant quantities.

Revision Changes:

Copyright was modified.

Section 5: Fire fighting procedures information was modified.

Section 7: Storage information was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 10: Materials and conditions to avoid physical property was modified.

Section 10: Hazardous polymerization physical property was modified.

Section 9: Vapor pressure value was modified.

Section 9: Boiling point information was modified.

Section 5: Flash point information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Flash point information was modified.

Section 3: Hazardous Polymerization information was added.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**