

MATERIAL SAFETY 3M
 DATA SHEET 3M Center
 St. Paul, Minnesota
 55144-1000
 1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.
 All rights reserved. Copying and/or downloading of this
 information for the purpose of properly utilizing 3M products
 is allowed provided that:

- 1) the information is copied in full with no changes unless
 prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise
 distributed with the intention of earning a profit thereon.

DIVISION: COMMERCIAL GRAPHICS

TRADE NAME:

3M(TM) SCREEN PRINTING INK 9720 GLOSS CLEAR

ID NUMBER/U.P.C.:

75-3466-8571-4 00-51128-34153-7 75-3466-8572-2 00-51128-34154-4

ISSUED: December 10, 2001

SUPERSEDES: April 19, 2001

DOCUMENT: 11-4012-8

1. INGREDIENT	C.A.S. NO.	PERCENT
URETHANE ACRYLATE OLIGOMER.....	230302-77-9	30.0 - 40.0
VINYLCAPROLACTAM.....	2235-00-9	10.0 - 20.0
2-PROPENOIC ACID, 2-		
[[(BUTYLAMINO) CARBONYL] OXY] ETHYL ESTER	63225-53-6	10.0 - 20.0
1,6-HEXANEDIOL DIACRYLATE.....	13048-33-4	5.0 - 10.0
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE..	7328-17-8	5.0 - 10.0
ISOCTYL ACRYLATE.....	29590-42-9	3.0 - 7.0
CYCLOALIPHATIC KETONE.....	TradeSecret	1.0 - 5.0
BIS(1,2,2,6,6-PENTAMETHYL-4-		
PIPERIDINYL) SEBACATE.....	41556-26-7	1.0 - 5.0
FLUOROALIPHATIC POLYMERIC ESTERS		
+(5050P).....	TradeSecret	1.0 - 5.0
ETHYL ACETATE.....	141-78-6	1.0 - 5.0
POLY(DIMETHYLSILOXANE).....	63148-62-9	0.5 - 1.5
POLYETHER.....	104810-48-2	0.5 - 1.5
POLYETHER.....	104810-47-1	0.5 - 1.5
METHYL 1,2,2,6,6-PENTAMETHYL-4-		
PIPERIDINYL SEBACATE.....	82919-37-7	0.1 - 1.0

Non-photochemically reactive per SCAQMD Rule 102.

New Jersey registry #04499600-6469

* Non-hazardous per WHMIS

This product contains the following toxic chemical or chemicals subject to
 the reporting requirements of Section 313 of Title III of the Emergency
 Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

2. PHYSICAL DATA

BOILING POINT:..... ca. 205 F
VAPOR PRESSURE:..... < 10 mmHg
VAPOR DENSITY:..... > 1 Air=1
EVAPORATION RATE:..... < 1 BuOAc=1
SOLUBILITY IN WATER:..... moderate
SPECIFIC GRAVITY:..... ca. 1.3 Water=1 ASTM
PERCENT VOLATILE:..... N/A
pH:..... N/A
VISCOSITY:..... 1000 - 5500 centipoise ASTM
MELTING POINT:..... N/D

APPEARANCE AND ODOR:
liquid, amber, acrylate odor

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... > 200 F TCC
FLAMMABLE LIMITS - LEL:..... N/D
FLAMMABLE LIMITS - UEL:..... N/D
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:
Water spray, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:
Wear full protective clothing, including helmet, self-contained,
positive pressure or pressure demand breathing apparatus, bunker coat
and pants, bands around arms, waist and legs, face mask, and
protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
Not determined.

NFPA HAZARD CODES: HEALTH: 3 FIRE: 1 REACTIVITY: 1
UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Class IIIB Combustible Liquid

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:
Strong Oxidizing Agents

Ultraviolet light and metal containers.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

4. REACTIVITY DATA (continued)

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Oxides of Nitrogen.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Observe precautions from other sections. Ventilate area. Contain spill. Cover with absorbent material. Collect spilled material. Clean up residue with water. Place in a closed container.

RECOMMENDED DISPOSAL:

Incinerate in an industrial or commercial facility in the presence of a combustibile material. Combustion products will include HCl. Disposal alternative: Dispose of waste product in a facility permitted to accept chemical waste.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 16 gms/liter.
VOC Less H2O & Exempt Solvents: ca. 16 gms/liter.

Since regulations vary, consult applicable regulations or authorities before disposal. In the event of an uncontrolled release of this material, the user should determine if the release qualifies as a reportable quantity. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

SKIN CONTACT:

Immediately flush skin with large amounts of water. Remove contaminated clothing. If irritation persists, call a physician. Wash contaminated clothing before reuse. Do not use solvents to remove material from skin or clothing.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST AID (continued)

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

Avoid eye contact. Wear unvented goggles during operations in which exposure is likely.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: nitrile rubber, polyethylene/ethylene vinyl alcohol. Use one or more of the following personal protection items as necessary to prevent skin contact: apron, coveralls.

RECOMMENDED VENTILATION:

Use with appropriate local exhaust ventilation. Curing ovens must be exhausted to outdoors or to a suitable emission control device. Provide appropriate local exhaust ventilation on open containers. Use in a well-ventilated area. If exhaust ventilation is not adequate, use appropriate respiratory protection.

RESPIRATORY PROTECTION:

Avoid breathing of vapors created during the cure cycle. Avoid prolonged breathing of vapors. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator, full-face organic vapor respirator.

PREVENTION OF ACCIDENTAL INGESTION:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Wash hands after handling and before eating.

RECOMMENDED STORAGE:

Store in a cool place. Store away from acids. Store away from heat. Store out of direct sunlight. Keep container dry. Keep container closed when not in use. Keep container in well-ventilated area.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

 7. PRECAUTIONARY INFORMATION (continued)

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition. Explosive when mixed with oxidizing substance.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
URETHANE ACRYLATE OLIGOMER.....	NONE	NONE	NONE	NONE	
VINYLCAPROLACTAM.....	0.1	PPM	TWA	3M	
2-PROPENOIC ACID,2- [[(BUTYLAMINO)CARBONYL]OXY]ETHYL ESTER.....	NONE	NONE	NONE	NONE	
1,6-HEXANEDIOL DIACRYLATE.....	1	MG/M3	TWA	AIHA	
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE.....	NONE	NONE	NONE	NONE	
ISOOCTYL ACRYLATE.....	5	PPM	TWA	AIHA	
ISOOCTYL ACRYLATE.....	5	PPM	TWA	3M	
CYCLOALIPHATIC KETONE.....	NONE	NONE	NONE	NONE	
BIS(1,2,2,6,6-PENTAMETHYL-4- PIPERIDINYL) SEBACATE.....	1	MG/M3	TWA	CMRG	
FLUOROALIPHATIC POLYMERIC ESTERS +(5050P).....	NONE	NONE	NONE	NONE	
ETHYL ACETATE.....	400	PPM	TWA	ACGIH	
ETHYL ACETATE.....	400	PPM	TWA	OSHA	
POLY(DIMETHYLSILOXANE).....	NONE	NONE	NONE	NONE	
POLYETHER.....	NONE	NONE	NONE	NONE	
POLYETHER.....	NONE	NONE	NONE	NONE	
METHYL 1,2,2,6,6-PENTAMETHYL-4- PIPERIDINYL SEBACATE.....	1	MG/M3	TWA	CMRG	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- 3M: 3M Recommended Exposure Guidelines
- ACGIH: American Conference of Governmental Industrial Hygienists
- AIHA: American Industrial Hygiene Assoc. Workplace Environmental Exposure Level Guideline
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- NONE: None Established

 Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA

EYE CONTACT:

Single exposure may cause:

Severe Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, cloudy appearance of the cornea, impaired vision and possible permanently impaired vision.

SKIN CONTACT:

Allergic Skin Reaction: signs/symptoms can include redness, swelling, blistering, and itching.

Single exposure may cause:

Severe Skin Irritation: signs/symptoms can include redness, swelling, itching, dryness, cracking, blistering, and pain.

INHALATION:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Liver Effects: signs/symptoms can include yellow skin(jaundice) and tenderness of upper abdomen.

IF SWALLOWED:

Esophageal Burns: signs/symptoms can include pain in throat, difficult swallowing and blood in sputum.

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue, blurred vision, slurred speech, giddiness, tremors and convulsions.

REPRODUCTIVE/DEVELOPMENTAL TOXINS:

POLY(OXY-1,2-ETHANEDIYL).,ALPHA.-[3-[3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXYPHENYL]-1-OXOPROPYL]-.OMEGA .-[3-[-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXYPHENYL]-1-OXOPROPOXY]-(104810-47-1) is a potential reproductive hazard causing

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

8. HEALTH HAZARD DATA (continued)

decreased number of live pups due to increased resorption and presence of stillborns.

POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-[3-[3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXYPHENYL]-1-OXOPROPYL]-.OMEGA.-HY DROXY (104810-48-2) is a potential reproductive hazard causing decreased number of live pups due to increased resorption and presence of stillborns.

SECTION CHANGE DATES

HEADING	SECTION CHANGED SINCE	April 19, 2001	ISSUE
INGREDIENTS	SECTION CHANGED SINCE	April 19, 2001	ISSUE
PHYSICAL DATA	SECTION CHANGED SINCE	April 19, 2001	ISSUE
REACTIVITY DATA	SECTION CHANGED SINCE	April 19, 2001	ISSUE
ENVIRONMENTAL INFO.	SECTION CHANGED SINCE	April 19, 2001	ISSUE
SUGG. FIRST AID	SECTION CHANGED SINCE	April 19, 2001	ISSUE
PRECAUTIONARY INFO.	SECTION CHANGED SINCE	April 19, 2001	ISSUE
HEALTH HAZARD DATA	SECTION CHANGED SINCE	April 19, 2001	ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.