



MATERIAL SAFETY DATA SHEET

SECTION 1 — IDENTIFICATION

Product identifier: Expert® Hold Tight Adhesive

Product Number: 1077

CAS Number: Mixture See Section 2.

Product Family: Aerosol Adhesive

HMIS: Health 2 Reactivity 0 Flammability 4

NFPA Rating as an Aerosol: Level 3

Medical Emergency: 1-800-633-9576

INFOTRAC: 1-800-535-5053

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

SECTION 2 — HAZARDOUS COMPONENTS

COMPONENT NAME(S)	EXPOSURE LIMITS CAS NO.	CONCENTRATION (%)
Heptane	142-82-5	30-35
Acetone	67-64-1	20-25
Propane	74-98-6	20-25
Butane	106-97-8	5-10
Pentane	109-66-0	5-10

SECTION 3 — HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW:

DANGER! Extremely Flammable. Contents under pressure. Mist or vapour may irritate the eyes, mucous membranes, and respiratory tract. **ASPIRATION** into the lungs may cause pulmonary edema and chemical pneumonia. Product may be harmful or fatal if inhaled.

Major Route(s) of Entry: Inhalation, Eye contact, Skin contact.

Signs and symptoms of Acute Exposure

EYE CONTACT: Considered as an eye irritant. May cause stinging, watering, swelling, and redness. Vapors may irritate eyes. Slight corneal injury could occur.

SKIN CONTACT: Prolonged or repeated exposure may cause severe skin irritation, even a burn. Repeated contact may cause drying and flaking of skin. May cause allergic skin reaction in susceptible individuals. Chronic symptoms may include dryness, swelling, scaling, blistering, cracking, and severe tissue damage.

SKIN ABSORPTION: A single prolonged skin exposure is not likely to result in harmful amounts, but this product may be readily absorbed through the skin and produce CNS depression.

INGESTION: **ASPIRATION HAZARD.** Aspiration of this material into the lungs can cause chemical pneumonitis which can be fatal. Is aspirated, it may be rapidly absorbed through the lungs and result in injury to other body

systems. May cause weakness and gastrointestinal tract irritation. May irritate the mucous membranes of the mouth, throat, and esophagus. It can be readily absorbed through the stomach and intestinal tract. Symptoms include a burning sensation of the mouth, and esophagus, nausea, vomiting, dizziness, staggering gait, drowsiness, loss of consciousness and delirium. Additional central nervous system effects may occur prior to the onset of convulsions, coma and death.

INHALATION: Breathing high concentrations of vapour may cause respiratory irritation, euphoria, excitation, or giddiness, headache, nausea, vomiting, abdominal pain, loss of appetite, fatigue muscular weakness, staggering gait, and CNS depression, (which includes dizziness, drowsiness, disorientation, vertigo, memory loss, visual disturbances, difficulty with breathing, convulsions unconsciousness, paralysis, coma, and even death). Irritation may occur to the mucous membranes of the respiratory tract. A loss of appetite, lassitude, light-headedness, in-coordination, respiratory arrest, convulsions, semi-consciousness may result from extreme exposure.

CHRONIC HEALTH EFFECTS SUMMARY: Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung disfunction.

CONDITIONS AGGRAVATED BY EXPOSURE: Personnel with pre-existing central nervous system diseases, neurological conditions, skin disorders, impaired liver or kidney function, or chronic respiratory diseases.

TARGET ORGANS: This substance is toxic to lungs, central nervous system, brain, mucous membranes, skin, eyes, and possibly, the blood, liver, and kidneys.

CARCINOGENIC POTENTIAL: This material does not contain any components at concentrations above 0.1% which are considered to be carcinogenic by OSHA, IARC, or NTP.

OSHA Health Hazard Classification		OSHA Physical Hazard Classification		
Irritant X	Toxic	Combustible	Explosive X	Pyrophoric
Sensitizer	Highly toxic	Flammable X	Oxidizer	Water-Reactive
Corrosive	Carcinogenic	Compressed Gas X	Organic Peroxide	Unstable

SECTION 4 — FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

EYE CONTACT: Flush with large amounts of water, occasionally lifting upper and lower eyelids. Get medical attention.

SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing and launder it before reuse. Should any irritation persist, get medical attention.

INHALATION: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Get medical attention.

INGESTION: Ingestion is not considered a potential route of exposure as an aerosol but, is swallowed, **do not induce vomiting**. If spontaneous vomiting is about to occur, place victims head between their knees to prevent aspiration. Call a physician or transport to an emergency facility.

SECTION 5 — FIRE FIGHTING MEASURES

NFPA Flammability Classification: LEVEL 1 Aerosol

FLASH POINT: Not Determined **FLAMMABLE LIMITS:** UEL 12.8% LEL 1.2%

EXTINGUISHING MEDIUM: AS APPROPRIATE FOR COMBUSTIBLE AREA.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires containing or around this product. Shut off all sources of ignition, if possible. Keep exposed containers cool with

water spray to prevent rupture. Evacuate all non-trained personnel. Wear full protective clothing, including helmet. Ventilate area. Contain spill and dike, if possible. For leaks or spills water spray can be used to disperse and flammable vapors that may become concentrated or form in poorly ventilated areas and to protect personnel attempting to stop the leak.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should wear SCBA's in a positive pressure mode with full face shield. Vapors are heavier than air and may travel long distances and accumulate in low areas or spread along ground from handling site. Eliminate all sources of ignition. Never use welding or cutting torch on or near this product because even just residue can ignite explosively.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.

Ventilate area-especially low places where heavy vapors might collect. Extinguish all ignition sources. For small spills/leaks mop, wipe, or soak up on an inorganic material immediately. Remove to vent hood or outside. For large spills/leaks evacuate area, contain spill (dike area), and transfer contained liquid to a DOT approved container for disposal. Keep out of water supply. Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personnel protective equipment.

SECTION 7 — ENVIRONMENTAL AND DISPOSAL INFORMATION

Store in tightly sealed containers. Keep away from heat, sparks & open flame. Do not get in eyes, on skin or clothing. Do not breathe vapour, mist or gas. Do not store or transfer to an unmarked container. Do not throw empty containers in trash compactor. Do not store in direct sun. Store containers below 120°F. Read label before using.

SECTION 8 — EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS: Control airborne concentrations below the exposure limits see below. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PERSONAL PROTECTIVE EQUIPMENT: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. Minimum requirements are: SAFETY GLASSES and GLOVES.

RESPIRATORY PROTECTION (SPECIFY TYPE): If workplace exposure limit(s) of product or any component is exceeded (see Section two), a NIOSH approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION: For brief contact, no precautions should be needed. When prolonged or frequently repeated contact could occur, use protective gloves such as; polyvinyl alcohol or polyethylene.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; OSHA regulations also permit other type of safety glasses (consult your safety equipment supplier).

BODY PROTECTION: To prevent repeated or prolonged skin contact, use protective clothing impervious to this

Hazard characteristics and regulatory waste stream classification can change with product use. It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

When disposing of unused contents, the preferred options are to send to licensed reclaimers or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local laws and regulations. Do not dump into sewers, on the ground, or into any body of water.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14 — TRANSPORT INFORMATION

DOT STATUS: This material is regulated by the U.S. Department of Transportation (DOT).

PROPER SHIPPING NAME: (to ship on the ocean):
Aerosols, Flammable (each not exceeding 1L capacity), 2.1 UN1950, LTD. QTY

HAZARD CLASS: 2.1

PACKING GROUPS: UN190

PLACARDS: None Required

EMERGENCY RESPONSE GUIDE NO: 126

SECTION 15 — REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS: Listed

311/312 HAZARD CATEGORIES:

Fire Hazard: Yes Pressure Hazard: Yes Reactivity Hazard: Yes Immediate Hazard: No Delayed Hazard: No

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III:

CHEMICAL	CAS NUMBER	CONCENTRATION %
None Listed		

FEDERAL EPA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

(CERCLA) requires the notification of the National Response Center of release of quantities of hazardous substances equal to or greater than the reportable quantities (rqs) in 40 CFR 302.4.

CHEMICAL	CAS NUMBER	CONCENTRATION % UPPER BOUND	RQs IN #
Acetone	67-64-1	20-25	5000

CALIFORNIA PROPOSITION 65: None listed.

MASSACHUSETTS RIGHT TO KNOW: Yes

Heptane	142-82-5	30-35
Acetone	67-64-1	20-25
Propane	74-98-6	20-25
Butane	106-97-8	5-10
Pentane	109-66-0	5-10

PENNSYLVANIA RIGHT TO KNOW: Yes

Heptane	142-82-5	30-35
Acetone	67-64-1	20-25
Propane	74-98-6	20-25
Butane	106-97-8	5-10

Pentane	109-66-0	5-10
NEW JERSEY RIGHT TO KNOW: Yes		
Heptane	142-82-5	30-35
Acetone	67-64-1	20-25
Propane	74-98-6	20-25
Butane	106-97-8	5-10
Pentane	109-66-0	5-10

SECTION 16 — OTHER INFORMATION

ABBREVIATIONS:

N/A: Not Applicable

N/D: Not Determined

NE: Not Established

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

HMIS: Hazardous Materials Information System NFPA: National Fire Protection Association EPA: US Environmental Protection Agency

NIOSH: National Institute of Occupational Safety and Health

Prepared by: Albatross USA Inc.

Telephone number: 718-392-6272

Preparation Date: February 14, 2003

Revision Date: April 1, 2005

NOTICE:

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or to be implied regarding the accuracy or completeness of this information or the product, the safety of this product, or the hazards related to its use. This information and product are furnished "as is" and on the condition that the personal receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.