

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : CAWIE 888 SILICONE MOLD RELEASE DATE PRINTED: 01/26/00
 IDENTIFICATION NUMBER: FCR0888
 PRODUCT USE/CLASS :

SUPPLIER: Camie-Campbell
 9225 Watson Industrial Park
 St. Louis, MO 63126

MANUFACTURER: Camie-Campbell
 9225 Watson Industrial Park
 St. Louis, MO 63126

EMERGENCY TELEPHONE: 800-424-9300 EMERGENCY TELEPHONE: 800-424-9300
 24 HOUR EMERGENCY PHONE 24 HOUR EMERGENCY PHONE

PREPARED: JLM, PHONE: 314/968-3222, PREPARE DATE: 01/26/00
 REPLACES DATE: 01/28/97

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT %
01	DICHLOROMETHANE	75-09-2	70.0 %
02	ISOBUTANE	75-28-5	25.0 %
03	PROPANE	74-98-6	15.0 %

ITEM	TLV-TWA	ACGIH	TLV-STEL	PEL-TWA	OSHA	PEL-CEILING	COMPANY	TLV-TWA	SKIN

[See Section 16 for abbreviation legend]

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: KEEP FROM REACH OF CHILDREN. DO NOT PUNCTURE, INCINERATE, OR PLACE AEROSOL PRODUCT CONTAINERS IN COMPACTORS. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED. DO NOT FLAME CUT, BRAZE, OR USE WELDING TORCH. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.

(Continued on Page 2)

Product: FCR0888

Preparation Date: 01/26/00

Page 2

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION DEFATTING, DERMATITIS.

EFFECTS OF OVEREXPOSURE - INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEARINESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, AND EVEN ASPHYXATION. METHYLENE CHLORIDE CAN RAISE THE LEVEL OF CARBON MONOXIDE IN THE BLOOD CAUSING CARDIOVASCULAR STRESS.

EFFECTS OF OVEREXPOSURE - INGESTION: No Information.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: METHYLENE CHLORIDE IS LISTED AS A POTENTIAL CARCINOGEN BY IARC (2B) AND NTP IN EXPERIMENTAL ANIMALS. OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS APPARENTLY BEEN FOUND TO CAUSE THE FOLLOWING EFFECTS IN LABORATORY ANIMALS: KIDNEY DAMAGE, LIVER DAMAGE, LUNG DAMAGE,

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE, GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

FIRST AID - INHALATION: REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. GIVE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. KEEP PERSON WARM AND QUIET. GET MEDICAL ATTENTION.

FIRST AID - INGESTION: DO NOT INDUCE VOMITING. GIVE TWO GLASSES OF WATER IF CONSCIOUS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: -156 F LOWER EXPLOSIVE LIMIT: 1.8 %
 (PENSKY-WARTENS C.C.) UPPER EXPLOSIVE LIMIT: 25.0 %

AUTOIGNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT. FOR AEROSOL PRODUCTS - EXPOSURE TO TEMPERATURES OVER 130F MAY CAUSE CONTAINERS TO BURST, RELEASING HIGHLY FLAMMABLE GAS. VAPORS CAN IGNITE OR DECOMPOSE FROM

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

EXTREMELY HIGH INTENSITY IGNITION SOURCE LIBERATING TOXIC GASES.

SPECIAL FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER FOG.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION & VENTILATE AREA. PERSONS NOT PROPERLY EQUIPPED SHOULD BE EXCLUDED FROM AREA. STOP SPILL AT SOURCE - PREVENT SPREADING. AVOID INHALATION OF VAPORS. AVOID SKIN CONTACT WITH LIQUID. SOAK UP ON ABSORBENT MATERIAL AND PLACE INTO PROPER CONTAINER FOR DISPOSAL. USE NON-SPARKING SCOOPS FOR FLAMMABLE MATERIALS. CLEAN WALKING SURFACES THOROUGHLY TO REDUCE SLIPPING HAZARD.

SECTION 7 - HANDLING AND STORAGE

HANDLING: DO NOT TRANSFER TO PLASTIC, RUBBER, OR ALUMINUM CONTAINER. STORAGE: DO NOT STORE ABOVE 120F. DO NOT STORE IN DIRECT SUNLIGHT. KEEP AWAY FROM HEAT SOURCES, OPEN FLAME, SPARKS. DO NOT STORE ABOVE 120F. DO NOT STORE IN DIRECT SUNLIGHT.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: PROVIDE SUFFICIENT MECHANICAL VENTILATION (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). RESPIRATORY PROTECTION: IF WORK PLACE EXPOSURE LIMITS OF PRODUCT OR ANY COMPONENT IS EXCEEDED, USE A NIOSH/MSHA APPROVED RESPIRATOR. CONSULT YOUR SAFETY EQUIPMENT SUPPLIER FOR RECOMMENDATIONS. CARTRIDGE TYPE RESPIRATORS ARE NOT ACCEPTABLE TO PROTECT AGAINST METHYLENE CHLORIDE EXPOSURE EXCEPT AS EMERGENCY ESCAPE RESPIRATORS. AIR SUPPLIED RESPIRATORS ARE REQUIRED BY OSHA WHEN METHYLENE CHLORIDE EXPOSURES EXCEED THEIR PERMISSIBLE EXPOSURE LIMITS OR SHORT TERM EXPOSURE LIMITS.

SKIN PROTECTION: WEAR IMPERVIOUS GLOVES IF METHOD OF USE INVOLVES SKIN CONTACT WITH PRODUCT. CONSULT YOUR SAFETY SUPPLY VENDOR FOR GLOVE RECOMMENDATIONS.

EYE PROTECTION: WEAR SAFETY GLASSES AT MINIMUM. MORE EXTENSIVE PROTECTION MAY BE NECESSARY DEPENDING ON HOW THE PRODUCT IS TO BE USED.

OTHER PROTECTIVE EQUIPMENT: WEAR IMPERVIOUS CLOTHING IF BODILY EXPOSURE IS ANTICIPATED. CONSULT YOUR SAFETY SUPPLY VENDOR FOR RECOMMENDATIONS.

(Continued on Page 4)

SECTION 9 - EXPOSURE CONTROLS/PERSONAL PROTECTION

HYGIENIC PRACTICES: WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY. REMOVE AND LAUNDRY CLOTHING IF CONTAMINATED.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : -44 - 400 F VAPOR DENSITY : Is heavier than air
ODOR : SWEET ETHER-LIKE ODOR THRESHOLD : N.D.
APPEARANCE : CLEAR LIQUID EVAPORATION RATE: Is faster than Butyl
SOLUBILITY IN H2O : NEGLIGIBLE
FREEZE POINT : N.D.
VAPOR PRESSURE : N.D. SPECIFIC GRAVITY: 0.9018 Acetate
PH @ 0.0 % : N.D.
PHYSICAL STATE : LIQUID VISCOSITY : N.D.
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.
(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: HEAT, SPARKS, WELDING ARCS, OPEN FLAME, STATIC ELECTRICITY, OR OTHER SOURCE OF IGNITION. EXCESSIVE HEAT WHICH MAY CAUSE GENERATION OF FORMALDEHYDE.

INCOMPATIBILITY: ALUMINUM, ALKALI, HIGHLY REACTIVE METALS, MAGNESIUM, ZINC, WATER, NITROGEN PEROXIDE, SODIUM, POTASSIUM, STRONG OXIDIZERS,

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND CARBON DIOXIDE. HYDROGEN CHLORIDE, PHOSGENE, CHLORINE, POSSIBLY SILICON DIOXIDE, THIS PRODUCT CONTAINS METHYLPOLYSILOXANES WHICH CAN GENERATE FORMALDEHYDE AT APPROXIMATELY 300 DEGREES FARENHEIT AND ABOVE, IN ATMOSPHERES WHICH CONTAIN OXYGEN.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

(Continued on Page 5)

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Aerosols

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

HAZARD SUBCLASS: NONE

DOT UN/NA NUMBER: UN1950 PACKING GROUP: NONE RESP. GUIDE PAGE: 126

ADDITIONAL INFORMATION: FOR DOMESTIC GROUND AND AIR SHIPMENT THIS PRODUCT MAY BE SHIPPED AS A CONSUMER COMMODITY ORM-D. OUTER CARTONS MUST HAVE THE ORM-D OR ORM-D AIR DESIGNATION. OUR ORIGINAL CARTONS ARE PREPRINTED WITH THE ORM-D DESIGNATION FOR GROUND SHIPMENT.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
DICHLOPOMETHANE 75-09-2 70.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

: ON JANUARY 10TH OSHA PUBLISHED A FINAL STANDARD FOR EXPOSURE TO METHYLENE CHLORIDE. THE FINAL RULE BECOMES EFFECTIVE APRIL 10, 1997. THE NEW ACTION LIMIT FOR METHYLENE CHLORIDE IS 12.5ppm, THE PEL IS 25ppm AND THERE IS A STEL OF 125ppm FOR A 15 MINUTE PERIOD.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/28/97

REASON FOR REVISION: SCHEDULED UPDATE

VOLATILE BY WEIGHT: 97.3% VOLATILE BY VOLUME: 97.5%

VOC CONTENT: 32.5 % BY WEIGHT, 293 GRAMS/LITER TOTAL PRODUCT,
519 GRAMS/LITER LESS WATER AND EXEMPT, 0.37 LBS/CAN

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materials identification system have been included by Camie-Campbell Inc. in order to provide additional health and hazard classification information. The ratings recommend are based upon the criteria supplied by the developers of these rating systems, together with Camie-Campbell Inc.'s interpretation of the available data. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.

<END OF MSDS>