



ROEDER INDUSTRIES, INC.

[www.easiwayproducts.com](http://www.easiwayproducts.com)



# MATERIAL SAFETY DATA SHEET

Prepared February 5, 2002

## MANUFACTURER:

EASIWAY SYSTEMS INC.  
540 S River Street  
P.O. Box 70  
Delano, MN 55328

Business Phone: 1-763-972-6306  
Emergency Phone: 1-800-424-9300

## IMPORTANT:

Read this MSDS before handling and disposing of this product and pass this information on to employees, customers and users of this product.

## SECTION I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: EASISOLV 201  
PRODUCT USE: Screen Wash  
CLASS: Organic Solvent mixture  
DOT SHIPPING NAME: Cleaning Compound, N.O.I.  
Not DOT regulated

## HMIS

Health: 1  
Flammability: 1  
Reactivity: 0  
Personal Protection: B

## SECTION II - COMPONENTS

	CAS #	%	OSHA PEL	ACGIH TLV
Propylene Glycol Ethers	Mixture	<90%	None Estab.	None Estab.
None of the ingredients in this product are on the OSHA Hazardous Substance List or any individual State Hazardous Substance List.				

SARA - None of the ingredients are SARA reportable.

## SECTION III - PHYSICAL DATA

APPEARANCE & ODOR: Clear, colorless liquid - mild odor.  
BOILING POINT: 210°C.  
SPECIFIC GRAVITY: 1.02 @ 25°C.  
VAPOR PRESSURE: 0.09mm Hg @ 20°C.  
VAPOR DENSITY: Heavier than air.  
VOC: 900 grams per liter, 7.5 lb./gallon, by EPA Method 24.  
pH: Neutral.

## SECTION IV - FIRE OR EXPLOSION HAZARD

FLASHPOINT: 204°F Setaflash.  
EXTINGUISHING MEDIA: Regular foam or water fog or CO<sub>2</sub>, or dry chemical.  
UNUSUAL FIRE & EXPLOSION HAZARDS: None.  
FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.



ROEDER INDUSTRIES, INC.

[www.easiwayproducts.com](http://www.easiwayproducts.com)



EASISOLV 201

## SECTION V - REACTIVITY DATA

STABILITY: Stable under normal conditions of storage and handling. Avoid heat, sparks, and open flames.

INCOMPATIBILITY: Oxidizing or reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

---

## SECTION VI - HEALTH HAZARD DATA

ROUTE OF ENTRY: Inhalation, skin absorption and ingestion.

EFFECTS OF ACUTE EXPOSURE: Slight health hazard. Liquid contact can cause eye irritation and conjunctivitis; and skin irritation, dermatitis.

EFFECTS OF CHRONIC EXPOSURE: Repeated or prolonged exposure may cause irritation, redness, burning, drying and cracking of the skin.

CARCINOGENICITY: No

TERATOGENICITY: No

REPRODUCTIVE TOXICITY: No

MUTAGENICITY: No

---

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

PERSONAL PROTECTIVE EQUIPMENT: Wear safety glasses or goggles and nitrile gloves when handling. Keep containers closed when not in use. Provide adequate ventilation in work area. An organic vapor respirator should be worn if needed.

LEAK AND SPILLS PROCEDURE: Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Use sand or other inert material to dam and contain spill. For small spills, use absorbent pads.

WASTE DISPOSAL: Dispose of in accordance with local, county, state and federal regulations. Do not weld, cut, braze or drill drums that are empty.

---

## SECTION VIII - FIRST AID MEASURES

INHALATION (BREATHING): Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

EYE CONTACT: Irrigate immediately with water for at least fifteen minutes.

SKIN CONTACT: Wash off in flowing water. Wash contaminated clothing before reuse.

INGESTION (SWALLOWING): If large quantity swallowed, induce vomiting. Obtain medical attention.

---

## SECTION IX - ADDITIONAL INFORMATION

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

**Roeder Industries is an authorized distributor of Easiway Systems' products.**

Toll Free: 866-532-8324 Phone: (321) 567-0400 Fax: (321) 567-0401

[www.screenprintproducts.com](http://www.screenprintproducts.com) [www.embroiderysupplycompany.com](http://www.embroiderysupplycompany.com) [www.screenprintingparts.com](http://www.screenprintingparts.com)