

Enthone
Enthone Inc.
 P.O. Box 1900
 New Haven, CT 06508
 (203) 934-8611
 (203) 799-8179 Fax

Page: 1 / 5

Printed 2/12/2002.

Product Name **XX2019**

50-120R White (XX2019)

Distributed by:
NAZDAR
 8501 Hedge Lane Terrace
 Shawnee, KS 66227
 Phone: 800-677-4657
 www.nazdar.com

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

COMPANY IDENTIFICATION

ALPHA PC FAB/ENTHONE
 P.O. BOX 1900
 NEW HAVEN, CT 06508
 USA
 Phone: 1-203-934-8611
 Fax: 1-203-799-8179

EMERGENCY TELEPHONE NUMBERS

Transportation:
 Chemtrec, USA, 1-800-424-9300
 International: 1-703-527-3887
 After Hours Non Transportation
 Emergency: 1-800-399-6503

PRODUCT CODE

XX2019

PRODUCT DESCRIPTION

Resin and filler mixture.

GENERAL USE

Two component 50-Series Cat-I-Ink

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#
Epoxy Resin	10.000- 30.000	25068-38-6
Bisphenol A	5.000- 10.000	80-05-7
Diethylene Glyc Eth Ether Acet	10.000- 30.000	112-15-2
Dipropyl Glyc Mono Meth Ether	1.000- 5.000	34590-94-8
Prop Gly Mono Methyl Ether Aca	1.000- 5.000	108-65-6

DISCLOSURE:

This product is hazardous under the criteria of the USA OSHA Hazard Communication Standard 29 CFR 1910.1200.
 Any ingredient claimed as a trade secret will be disclosed in accordance with 29 CFR 1910.1200 (i).
 See Section 8 of this MSDS for any noted exposure limits for these compounds.

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Caution!

May be harmful if swallowed.
 May cause eye irritation.
 White, high viscosity liquid. Mild odor.

EYE CONTACT

Moderately irritating with redness, pain or tearing. Prolonged contact may cause burns.

SKIN CONTACT

Slightly irritating. Frequent or prolonged contact may irritate and cause a rash (dermatitis). Repeated exposure may cause allergic skin reactions. Once an allergy develops, even an exposure to a very small amount can trigger an allergic reaction.

INHALATION

Slightly irritating to the eyes, nose, throat and lungs.

INGESTION

Slightly irritating to the mouth, stomach and digestive tract. May cause vomiting.

PRIMARY ROUTE OF EXPOSURE

Skin contact, skin absorption, eye, inhalation, ingestion.

CARCINOGENICITY

IARC - Not Listed
 OSHA - Not Listed
 NTP - Not Listed

TARGET ORGANS

Ingredients may be toxic to the following organs:
 Skin, eyes, lungs, mucous membranes.

SECTION 4. FIRST AID MEASURES

EYE CONTACT

Flush eyes with flowing water for 10 to 15 minutes. Blink eyes frequently. Repeat flushing if burning or pain persists. Get immediate medical attention.

SKIN CONTACT

Rinse skin immediately with plenty of water. Then wash skin immediately with soap and water. Remove contaminated clothing. Do not apply lotions or creams without the advice of a physician or poison center. If problems persist get prompt medical attention.

INHALATION

Remove victim to fresh air. If breathing is difficult get immediate

Enthone
 Enthone Inc.
 P.O. Box 1900
 New Haven, CT 06508
 (203) 934-8611
 (203) 799-8179 Fax

Page: 2 / 5

Printed 2/12/2002.

Product Name XX2019

50-120R White (XX2019)

medical attention. If not breathing give artificial respiration and call for emergency medical assistance.

INGESTION

Do NOT induce vomiting. Rinse mouth with water and allow patient to drink as much water as desired. Contact a poison center or get prompt medical attention if symptoms of irritation persist.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT

188.00 F 86.66 C

FLASH METHOD

P.M.C.C.

EXTINGUISHING METHOD

Carbon dioxide, foam, dry chemicals, water spray or fog.

FIRE FIGHTING PROCEDURES

Wear self contained breathing apparatus (pressure-demand MSA/NIOSH or equivalent) and full fire fighting protective gear.

FIRE AND EXPLOSION HAZARDS

Heat in excess of flashpoint, open flame, or storage with incompatible materials as listed in Stability And Reactivity.

HAZARDOUS PRODUCTS/COMBUSTION

Carbon monoxide, carbon dioxide.

SECTION 6. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Remove ignition sources. Provide adequate ventilation and/or personal protective equipment (see Section 8). Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Prevent runoff to storm sewers, ditches and other pathways to soil and waterways.

SECTION 7. HANDLING AND STORAGE

HANDLING

Avoid breathing fumes. Do not splash or spill.

STORAGE

Do not store with incompatible materials. Store containers upright. Keep away from heat and flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Use local exhaust ventilation.

EYE PROTECTION

Wear safety glasses with side shields or a face shield.

SKIN PROTECTION

Wear chemical resistant rubber gloves and apron.

RESPIRATORY PROTECTION

No respirator is required if ingredient exposure limits are not exceeded. An OSHA approved (29 CFR 1910.134 USA Dept. of Labor), air purifying, half-face respirator with the appropriate cartridge should be used if exposure limits are exceeded.

OTHER PROTECTION

A safety shower and eye wash station should be within reasonable distance of the work area.

SUBSTANCE DESCRIPTION	EXPOSURE LIMITS/REGULATORY INFORMATION			
	REG. AGENCY	PELTL	STEL	CEIL
Epoxy Resin	OSHA	N/D	N/D	N/D
	ACGIH	N/D	N/D	N/D
Bisphenol A	OSHA	N/D	N/D	N/D
	ACGIH	N/D	N/D	N/D
Diethylene Glyc Eth Ether Acet	OSHA	N/D	N/D	N/D
	ACGIH	N/D	N/D	N/D
Dipropyl Glyc Mono Meth Ether	OSHA	100.0000	150.0000	N/D
	ACGIH	100.0000	150.0000	N/D
Prop Gly Mono Methyl Ether Ace	OSHA	N/D	N/D	N/D
	ACGIH	N/D	N/D	N/D

LEGEND:

EXPOSURE LIMIT DESCRIPTIONS

CEIL Ceiling Exposure Limit
 PELTL PEL/TLV
 STEL Short Term Exposure Limit

Page: 3 / 5

Printed 2/12/2002.

Product Name XX2019

50-120R White (XX2019)

Enthone
Enthone Inc.
 P.O. Box 1900
 New Haven, CT 06508
 (203) 934-8611
 (203) 799-8179 Fax

N/D = Not Determined

UNIT OF MEASURE

PPM Parts Per Million (Liquid)
 MG/M3 Milligrams Per Cubic Meter (Solid)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR

White, high viscosity liquid. Mild odor.

SPECIFIC GRAVITY

1.67

pH FACTOR

N/D

BOILING POINT

N/D F N/D C 320 - 370 deg. F

VOLATILE ORGANIC COMPOUNDS

VOC - %	32.7
VOC - g/L	411
VOC - lbs/Gal	3.43

SECTION 10. STABILITY AND REACTIVITY

INCOMPATIBILITIES

Oxidizing agents.

DECOMPOSITION

None

POLYMERIZATION

None.

CONDITIONS TO AVOID

Extreme temperatures.

STABILITY

Stable.

SECTION 11. TOXICOLOGICAL INFORMATION

EYE EFFECTS

Conjunctival irritation and redness. May cause corneal damage.

DERMAL EFFECTS

Slightly irritating. Absorption of toxic amounts through the skin is unlikely under ordinary conditions of industrial use.

INHALATION EFFECTS

Minor irritation of the mucous membranes and the upper respiratory tract. Systemic toxicity is very unlikely under ordinary conditions of industrial use.

The glycol ether in this product does not cause adverse effects on the male or female reproductive system.

INGESTION EFFECTS

Systemic effects are unlikely unless taken in massive amounts.

ACUTE TOXICITY DATA

Enthone is not aware of any toxicity data on the specific mixture of chemical components contained in this product. Data on the individual chemical components of this mixture is available in the literature or can be obtained by contacting Dexter's Health, Safety and Environmental department at the address and telephone number listed in Section 1.

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Enthone has not conducted specific studies on the eco toxicity or environmental fate of this product. Commonly available data on certain ingredients indicate that acute or chronic effects could result from uncontrolled releases to soil, ground water, storm waters, or air. Appropriate measures should be taken to prevent uncontrolled releases. Prompt containment and clean-up should be performed if releases do occur (see Section 6).

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable Federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.

It is recommended that the following priority hierarchy be used when selecting a disposal method: (1) Reuse or reintroduction into the process. (2) Reclamation, regeneration or recycling. (3) Burning for energy recovery, or incineration. (4) Treatment.

SECTION 14. TRANSPORT INFORMATION

Enthone
 Enthone Inc.
 P.O. Box 1900
 New Haven, CT 06508
 (203) 934-8611
 (203) 799-8179 Fax

Page: 4 / 5

Printed 2/12/2002.

Product Name **XX2019**

50-120R White (XX2019)

DOT/IATA PROPER SHIPPING NAME

Ink Materials
 DOT/IATA HAZARD CLASS
 Not Regulated
 DOT/IATA UN OR NA NUMBER
 Not Regulated
 DOT/IATA PACKING GROUP
 Not Regulated
 DOT/IATA LABEL
 None
 DOT/IATA PLACARD
 Not Regulated

SECTION 15. REGULATORY INFORMATION

Component Epoxy Resin is subject to the following

Environmental List

311/312 SARA Phy/Hea Haz (40CFR370.40)

Component Bisphenol A is subject to the following

Environmental List

311/312 SARA Phy/Hea Haz (40CFR370.40)
 313 SARA toxic chem (40CFR372.65)

Component Diethylene Glyc Eth is subject to the following

Environmental List

311/312 SARA Phy/Hea Haz (40CFR370.40)
 313 SARA toxic chem (40CFR372.65)

Component Dipropyl Glyc Mono M is subject to the following

Environmental List

311/312 SARA Phy/Hea Haz (40CFR370.40)

Component Prop Gly Mono Methyl is subject to the following

Environmental List

311/312 SARA Phy/Hea Haz (40CFR370.40)
 313 SARA toxic chem (40CFR372.65)

CALIFORNIA PROPOSITION 65

This product contains a chemical(s) known to the State of California to cause cancer.

SECTION 16. OTHER INFORMATION

HAZARDOUS MATERIALS ID. SYSTEM

HMIS		HAZARD RATING			
Health	2	Least	0	Slight	1
Fire	2	Moderate	2	High	3
Reactivity	1	Extreme	4		

WHMIS HAZARD CLASS

B3, D2B

REVISION NO.

002

REVISION DATE

10/20/1997

REVISION SECTION / REASON

Section 1 / PRODUCT NAME, GENERAL USE change

CREATED BY

HSE & R&D INDUSTRY, CALIF.

APPROVED BY

HSE - California

LIMITATIONS AND DISCLAIMER:

This MSDS relates only to the specific material identified in Section 2. In compiling this MSDS, Enthone has relied in good faith on information provided to Enthone by suppliers of the components of this material, and, in some cases, provided by independent data resources. Enthone has not independently verified such information, and, in addition, users should be aware that all materials may present unknown hazards. Use of this material in combination with other materials and/or in specific processes may render information set forth in this MSDS inaccurate or otherwise invalid.

NO WARRANTY, EXPRESS OR IMPLIED, IS MADE REGARDING THE INFORMATION FURNISHED ON THIS MSDS.

KEY TO ABBREVIATIONS:

Page: 5 / 5

Printed 2/12/2002.

Product Name XX2019

50-120R White (XX2019)

Enthone
Enthone Inc.
P.O. Box 1900
New Haven, CT 06508
(203) 934-8611
(203) 799-8179 Fax

EQ = Equal
AP = Approximately
N/D = Not Determined
ND = No Data Available
HSE = Health, Safety and Environmental

LT = Less Than
GT = Greater Than
TR = Trace
> = Greater Than
< = Less Than

