


enthone

Material Safety
Data Sheet

Material Safety Data Sheet

Emergency phone: CHEMTREC Number
(800) 424-9300



Health	2
Flammability	2
Instability	0
Reactivity	0
Personal protection	C

Section 1. Chemical product and company identification

Product name : ENTHONE® 50-771R CAT-L-INK
Product code : 135712
Material uses : Specialty chemicals for the electronics and surface finishing industries.
Manufacturer : Enthone Inc
350 Frontage Road
West Haven, CT 06516
Phone: (203) 799-4917
Fax: (203) 799-8179
www.cooksonelectronics.com
Enthone OMI deMexico S.A. de C.V.
Norte 59 No. 896
Col. Industrial Vallejo
Mexico, D.F. 02300
Mexico
Phone: 52 55 5078 3904
Fax: 52 555 567 6326
www.cooksonelectronics.com
Tel. local de emergencias: 080
Tel. de emergencias en
transportacion: 01 800 0021 400 ;
(55) 5559 1588

Validation date : 8/10/2005. **Supersedes Date** : 1/10/2003
Prepared by : T. Maturo

Section 2. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
Epoxy Resin(s)		30-40
c.i. pigment black 28	68186-91-4	30-40
di ethylene glycol monoethyl ether acetate	112-15-2	10-20
dipropylene glycol methyl ether	34590-94-8	5-10
2-methoxy-1-methylethyl acetate	108-65-6	5-10
Proprietary Polymer.		1-5
silica, amorphous, fumed, cryst.-free	112945-52-5	0.1-1.0

Any component not listed in Section 2 is non-regulated or present in the product in concentrations below legal disclosure limits

All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.

Continued on next page

Section 3. Hazards identification

Physical state	: Liquid.
Odor	: Mild.
Emergency overview	: Warning! CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL WHICH MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: KIDNEYS, LIVER, MUCOUS MEMBRANES, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA. POSSIBLE CANCER HAZARD CONTAINS MATERIAL WHICH MAY CAUSE CANCER BASED ON ANIMAL DATA. COMBUSTIBLE LIQUID AND VAPOR. VAPOR MAY CAUSE FIRE. Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Risk of cancer depends on duration and level of exposure.
Routes of entry	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects	
Eye contact	: Irritating to eyes.
Skin contact	: Harmful in contact with skin. Irritating to skin. May cause sensitization by skin contact.
Inhalation	: Irritating to respiratory system.
Ingestion	: Harmful if swallowed.
Potential chronic health effects	
Target organs	: Contains material which may cause damage to the following organs: kidneys, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Over-exposure signs/symptoms	: dipropylene glycol methyl ether May be slightly toxic by inhalation, in contact with skin or if swallowed. Can cause dizziness, lightheadedness, headache, nausea, and blurred vision. Prolonged exposure may cause narcotic effect. Epoxy Resin(s) Irritating to eyes, respiratory system and skin. MAY BE HARMFUL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED. Material is irritating to mucous membranes and upper respiratory tract. May cause allergic skin reactions with repeated exposure. Di ethylene glycol monoethyl ether acetate Inhalation and Ingestion: stomach pains, nausea/vomiting, diarrhea and central nervous system depression. Harmful if absorbed through the skin. Repeated or prolonged exposure to the substance can produce kidney damage. c.i. pigment black 28 : Material contains copper and chromium (III) compounds. Ingestion may cause nausea/vomiting and diarrhea. May cause allergic reactions to certain individuals. Silica, amorphous, fumed, cryst.-free Because this product is a liquid, exposure to this particulate is unlikely under ordinary conditions of use.
Carcinogenicity	: Classified 3 (Not classifiable for human.) by IARC [Silica, amorphous, fumed, cryst.-free].
Special remarks on chronic effects on humans	: Silica, amorphous, fumed, cryst.-free Carcinogen status based on inhalation of particulate form of this chemical If this product is a liquid, exposure to this particulate is unlikely under ordinary conditions of use. See toxicological Information (section 11)

Section 4. First aid measures

First aid

- Eye contact** : Provide a readily accessible eyewash facility and quick drench safety shower. Provide a readily accessible eyewash facility and quick drench safety shower. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately. Get medical attention immediately.
- Skin contact** : Evacuate the victim to a safe area as soon as possible. Ensure that eyewash stations and safety showers are proximal to the work-station location. In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
- Inhalation** : If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.
- Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear suitable protective clothing.

Section 5. Fire fighting measures

- NFPA Hazard identification number Flammability** : 2
- Auto-ignition temperature** : The lowest known value is 680°C (1256°F) (Di ethylene glycol monoethyl ether acetate).
- Flash point** : Closed cup: 62.78°C (145°F).
- Flammable limits** : Not available.
- Products of combustion** : These products are carbon oxides (CO, CO₂).
- Fire hazards in presence of various substances** : Flammable in presence of open flames, sparks and static discharge, of heat.
- Special remarks on fire hazards** : Vapors are heavier than air and may spread along floors. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back.
- Explosion hazards in presence of various substances.** : Explosive in presence of open flames, sparks and static discharge.
- Special remarks on explosion hazards** : No additional remark.
- Fire fighting media and instructions** : In case of fire, use water spray (fog), foam, dry chemicals, or CO₂.

Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid all possible sources of ignition (spark or flame). Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Dike large spills and use a non-sparking or explosion proof means to transfer material to an appropriate container for disposal. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of according to all federal, state and local applicable regulations.

Section 7. Handling and storage

Handling : Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.

Storage : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Incompatibility with various substances: : Reactive with oxidizing agents.

Hazardous decomposition products: : Toxic carbon oxides (CO, CO₂) and nitrogen oxides (NO, NO₂...)

Section 8. Exposure Controls, Personal Protection

Engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any explosive limits. Use explosion-proof ventilation equipment.

Personal protection

Eyes : Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Avoid contact with skin and clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Avoid contact with skin. Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Personal protection in case of a large spill : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing and eye/face protection. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

<u>Ingredient name</u>	<u>CAS number</u>	<u>Exposure limits</u>
c.i. pigment black 28	68186-91-4	<p>ACGIH TLV (United States, 6/2005). TWA: 0.5 mg/m³ 8 hour(s). Form: (as chromium (III)) TWA: 1 mg/m³ 8 hour(s). Form: Dusts and Mists (As copper) TWA: 0.2 mg/m³ 8 hour(s). Form: Fume (As copper)</p> <p>OSHA PEL (United States, 6/2005). TWA: 0.5 mg/m³ 8 hour(s). Form: (as chromium (III)) TWA: 1 mg/m³ 8 hour(s). Form: Dusts and Mists (As copper) TWA: 0.1 mg/m³ 8 hour(s). Form: Fume (As copper)</p>
dipropylene glycol methyl ether	34590-94-8	<p>ACGIH TLV (United States, 9/2004). Skin STEL: 909 mg/m³ 15 minute(s). Form: All forms STEL: 150 ppm 15 minute(s). Form: All forms TWA: 606 mg/m³ 8 hour(s). Form: All forms TWA: 100 ppm 8 hour(s). Form: All forms</p> <p>NIOSH REL (United States, 6/2001). Skin STEL: 900 mg/m³ 15 minute(s). Form: All forms STEL: 150 ppm 15 minute(s). Form: All forms TWA: 600 mg/m³ 10 hour(s). Form: All forms TWA: 100 ppm 10 hour(s). Form: All forms</p> <p>OSHA PEL (United States, 6/1993). Skin TWA: 600 mg/m³ 8 hour(s). Form: All forms TWA: 100 ppm 8 hour(s). Form: All forms</p> <p>OSHA PEL 1989 (United States, 3/1989). Skin STEL: 900 mg/m³ 15 minute(s). Form: All forms STEL: 150 ppm 15 minute(s). Form: All forms TWA: 600 mg/m³ 8 hour(s). Form: All forms TWA: 100 ppm 8 hour(s). Form: All forms</p>
2-Methoxy-1-methylethyl acetate	108-65-6	<p>AIHA WEEL (United States, 1/2004). TWA: 100 ppm 8 hour(s). Form: All forms</p>
Silica, amorphous, fumed, cryst.-free	112945-52-5	<p>ACGIH TLV (United States, 3/2005). TWA: 10 mg/m³ 8 hour(s).</p> <p>OSHA PEL (United States, 3/2005). TWA: 20 mmppcf 8 hour(s).</p>

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical state	: Liquid.
Color	: Black.
Odor	: Mild.
pH	: Not available.
Boiling/condensation point	: 176.67°C (350°F)
Melting/freezing point	: May start to solidify at -75°C (-103°F) based on data for: 2-Methoxy-1-methylethyl acetate. Weighted average: -79.2°C (-110.6°F)
Specific gravity	: 1.47 (Water = 1)

Continued on next page

Vapor pressure	: The highest known value is 0.3 kPa (2.4 mm Hg) (at 20°C) (2-Methoxy-1-methylethyl acetate).
Vapor density	: The highest known value is 6.07 (Air = 1) (Di ethylene glycol monoethyl ether acetate). Weighted average: 5.41 (Air = 1)
Odor threshold	: Not available.
Evaporation rate	: 0.02 (dipropylene glycol methyl ether) compared to Butyl acetate.
Ionicity (in water)	: Not available.
Dispersion properties	: Is not dispersed in cold water, hot water.
Solubility	: Insoluble in cold water, hot water.
Physical chemical comments	: Complete (copper)

Section 10. Stability and reactivity

Stability and reactivity	The product is stable.
Incompatibility with various substances:	: Reactive with oxidizing agents.
Other hazardous decomposition products	: Toxic carbon oxides (CO, CO ₂) and nitrogen oxides (NO, NO ₂ ...)
Hazardous polymerization	: Will not occur.

Section 11. Toxicological information

Toxicity data

<u>Ingredient name</u>	<u>CAS number</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Epoxy Resin(s)		LD50	>2000 mg/kg	Oral	Rat
		LD50	>2000 mg/kg	Dermal	Rabbit
di ethylene glycol monoethyl ether acetate	112-15-2	LD50	4400 mg/kg	Oral	Rabbit
		LD50	3930 mg/kg	Oral	Guinea pig
		LD50	11000 mg/kg	Oral	Rat
		LD50	7500 mg/kg	Oral	Dog
dipropylene glycol methyl ether	34590-94-8	LD50	7500 mg/kg	Oral	Dog
2-methoxy-1-methylethyl acetate	108-65-6	LD50	8532 mg/kg	Oral	Rat
Proprietary Polymer.		LD50	>7940 mg/kg	Oral	Rat
		LD50	>7940 mg/kg	Dermal	Rabbit
		LD50	3160 mg/kg	Oral	Rat
silica, amorphous, fumed, cryst.-free	112945-52-5	LD50	3160 mg/kg	Oral	Rat

IDLH : Not available.

Chronic effects on humans : **CARCINOGENIC EFFECTS** Classified 3 (Not classifiable for human.) by IARC [Silica, amorphous, fumed, cryst.-free].
Contains material which may cause damage to the following organs: kidneys, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Special remarks on chronic effects on humans : **Silica, amorphous, fumed, cryst.-free** Carcinogen status based on inhalation of particulate form of this chemical If this product is a liquid, exposure to this particulate is unlikely under ordinary conditions of use.

California prop. 65 : **WARNING:** This product contains chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm: Benzene
WARNING: This product contains chemical(s) known to the state of California to cause reproductive harm (male): Benzene
California prop. 65 (no significant risk level): Benzene
California prop. 65 (acceptable daily intake level): Benzene
WARNING: This product contains chemical(s) known to the state of California to cause

birth defects or other reproductive harm.: Benzene; chromium

WARNING: This product contains chemical(s) known to the state of California to cause cancer.: Benzene; chromium

Enthone has not conducted specific studies on the toxicity of this product.

Section 12. Ecological information

Ecotoxicity data

Ingredient name	Species	Period	Result
Proprietary Polymer.	Fish (LC50)	96 hour(s)	>1000 mg/l

Enthone has not conducted specific studies on the ecotoxicity or environmental fate of this product.

Section 13. Disposal considerations

Waste disposal : Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	Not regulated.	-	-	Not available.		Not available.

Section 15. Regulatory information

United States

U.S. Federal regulations : All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.

TSCA 12(b) annual export notification: No products were found.

TSCA 12(b) one time export: No products were found.

Clean air act (CAA) 112 accidental release prevention: No products were found.

Clean air act (CAA) 112 regulated flammable substances: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

SARA 313	Product name	CAS number	Concentration
:	di ethylene glycol monoethyl ether acetate	112-15-2	10-20

State regulations : California prop. 65 (no significant risk level): Benzene

WHMIS (Canada) : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Class D-2B: Material causing other toxic effects (TOXIC).

Ingredients not listed on the CEPA DSL:

PROPRIETARY SURFACTANTS

Section 16. Other information

Definition of Terms

ACGIH	American Conference of Governmental Industrial Hygienists
Ceiling	Maximum exposure limit defined by OSHA
CAS	Chemical Abstract Service
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
REL	Recommended Exposure Limit
RTK	Right to Know
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	ACGIH Threshold Limit Value
TLV-C	ACGIH Threshold Limit Value, Ceiling
TRADE SECRET	Claimed as allowed under 29CFR§1910.1200
TSCA	Toxic Substances Control Act
PPE	Personal Protection Equipment
CEPA	Canadian Environmental Protection Act
DSL	Domestic Substance List
NDSL	Non-Domestic Substance List
NSN	New Substance Notification Rules

Disclaimer

This Material Safety Data Sheet may be used to comply with OSHA's Hazard Communication Standard, 29CFR§1910.1200. This Material Safety Data Sheet may also be used to comply with the requirements of Workplace Hazardous Materials Information System, of the Controlled Products Regulations, under the Hazardous Products Act. Enthone furnishes the data contained herein in good faith at customer's request without liability or legal responsibility for same whatsoever, and no warranty or guarantee, express or implied, is made with respect to such data; nor does Enthone grant permission, recommendation, or inducement to infringe any patent whether owned by Enthone or others. The data is offered solely for your information and consideration. Since conditions of use are beyond Enthone's control, user assumes all responsibility and risk.



Cookson Electronics