


enthone

Material Safety  
Data Sheet

## Material Safety Data Sheet

Emergency phone: CHEMTREC Number  
(800) 424-9300



Health	2
Flammability	0
Instability	0
Reactivity	0
Personal protection	C

### Section 1. Chemical product and company identification

**Product name** : ENTHONE® AD-2001 THINNER  
**Product code** : 134756  
**Material uses** : Specialty chemicals for the electronics and surface finishing industries.  
**Manufacturer** : Enthone Inc  
350 Frontage Road  
West Haven, CT 06516  
Phone: (203) 799-4917  
Fax: (203) 799-8179  
www.cooksonelectronics.com  
Enthone OMI de Mexico S.A. de C.V.  
Norte 59 No. 896  
Col. Industrial Vallejo  
Mexico, D.F. 02300  
Mexico  
Phone: 52 55 5078 3904  
Fax: 52 555 567 6326  
www.cooksonelectronics.com  
Tel. local de emergencias: 080  
Tel. de emergencias en  
transportacion: 01 800 0021 400 ;  
(55) 5559 1588

**Validation date** : 8/3/2005.  
**Prepared by** : T. Maturo

**Supersedes Date** : 4/6/2004

### Section 2. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
di ethylene glycol monoethyl ether acetate	112-15-2	30-40
dipropylene glycol methyl ether	34590-94-8	30-40
2-methoxy-1-methylethyl acetate	108-65-6	20-30

Any component not listed in Section 2 is non-regulated or present in the product in concentrations below legal disclosure limits

*All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.*

### Section 3. Hazards identification

**Physical state** : Liquid.  
**Odor** : Mild.  
**Emergency overview** : Warning!

Continued on next page

HARMFUL IF INHALED.  
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION.  
MAY CAUSE ALLERGIC SKIN REACTION.  
MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED.  
CONTAINS MATERIAL WHICH MAY CAUSE DAMAGE TO THE FOLLOWING  
ORGANS: KIDNEYS, LIVER, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS  
SYSTEM, EYE, LENS OR CORNEA.  
COMBUSTIBLE LIQUID AND VAPOR.  
VAPOR MAY CAUSE FIRE.

Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

**Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.

**Potential acute health effects**

**Eye contact** : Irritating to eyes.

**Skin contact** : Harmful in contact with skin. Irritating to skin.  
May cause sensitization by skin contact.

**Inhalation** : Toxic by inhalation. Irritating to respiratory system.

**Ingestion** : Harmful if swallowed.

**Potential chronic health effects**

**Target organs** : Contains material which may cause damage to the following organs: kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

**Over-exposure signs/symptoms**

: Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. Irritating to mouth, throat and stomach., digestive system. Can cause dizziness, lightheadedness, headache, nausea, and blurred vision., drowsiness/fatigue, nausea/vomiting, diarrhea and central nervous system depression. Prolonged skin contact may cause dermatitis. Prolonged or repeated exposure may cause kidneys damage and Possible Narcotic. effects.

**Carcinogenicity** : Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.  
**Special remarks on chronic effects on humans** : **See toxicological Information (section 11)**

**Section 4. First aid measures**

**First aid**

**Eye contact** : Provide a readily accessible eyewash facility and quick drench safety shower. Provide a readily accessible eyewash facility and quick drench safety shower. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately. Get medical attention immediately.

**Skin contact** : Evacuate the victim to a safe area as soon as possible. Ensure that eyewash stations and safety showers are proximal to the work-station location. In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

**Inhalation** : If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.

**Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If fumes are still suspected to be present, the rescuer should wear an appropriate mask or a self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear suitable protective clothing.

## Section 5. Fire fighting measures

- NFPA Hazard identification number Flammability** : 2
- Auto-ignition temperature** : The lowest known value is 680°C (1256°F) (Di ethylene glycol monoethyl ether acetate).
- Flash point** : Closed cup: 57.23°C (135°F).
- Flammable limits** : Not available.
- Products of combustion** : These products are carbon oxides (CO, CO<sub>2</sub>).
- Fire hazards in presence of various substances** : Flammable in presence of open flames, sparks and static discharge, of heat.
- Special remarks on fire hazards** : Vapors can travel to a source of ignition and flashback.
- Explosion hazards in presence of various substances.** : Explosive in presence of open flames, sparks and static discharge, of heat.
- Special remarks on explosion hazards** : To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap.
- Fire fighting media and instructions** : In case of fire, use water spray (fog), foam, dry chemicals, or CO<sub>2</sub>.
- Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

## Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid all possible sources of ignition (spark or flame). Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Dike large spills and use a non-sparking or explosion proof means to transfer material to an appropriate container for disposal. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of according to all federal, state and local applicable regulations.

## Section 7. Handling and storage

- Handling** : Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.
- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

*Continued on next page*

**Incompatibility with various substances:** : Reactive with oxidizing agents.

**Hazardous decomposition products:** : Toxic carbon oxides (CO, CO<sub>2</sub>) nitrogen oxides (NO, NO<sub>2</sub>...)

## **Section 8. Exposure Controls, Personal Protection**

**Engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any explosive limits. Use explosion-proof ventilation equipment.

### **Personal protection**

**Eyes** : Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Recommended: Face shield , Splash goggles

**Skin** : Avoid contact with skin and clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body: Recommended: safety apron

Feet: Recommended: Nitrile rubber

**Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Recommended: Be sure to use an approved/certified respirator or equivalent. Employers must ensure that employees are properly fitted and trained in the use of respiratory and other personal protection equipment.

**Hands** : Avoid contact with skin. Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

>8 hour(s) (breakthrough time): Nitrile rubber , Butyl rubber . Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Personal protection in case of a large spill** : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing and eye/face protection. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### **Ingredient name**

### **CAS number**

### **Exposure limits**

dipropylene glycol methyl ether 34590-94-8

#### **ACGIH TLV (United States, 9/2004). Skin**

STEL: 909 mg/m<sup>3</sup> 15 minute(s). Form: All forms

STEL: 150 ppm 15 minute(s). Form: All forms

TWA: 606 mg/m<sup>3</sup> 8 hour(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

#### **NIOSH REL (United States, 6/2001). Skin**

STEL: 900 mg/m<sup>3</sup> 15 minute(s). Form: All forms

STEL: 150 ppm 15 minute(s). Form: All forms

TWA: 600 mg/m<sup>3</sup> 10 hour(s). Form: All forms

TWA: 100 ppm 10 hour(s). Form: All forms

#### **OSHA PEL (United States, 6/1993). Skin**

2-Methoxy-1-methylethyl acetate 108-65-6

TWA: 600 mg/m<sup>3</sup> 8 hour(s). Form: All forms  
TWA: 100 ppm 8 hour(s). Form: All forms  
**OSHA PEL 1989 (United States, 3/1989). Skin**  
STEL: 900 mg/m<sup>3</sup> 15 minute(s). Form: All forms  
STEL: 150 ppm 15 minute(s). Form: All forms  
TWA: 600 mg/m<sup>3</sup> 8 hour(s). Form: All forms  
TWA: 100 ppm 8 hour(s). Form: All forms  
**AIHA WEEL (United States, 1/2004).**  
TWA: 100 ppm 8 hour(s). Form: All forms

Consult local authorities for acceptable exposure limits.

## Section 9. Physical and chemical properties

<b>Physical state</b>	: Liquid.
<b>Color</b>	: Clear.
<b>Odor</b>	: Mild.
<b>pH</b>	: Not available.
<b>Boiling/condensation point</b>	: 182.22°C (360°F)
<b>Melting/freezing point</b>	: May start to solidify at -75°C (-103°F) based on data for: 2-Methoxy-1-methylethyl acetate. Weighted average: -79.2°C (-110.6°F)
<b>Specific gravity</b>	: 0.979 (Water = 1)
<b>Vapor pressure</b>	: The highest known value is 0.3 kPa (2.4 mm Hg) (at 20°C) (2-Methoxy-1-methylethyl acetate).
<b>Vapor density</b>	: The highest known value is 6.07 (Air = 1) (Di ethylene glycol monoethyl ether acetate). Weighted average: 5.34 (Air = 1)
<b>Odor threshold</b>	: Not available.
<b>Evaporation rate</b>	: 0.02 (dipropylene glycol methyl ether) compared to Butyl acetate.
<b>Ionicity (in water)</b>	: Not available.
<b>Dispersion properties</b>	: See solubility in water.
<b>Solubility</b>	: Easily soluble in cold water, hot water.

## Section 10. Stability and reactivity

<b>Stability and reactivity</b>	The product is stable.
<b>Incompatibility with various substances:</b>	: Reactive with oxidizing agents.
<b>Other hazardous decomposition products</b>	: Toxic carbon oxides (CO, CO <sub>2</sub> ) nitrogen oxides (NO, NO <sub>2</sub> ...)
<b>Hazardous polymerization</b>	: Will not occur.

## Section 11. Toxicological information

### Toxicity data

<u>Ingredient name</u>	<u>CAS number</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
di ethylene glycol monoethyl ether acetate	112-15-2	LD50	4400 mg/kg	Oral	Rabbit
		LD50	3930 mg/kg	Oral	Guinea pig
		LD50	11000 mg/kg	Oral	Rat
dipropylene glycol methyl ether	34590-94-8	LD50	7500 mg/kg	Oral	Dog
2-methoxy-1-methylethyl acetate	108-65-6	LD50	8532 mg/kg	Oral	Rat

**IDLH** : Not available.

**Chronic effects on humans** : Contains material which may cause damage to the following organs: kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Continued on next page

**Special remarks on chronic effects on humans** : Not available.

**California prop. 65** : California prop. 65: No products were found.  
Enthone has not conducted specific studies on the toxicity of this product.

## Section 12. Ecological information


Enthone has not conducted specific studies on the ecotoxicity or environmental fate of this product.

## Section 13. Disposal considerations

**Waste disposal** : Waste must be disposed of in accordance with federal, state and local environmental control regulations.

*Consult your local or regional authorities.*

## Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1METHYLETI ACETATE)	3	III		ERG# 128

## Section 15. Regulatory information

### United States

**U.S. Federal regulations** : All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.

TSCA 12(b) annual export notification: No products were found.

TSCA 12(b) one time export: No products were found.

Clean air act (CAA) 112 accidental release prevention: No products were found.

Clean air act (CAA) 112 regulated flammable substances: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

	<u>Product name</u>	<u>CAS number</u>	<u>Concentration</u>
<b>SARA 313</b>	: di ethylene glycol monoethyl ether acetate	112-15-2	30-40

**State regulations** : No products were found.

**WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

All ingredients in this product are found on the CEPA DSL.

## Section 16. Other information

### Definition of Terms

ACGIH	American Conference of Governmental Industrial Hygienists
Ceiling	Maximum exposure limit defined by OSHA
CAS	Chemical Abstract Service
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
REL	Recommended Exposure Limit
RTK	Right to Know
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	ACGIH Threshold Limit Value
TLV-C	ACGIH Threshold Limit Value, Ceiling
TRADE SECRET	Claimed as allowed under 29CFR§1910.1200
TSCA	Toxic Substances Control Act
PPE	Personal Protection Equipment
CEPA	Canadian Environmental Protection Act
DSL	Domestic Substance List
NDSL	Non-Domestic Substance List
NSN	New Substance Notification Rules

### Disclaimer

This Material Safety Data Sheet may be used to comply with OSHA's Hazard Communication Standard, 29CFR§1910.1200. This Material Safety Data Sheet may also be used to comply with the requirements of Workplace Hazardous Materials Information System, of the Controlled Products Regulations, under the Hazardous Products Act. Enthone furnishes the data contained herein in good faith at customer's request without liability or legal responsibility for same whatsoever, and no warranty or guarantee, express or implied, is made with respect to such data; nor does Enthone grant permission, recommendation, or inducement to infringe any patent whether owned by Enthone or others. The data is offered solely for your information and consideration. Since conditions of use are beyond Enthone's control, user assumes all responsibility and risk.



**Cookson Electronics**