


Material Safety Data Sheet

Emergency phone: CHEMTREC Number
(800) 424-9300



Health	3
Fire hazard	2
Reactivity	1
Personal protection	C

Section 1. Chemical product and company identification

Product name : ENTHONE® AD-3002
Product code : 135182
Material uses : Specialty chemicals for the electronics and surface finishing industries.
Manufacturer : Enthone Inc
 350 Frontage Road
 West Haven, CT 06516
 Phone: (203) 799-4917
 Fax: (203) 799-8179
 www.cooksonelectronics.com

Enthone OMI de Mexico S.A. de C.V.
 Norte 59 No. 896
 Col. Industrial Vallejo
 Mexico, D.F. 02300
 Mexico
 Phone: 52 55 5078 3904
 Fax: 52 555 567 6326
 www.cooksonelectronics.com
 Tel. local de emergencias: 080
 Tel. de emergencias en
 transportacion: 01 800 0021 400 ;
 (55) 5559 1588

Validation date : 12/22/2005. **Supersedes Date** : 1/23/2003
Prepared by : T. Maturo

Section 2. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
Acrylic. Resins.		40-50
solvent naphtha (petroleum), heavy arom.	64742-94-5	40-50
naphthalene	91-20-3	1-5

Any component not listed in Section 2 is non-regulated or present in the product in concentrations below legal disclosure limits

All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.

Section 3. Hazards identification

Physical state	: Liquid.
Odor	: None.
Emergency overview	: Warning! HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. MAY CAUSE DAMAGE TO THE FOLLOWING ORGANS: BLOOD, KIDNEYS, LIVER, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYE, LENS OR CORNEA. POSSIBLE CANCER HAZARD CONTAINS MATERIAL WHICH MAY CAUSE CANCER BASED ON ANIMAL DATA. COMBUSTIBLE LIQUID AND VAPOR. VAPOR MAY CAUSE FIRE. Do not ingest. Avoid prolonged contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Risk of cancer depends on duration and level of exposure.
Routes of entry	: Dermal contact. Inhalation. Ingestion.
Potential acute health effects	
Eye contact	: Irritating to eyes.
Skin contact	: Harmful in contact with skin. Irritating to skin.
Inhalation	: Toxic by inhalation. Irritating to respiratory system.
Ingestion	: Harmful if swallowed.
Potential chronic health effects	
Target organs	: May cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Over-exposure signs/symptoms	: Solvent naphtha (petroleum), heavy arom.: Repeated or prolonged contact with irritants may cause dermatitis. Aspiration hazard if swallowed- can enter lungs and cause damage. Over-exposure by inhalation may cause respiratory irritation.
Carcinogenicity	: Classified 2B (Possible for human.) by IARC [naphthalene]. Classified 2 (Reasonably Anticipated To Be Human Carcinogens.) by NTP [naphthalene]. Classified A4 (Not classifiable for human or animal.) by ACGIH [naphthalene]. See toxicological information (section 11)

Section 4. First aid measures

First aid	
Eye contact	: Provide a readily accessible eyewash facility and quick drench safety shower. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin contact	: Evacuate the victim to a safe area as soon as possible. Ensure that eyewash stations and safety showers are proximal to the work-station location. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Inhalation	: If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.
Ingestion	: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If fumes are still suspected to be present, the rescuer should wear an appropriate mask or a self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wear suitable protective clothing.

Section 5. Fire fighting measures

NFPA Hazard identification number Flammability : 2

Auto-ignition temperature : Not available.

Flash point : Closed cup: 65 to 67.778°C (149 to 154°F).

Flammable limits : Not available.

Products of combustion : These products are carbon oxides (CO, CO₂).

Fire hazards in presence of various substances : Flammable in presence of open flames, sparks and static discharge, of heat.

Explosion hazards in presence of various substances. : Not available.

Fire fighting media and instructions : In case of fire, use water spray (fog), foam, dry chemicals, or CO₂.

Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid all possible sources of ignition (spark or flame). Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Dike large spills and use a non-sparking or explosion proof means to transfer material to an appropriate container for disposal. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of according to all federal, state and local applicable regulations.

Section 7. Handling and storage

Handling : Do not ingest. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Wash thoroughly after handling.

- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
- Incompatibility with various substances:** : Reactive with oxidizing agents.
- :

Section 8. Exposure Controls, Personal Protection

- Engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any explosive limits. Use explosion-proof ventilation equipment.
- Personal protection**
- Eyes** : Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Avoid contact with skin and clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Avoid contact with skin. Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Personal protection in case of a large spill** : Do not clean-up or dispose except under supervision of a specialist. Keep unnecessary and unprotected personnel from entering. Follow your company's spill procedures. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing and eye/face protection. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Avoid breathing vapors of this product. Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

<u>Ingredient name</u>	<u>CAS number</u>	<u>Exposure limits</u>
naphthalene	91-20-3	ACGIH TLV (United States, 2002). STEL: 79 mg/m ³ 15 minute(s). STEL: 79 mg/m ³ 15 minute(s). Form: All forms STEL: 15 ppm 15 minute(s). Form: All forms TWA: 52 mg/m ³ 8 hour(s). Form: All forms TWA: 10 ppm 8 hour(s). Form: All forms NIOSH REL (United States, 6/2001). STEL: 75 mg/m ³ 15 minute(s). Form: All forms STEL: 15 ppm 15 minute(s). Form: All forms TWA: 50 mg/m ³ 10 hour(s). Form: All forms TWA: 10 ppm 10 hour(s). Form: All forms OSHA PEL (United States, 6/1993). TWA: 50 mg/m ³ 8 hour(s). Form: All forms TWA: 10 ppm 8 hour(s). Form: All forms OSHA PEL 1989 (United States, 3/1989). STEL: 75 mg/m ³ 15 minute(s). Form: All forms STEL: 15 ppm 15 minute(s). Form: All forms TWA: 50 mg/m ³ 8 hour(s). Form: All forms

Continued on next page

TWA: 10 ppm 8 hour(s). Form: All forms

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical state	: Liquid.
Color	: Clear.
Odor	: None.
pH	: Not available.
Boiling/condensation point	: The lowest known value is 177 to 193°C (350.6 to 379.4°F) (Solvent naphtha (petroleum), heavy arom.). Weighted average: 195.05°C (383.1°F)
Melting/freezing point	: Not available.
Specific gravity	: 0.954 (Water = 1)
Vapor pressure	: Not available.
Vapor density	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
Ionicity (in water)	: Not available.
Dispersion properties	: See solubility in water.
Solubility	: Soluble in cold water, hot water.

Section 10. Stability and reactivity

Stability and reactivity	The product is stable.
Incompatibility with various substances:	: Reactive with oxidizing agents.
Hazardous polymerization	: Will not occur.

Section 11. Toxicological information

Toxicity data

<u>Ingredient name</u>	<u>CAS number</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Acrylic. Resins.		LD50	>7940 mg/kg	Oral	Rat
		LD50	>7940 mg/kg	Dermal	Rabbit
solvent naphtha (petroleum), heavy arom.	64742-94-5	LD50	3200 mg/kg	Oral	Rat
		LD50	>2000 mg/kg	Dermal	Rabbit
		LC50	>590 mg/m ³ (4 hour(s))	Inhalation	Rat
naphthalene	91-20-3	LD50	490 mg/kg	Oral	Rat
		LD50	316 mg/kg	Oral	Mouse
		LD50	1200 mg/kg	Oral	Guinea pig
		LD50	>2500 mg/kg	Dermal	Rat
		LDLo	100 mg/kg	Oral	child
		LDLo	400 mg/kg	Oral	Dog
LC50	>340 mg/m ³ (1 hour(s))	Inhalation	Rat		

IDLH : Not available.

Continued on next page

Chronic effects on humans : **CARCINOGENIC EFFECTS:** Classified 2B (Possible for human.) by IARC [naphthalene].
Classified 2 (Reasonably Anticipated To Be Human Carcinogens.) by NTP [naphthalene].
Classified A4 (Not classifiable for human or animal.) by ACGIH [naphthalene].
May cause damage to the following organs: blood, kidneys, liver, upper respiratory tract,
skin, central nervous system (CNS), eye, lens or cornea.

California prop. 65 : **WARNING:** This product contains chemical(s) known to the state of California to cause
cancer, birth defects or other reproductive harm: naphthalene
California prop. 65 (no significant risk level): naphthalene
WARNING: This product contains chemical(s) known to the state of California to cause
cancer.: naphthalene

Enthone has not conducted specific studies on the toxicity of this product.

Section 12. Ecological information

Ecotoxicity data

Ingredient name

Acrylic. Resins.
naphthalene

Species

Fish (LC50)
Daphnia magna (EC50)
Daphnia magna (EC50)
Daphnia magna (EC50)
Daphnia pulex (LC50)
Oncorhynchus mykiss (LC50)
Oncorhynchus mykiss (LC50)

Period

96 hour(s)
48 hour(s)
48 hour(s)
48 hour(s)
96 hour(s)
96 hour(s)
96 hour(s)

Result

>1000 mg/l
1.6 mg/l
2.194 mg/l
2.55 mg/l
1 mg/l
1.6 mg/l
1.8 mg/l

Enthone has not conducted specific studies on the ecotoxicity or environmental fate of this product.

Section 13. Disposal considerations

Waste disposal : Waste must be disposed of in accordance with federal, state and local environmental
control regulations.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	Not regulated.	-	-	Not available.		Not available.

Continued on next page

Section 15. Regulatory information

United States

U.S. Federal regulations : All ingredients comply with applicable rules or orders under United States TSCA and Canadian CEPA regulations.

TSCA 12(b) annual export notification: No products were found.

TSCA 12(b) one time export: No products were found.

TSCA 5(a)2 final significant rules: No products were found.

Clean air act (CAA) 112 accidental release prevention: No products were found.

Clean air act (CAA) 112 regulated flammable substances: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

<u>Product name</u>	<u>CAS number</u>	<u>Concentration</u>
naphthalene	91-20-3	1-5

SARA 313

State regulations WHMIS (Canada)

: California prop. 65 (no significant risk level): naphthalene
: Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
Class D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).
Class D-2A: Material causing other toxic effects (VERY TOXIC).
Class D-2B: Material causing other toxic effects (TOXIC).
All ingredients in this product are found on the CEPA DSL.

Section 16. Other information

Definition of Terms

ACGIH	American Conference of Governmental Industrial Hygienists
Ceiling	Maximum exposure limit defined by OSHA
CAS	Chemical Abstract Service
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
REL	Recommended Exposure Limit
RTK	Right to Know
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	ACGIH Threshold Limit Value
TLV-C	ACGIH Threshold Limit Value, Ceiling
TRADE SECRET	Claimed as allowed under 29CFR§1910.1200
TSCA	Toxic Substances Control Act
PPE	Personal Protection Equipment
CEPA	Canadian Environmental Protection Act
DSL	Domestic Substance List
NDSL	Non-Domestic Substance List
NSN	New Substance Notification Rules

Disclaimer

This Material Safety Data Sheet may be used to comply with OSHA's Hazard Communication Standard, 29CFR§1910.1200. This Material Safety Data Sheet may also be used to comply with the requirements of Workplace Hazardous Materials Information System, of the Controlled Products Regulations, under the Hazardous Products Act. Enthone furnishes the data contained herein in good faith without liability or legal responsibility for same whatsoever, and no warranty or guarantee, express or implied, is made with respect to such data; nor does Enthone grant permission, recommendation, or inducement to infringe any patent whether owned by Enthone or others. The data is offered solely for your information and consideration. Since conditions of use are beyond Enthone's control, user assumes all responsibility

Continued on next page

and risk.



Cookson Electronics