



## MATERIAL SAFETY DATA SHEET

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: LORD 363B

Product Use/Class: EPOXY ADHESIVE, PART 2 OF 2

LORD CORPORATION  
CHEMICAL PRODUCTS DIVISION  
2000 WEST GRANDVIEW BLVD  
ERIE, PA 16514

INFORMATION TELEPHONE: 814 868-3611

TRANSPORTATION EMERGENCY  
CALL CHEMTREC: 800 424-9300

NON-TRANSPORTATION EMERGENCY: 814 763-2345

EFFECTIVE DATE: 11/15/1999

SUPERCEDES DATE: 10/25/1996

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL- TWA	OSHA PEL- CEILING	Units	Skin
Amine compound	Proprietary	10 %	N.E.	N.E.	N.E.	N.E.		

N.E. - Not Established, S - Skin Designation, C - Ceiling

### SECTION 3 - HAZARDS IDENTIFICATION

**\*\*\* EMERGENCY OVERVIEW \*\*\*:** Clear to yellow Liquid, with Mercaptan odor. Harmful if inhaled. May cause skin and eye burns. May cause allergic skin reaction. May cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Eye contact may cause severe eye damage, including vision disturbances, corneal damage, and blindness.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May be corrosive to skin; contact may cause skin burns. May cause skin sensitization. May cause dermatitis.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Chronic skin contact may cause dermatitis.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation, Ingestion, Eye Contact

### SECTION 4 - FIRST AID MEASURES

**FIRST AID- EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Give victim one or two glasses of water or milk. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious person.

## SECTION 5 - FIRE FIGHTING MEASURES

**FLASH POINT:** > 200F, 94C  
(Setaflash Closed Cup)

**LOWER EXPLOSIVE LIMIT (%):** Not Applicable

**UPPER EXPLOSIVE LIMIT (%):** Not Applicable

**AUTOIGNITION TEMPERATURE:** N.D.

**OSHA FLAMMABILITY CLASSIFICATION:** COMBUSTIBLE LIQUID - CLASS IIIIB

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Keep non-essential personnel a safe distance away from the spill area. Avoid breathing vapors. Use self-contained breathing equipment. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the MSDS form. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

## SECTION 7 - HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

**STORAGE:** Store only in well-ventilated areas. Keep container closed when not in use.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

**RESPIRATORY PROTECTION:** Use a NIOSH/MSHA approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>BOILING RANGE:</b>	266 - 275 F	<b>VAPOR DENSITY:</b>	Heavier than Air
<b>APPEARANCE:</b>	Clear to yellow	<b>EVAPORATION RATE:</b>	Slower than Ether
<b>PHYSICAL STATE:</b>	Liquid	<b>DENSITY, LB/GL:</b>	9.40
<b>ODOR:</b>	Mercaptan	<b>SPECIFIC GRAVITY:</b>	1.13
<b>SOLUBILITY IN H2O:</b>	Insoluble	<b>pH:</b>	N.A.
<b>FREEZE POINT:</b>	N.D.	<b>ODOR THRESHOLD:</b>	N.D.
<b>VOLATILE BY WEIGHT:</b>	0.0%	<b>VOLATILE BY VOLUME:</b>	0.0%
<b>VAPOR PRESSURE:</b>	N.D.		
<b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b>	N.D.		

(See section 16 for abbreviation legend)

## SECTION 10 - STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** High temperatures.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, organic or inorganic nitrogen compounds including traces of hydrogen cyanide.

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

## SECTION 11 - TOXICOLOGICAL INFORMATION

<b>PRODUCT LD50</b>	<b>(ORAL)</b>	: No Data
	<b>(DERMAL)</b>	: No Data
<b>PRODUCT LC50</b>		: No Data

## SECTION 12 - ECOLOGICAL INFORMATION

**ECOLOGICAL INFORMATION:** No Information.

## SECTION 13 - DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

## SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: NOT REGULATED  
DOT HAZARD CLASS: NONE  
DOT UN/NA NUMBER: NONE  
PACKING GROUP: NONE  
EMERGENCY RESPONSE GUIDE NUMBER: NONE

**SECTION 15 - REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS: AS FOLLOWS -**

OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

NONE

**TOXIC SUBSTANCES CONTROL ACT:**

**INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

**EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

**INTERNATIONAL REGULATIONS: AS FOLLOWS -**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** D2A, D2B

**SECTION 16 - OTHER INFORMATION**

**HMIS RATINGS - HEALTH:** 2      **FLAMMABILITY:** 1      **REACTIVITY:** 0

\* - Indicates a chronic hazard; see Section 3

**REASON FOR REVISION:** Computer System Upgrade

**VOLATILE ORGANIC COMPOUNDS (Calculated) :** 0.00 lbs/gal, 0 grams/ltr

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

9901693630B

**DISCLAIMER**

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this

material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.