

MATERIAL SAFETY DATA SHEET
MATTHEWS PAINT COMPANY

SECTION 1 - CHEMICAL, PRODUCT, AND COMPANY INFORMATION

PRODUCT CODE/IDENTITY: 287437SP
REVISION DATE: 01/05/99 (000) 0808
CUSTOMER PART #/NAME:
PRODUCT TRADE NAME: HIGH SOLIDS ACCELERATOR
CHEMICAL FAMILY: DIBUTYL TIN DILAURATE
EMERGENCY MEDICAL/SPILL INFO: (800) 424-9300 CHEMTREC (U.S.)
91-800-00-214 (MEXICO)
(514) 645-1320 (CANADA)
TECHNICAL INFORMATION: (800) 323-6593
PRODUCT SAFETY/MSDS INFORMATION: 8201 - 100TH STREET
PLEASANT PRAIRIE, WISCONSIN 53158
(262) 947-0700
DATE OF MSDS PREPARATION: 10/21/99

PRIMARY HAZARD WARNING

Flammable. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone. Harmful or fatal if swallowed. May cause skin burns. Causes severe eye irritation. May be harmful if absorbed through the skin. Vapor and/or spray mist harmful if inhaled.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

REF	HAZARDOUS INGREDIENTS	PERCENT	CAS NUMBER	CARCINOGEN*
01	ACETYLACETONE	90- 100	123-54-6	
02	DIBUTYL TIN DILAURATE	1 - <5	77-58-7	

* Carcinogens: O = OSHA; A = ACGIH; N = NTP; I = IARC

SARA TITLE III & CERCLA CLASSIFICATIONS

SARA 311/312

REF	SARA 102 RQ (LBS)	SARA 302 TPQ (LBS)	SARA 313	AC	CH	FL	PR	RE
01	NOT ESTAB	NOT ESTAB	N	Y	N	Y	N	N
02	NOT ESTAB	NOT ESTAB	N	Y	N	N	N	N

SARA 311/312 CATEGORIES FOR THIS PRODUCT: ACUTE = Y, CHRONIC = N, FLAMMABILITY = Y, PRESSURE = N, REACTIVITY = N

OCCUPATIONAL EXPOSURE LIMITS HAVE BEEN ESTABLISHED FOR THE FOLLOWING MATERIALS:

REF	ACGIH		U.S. OSHA	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-STEL
01	NOT ESTAB.	NOT ESTAB.	NOT ESTAB.	NOT ESTAB.
01	IPEL-TWA: 20 ppm		IPEL-STEL: NOT ESTAB.	
02	0.1 mg/m ³	0.2 mg/m ³	S- 0.1 mg/m ³	NOT ESTAB.

[C- Ceiling Limit; S- Potential Skin Absorption; R- Respirable Dust] [NOT ESTAB. = NOT ESTABLISHED = NOT APPLICABLE]

PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT

All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3 - HAZARDS IDENTIFICATION**EFFECTS OF OVEREXPOSURE FROM:**

- ▶ **INGESTION:** Harmful or fatal if swallowed.
- ▶ **EYE CONTACT:** Causes severe eye irritation.
- ▶ **SKIN CONTACT:** May cause skin burns. May be harmful if absorbed through the skin.
- ▶ **INHALATION:** Vapor and/or spray mist harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage.
- ▶ **CHRONIC OVEREXPOSURE:** Avoid long-term and repeated contact. This product contains 2,4-pentadione. Animals repeatedly inhaling high concentrations (up to 650 ppm) had the following toxic effects: decreased body weight, nasal lining thickening, anemia, brain/thymus degeneration and death (650 ppm level only). The low odor threshold, unpleasant odor and nauseating effects at levels of a few ppm should provide adequate warning to prevent overexposure in the workplace.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eye watering, headaches, nausea, dizziness, and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

SECTION 4 - FIRST AID MEASURES

- ▶ **INGESTION:** If swallowed, give one to two eight ounce glasses of water, but do not induce vomiting. Gently wipe out inside mouth to remove any residual material.
- ▶ **EYE CONTACT:** In case of eye contact, remove contact lenses and flush eyes immediately with a gentle stream of luke warm water for at least 15 minutes.
- ▶ **SKIN CONTACT:** In case of skin contact, flush immediately with plenty of water for at least 15 minutes, followed by waterless hand cleaner and soap and water if the material appears to adhere to skin.
- ▶ **INHALATION:** If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other support measures as required.
- ▶ **OTHER:** If ingestion, any type of overexposure or symptoms of overexposure occur during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

Distributed by:
MATTHEWS PAINT COMPANY
LAKE VIEW CORPORATE PARK 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158

MSDS continued on page 3

SECTION 5 - FIRE FIGHTING MEASURES

- ▶ **FLASHPOINT:** 96 Degrees F (35 Degrees C) (PENSKY-MARTENS CLOSED CUP)
- ▶ **FLAMMABLE LIMITS:** Lower explosion limit (LEL): Not available
- ▶ **Upper explosion limit (UEL):** Not available
- ▶ **EXTINGUISHING MEDIA:** Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IC flammable liquid fires.
- ▶ **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat.
- ▶ **SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- ▶ **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.
- ▶ **WASTE DISPOSAL METHOD:** Waste material must be disposed of in accordance with federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7 - HANDLING AND STORAGE

- ▶ **HANDLING AND STORAGE PRECAUTIONS:** Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IC flammable liquids.
- ▶ **OTHER PRECAUTIONS:** Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

- ▶ **EYE PROTECTION:** Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.
- ▶ **SKIN PROTECTION:** Wear protective clothing sufficient to cover exposed skin surfaces. For applications where skin contact is likely and impermeable clothing is necessary, select clothing constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.
- ▶ **RESPIRATORY PROTECTION:** Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.
- ▶ **OTHER EQUIPMENT:** Clean contaminated clothing and shoes.

VENTILATION REQUIREMENTS: Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

(FORMULA VALUES, NOT SALES SPECIFICATIONS)

BOILING RANGE: 284- 284Degrees F	SOLUBILITY IN WATER: 16.3 %
VAPOR PRESSURE: N.A. mmHg	WEIGHT/GALLON (LBS): 8.15 (U.S.)
VAPOR DENSITY: Heavier than air	pH: Not applicable
% VOLATILE/VOLUME: 98.430	% SOLIDS BY WEIGHT: 1.68
SPECIFIC GRAVITY: .978	EVAPORATION RATE(BuOAc = 100): 75
ODOR/APPEARANCE: Viscous liquid with an odor characteristic of the solvents listed in Section 2.	

Distributed by:
MATTHEWS PAINT COMPANY
LAKE VIEW CORPORATE PARK 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158

SECTION 10 - STABILITY AND REACTIVITY

▶ This product is normally stable and will not undergo hazardous reactions.

▶ **INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID):** Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

▶ **HAZARDOUS DECOMPOSITION PRODUCTS:** May produce the following hazardous decomposition products when exposed to extreme heat: carbon dioxide ; carbon monoxide ; oxides of tin ; Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

▶ Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) Ratings:

HMIS Rating		NFPA Rating	
-----		-----	
HEALTH	3	HEALTH	3
FLAMMABILITY	3	FLAMMABILITY	3
REACTIVITY	0	INSTABILITY	0

Rating System: 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe, * = Chronic Effects.

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

THIS IS THE END OF THE MSDS FOR: 287437SP (00139341.002287437SP 10/21/99)