

**MATERIAL SAFETY DATA SHEET
MATTHEWS PAINT COMPANY**

Map SV954SP

Sign Silver

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

| | |
|---|---|
| PRODUCT CODE/IDENTITY: | SV954SP |
| REVISION DATE: | 01/05/99 (000) 0808 |
| CUSTOMER PART #/NAME: | |
| PRODUCT TRADE NAME: | FINE SILVER |
| CHEMICAL FAMILY: | Acrylic |
| EMERGENCY MEDICAL/SPILL INFO: | (800) 424-9300 CHEMTREC (U.S.) 91-800-00-214 (MEXICO) (514) 645-1320 (CANADA) |
| TECHNICAL INFORMATION: | (800) 323-6593 |
| PRODUCT SAFETY/MSDS INFORMATION: | 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158 (414) 947-0700 |
| DATE OF MSDS PREPARATION: | 04/06/99 |

PRIMARY HAZARD WARNING

Flammable. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone. Harmful if swallowed. May cause slight skin irritation. Causes eye irritation. Vapor and/or spray mist may be harmful if inhaled. Vapor irritates eyes, nose, and throat.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

Distributed by:
MATTHEWS PAINT COMPANY
LAKE VIEW CORPORATE PARK 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158

MSDS continued on page 2

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

| REF | HAZARDOUS INGREDIENTS | PERCENT | CAS NUMBER | CARCINOGEN* |
|-----|----------------------------|---------|------------|-------------|
| 01 | 1-METHOXY-2-PROPYL ACETATE | 5 - <10 | 108-65-6 | |
| 02 | METHYL (N-AMYL) KETONE | 5 - <10 | 110-43-0 | |
| 03 | XYLENES | 10- <20 | 1330-20-7 | |
| 04 | AROMATIC NAPHTHA | 1 - <5 | 64742-95-6 | |
| 05 | ALUMINUM POWDER | 5 - <10 | 7429-90-5 | |
| 06 | NAPHTHA | 1 - <5 | 8052-41-3 | |
| 07 | PARACHLOROBENZOTRIFLUORIDE | 20- <30 | 98-56-6 | |

* Carcinogens: O = OSHA; A = ACGIH; N = NTP; I = IARC

SARA TITLE III & CERCLA CLASSIFICATIONS

| REF | SARA 102 RQ (LBS) | SARA 302 TPQ (LBS) | SARA 313 | SARA 311/312 | | | | | |
|-----|-------------------|--------------------|----------|--------------|----|----|----|----|--|
| | | | | AC | CH | FL | PR | RE | |
| 01 | NOT ESTAB | NOT ESTAB | N | Y | N | Y | N | N | |
| 02 | NOT ESTAB | NOT ESTAB | N | Y | N | Y | N | N | |
| 03 | 100 | NOT ESTAB | Y | Y | N | Y | N | N | |
| 04 | NOT ESTAB | NOT ESTAB | N | Y | N | Y | N | N | |
| 05 | NOT ESTAB | NOT ESTAB | Y | N | N | Y | N | N | |
| 06 | NOT ESTAB | NOT ESTAB | N | Y | N | Y | N | N | |
| 07 | NOT ESTAB | NOT ESTAB | N | Y | Y | Y | N | N | |

SARA 311/312 CATEGORIES FOR THIS PRODUCT: ACUTE = Y, CHRONIC = Y, FLAMMABILITY = Y, PRESSURE = N, REACTIVITY = N

OCCUPATIONAL EXPOSURE LIMITS HAVE BEEN ESTABLISHED FOR THE FOLLOWING MATERIALS:

| REF | ACGIH | | U.S. OSHA | |
|-----|----------------------|------------|------------------------|------------|
| | TLV-TWA | TLV-STEL | PEL-TWA | PEL-STEL |
| 01 | NOT ESTAB. | NOT ESTAB. | NOT ESTAB. | NOT ESTAB. |
| 01 | IPEL-TWA: 100 ppm | | IPEL-STEL: NOT ESTAB. | |
| 02 | 50 ppm | NOT ESTAB. | 100 ppm | NOT ESTAB. |
| 03 | 100 ppm | 150 ppm | 100 ppm | 150 ppm |
| 04 | NOT ESTAB. | NOT ESTAB. | NOT ESTAB. | NOT ESTAB. |
| 05 | 10 mg/m ³ | NOT ESTAB. | R- 5 mg/m ³ | NOT ESTAB. |
| 06 | 100 ppm | NOT ESTAB. | 100 ppm | NOT ESTAB. |
| 07 | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB |
| 07 | IPEL-TWA: 25 ppm | | IPEL-STEL: NOT ESTAB. | |

[C- Ceiling Limit; S- Potential Skin Absorption; R- Respirable Dust] [NOT ESTAB. = NOT ESTABLISHED = NOT APPLICABLE]

PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT

All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3: HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE FROM:

- > **INGESTION:** Harmful if swallowed.
- > **EYE CONTACT:** Causes eye irritation.
- > **SKIN CONTACT:** May cause slight skin irritation.
- > **INHALATION:** Vapor and/or spray mist may be harmful if inhaled. Vapor irritates eyes, nose, and throat. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage.
- > **CHRONIC OVEREXPOSURE:** Avoid long-term and repeated contact. Prolonged exposure to an ingredient(s) in this product may cause kidney and/or liver damage.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eye watering, headaches, nausea, dizziness, and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

Distributed by:
 MATTHEWS PAINT COMPANY
 LAKE VIEW CORPORATE PARK 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

SECTION 4: FIRST AID MEASURES

- **INGESTION:** If swallowed, do not induce vomiting. Gently wipe out inside mouth to remove any residual material.
- **EYE CONTACT:** In case of eye contact, remove contact lenses and flush eyes immediately with a gentle stream of luke warm water for at least 15 minutes.
- **SKIN CONTACT:** In case of skin contact, flush immediately with plenty of water for at least 15 minutes followed by washing with soap and water.
- **INHALATION:** If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other support measures as required.
- **OTHER:** If ingestion, any type of overexposure or symptoms of overexposure occur during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

SECTION 5: FIRE FIGHTING MEASURES

- **FLASHPOINT:** 80 Degrees F (26 Degrees C) (PENSKY-MARTENS CLOSED CUP)
- **FLAMMABLE LIMITS:** Lower explosion limit (LEL): 1.2
- **Upper explosion limit (UEL):** Not available
- **EXTINGUISHING MEDIA:** Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IC flammable liquid fires.
- **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat.
- **SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.
- **WASTE DISPOSAL METHOD:** Waste material must be disposed of in accordance with federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7: HANDLING AND STORAGE

- **HANDLING AND STORAGE PRECAUTIONS:** Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IC flammable liquids.
- **OTHER PRECAUTIONS:** Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

- **EYE PROTECTION:** Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.
- **SKIN PROTECTION:** Wear protective clothing. Gloves should be constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.
- **RESPIRATORY PROTECTION:** Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.
- **OTHER EQUIPMENT:** Clean contaminated clothing and shoes.

VENTILATION REQUIREMENTS: Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products