

MATERIAL SAFETY DATA SHEET  
MATTHEWS PAINT COMPANY

SVOC MSDS #1

**SECTION 1 - CHEMICAL, PRODUCT, AND COMPANY INFORMATION**

<b>PRODUCT CODE/IDENTITY:</b>	<b>SVOC</b>
<b>REVISION DATE:</b>	04/05/99 ( T ) 0809
<b>CUSTOMER PART #/NAME:</b>	Not applicable
<b>PRODUCT TRADE NAME:</b>	SATIN VOC MAP
<b>CHEMICAL FAMILY:</b>	ACRYLIC
<b>EMERGENCY MEDICAL/SPILL INFO:</b>	(800) 424-9300 CHEMTREC (U.S.) 91-800-00-214 (MEXICO) (514) 645-1320 (CANADA)
<b>TECHNICAL INFORMATION:</b>	(800) 323-6593
<b>PRODUCT SAFETY/MSDS INFORMATION:</b>	8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158 (262) 947-0700
<b>DATE OF MSDS PREPARATION:</b>	10/14/99

**PRIMARY HAZARD WARNING**

Flammable. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone. Harmful if swallowed. May cause slight skin irritation. Causes eye irritation. Vapor and/or spray mist may be harmful if inhaled. Vapor irritates eyes, nose, and throat.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

Distributed by:  
MATTHEWS PAINT COMPANY  
LAKE VIEW CORPORATE PARK 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN 53158

MSDS continued on page 2

#### **SECTION 4 - FIRST AID MEASURES**

- ▶ **INGESTION:** If swallowed, do not induce vomiting. Gently wipe out inside mouth to remove any residual material.
- ▶ **EYE CONTACT:** In case of eye contact, remove contact lenses and flush eyes immediately with a gentle stream of luke warm water for at least 15 minutes.
- ▶ **SKIN CONTACT:** In case of skin contact, flush immediately with plenty of water for at least 15 minutes followed by washing with soap and water.
- ▶ **INHALATION:** If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other support measures as required.
- ▶ **OTHER:** If ingestion, any type of overexposure or symptoms of overexposure occur during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

#### **SECTION 5 - FIRE FIGHTING MEASURES**

- ▶ **FLASHPOINT:** 72 Degrees F ( 22 Degrees C) (PENSKY-MARTENS CLOSED CUP)
- ▶ **FLAMMABLE LIMITS:** Lower explosion limit (LEL): 1.2
- ▶ **Upper explosion limit (UEL):** Not available
- ▶ **EXTINGUISHING MEDIA:** Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IB flammable liquid fires.
- ▶ **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat.
- ▶ **SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

- ▶ **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.
- ▶ **WASTE DISPOSAL METHOD:** Waste material must be disposed of in accordance with federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

#### **SECTION 7 - HANDLING AND STORAGE**

- ▶ **HANDLING AND STORAGE PRECAUTIONS:** Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IB flammable liquids.
- ▶ **OTHER PRECAUTIONS:** Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

#### **SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

##### **PERSONAL PROTECTIVE EQUIPMENT FOR:**

- ▶ **EYE PROTECTION:** Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.
- ▶ **SKIN PROTECTION:** Wear protective clothing. Gloves should be constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.
- ▶ **RESPIRATORY PROTECTION:** Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.
- ▶ **OTHER EQUIPMENT:** Clean contaminated clothing and shoes.

**VENTILATION REQUIREMENTS:** Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.