

MATERIAL SAFETY DATA SHEET

MATTHEWS PAINT COMPANY

SECTION 1 - CHEMICAL, PRODUCT, AND COMPANY INFORMATION

PRODUCT CODE/IDENTITY: VOC920SP

PRODUCT TRADE NAME: BLUE

REVISION DATE: 01/05/99 (000) 0808

CUSTOMER PART #/NAME: Not applicable

CHEMICAL FAMILY: Acrylic

EMERGENCY MEDICAL/SPILL INFO: (800) 424-9300 CHEMTREC (U.S.) 91-800-00-214
(MEXICO) (514) 645-1320 (CANADA)

TECHNICAL INFORMATION: (800) 323-6593

PRODUCT SAFETY/MSDS INFORMATION: 8201 - 100TH STREET PLEASANT PRAIRIE, WISCONSIN
53158 (262) 947-0700

DATE OF MSDS PREPARATION: 05/25/01

PRIMARY HAZARD WARNING

Flammable. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone. Harmful if swallowed. May cause moderate skin irritation. Causes severe eye irritation. May be absorbed through the skin. Vapor and/or spray mist may be harmful if inhaled. Vapor irritates eyes, nose, and throat.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

TRANSPORTATION OF DANGEROUS GOODS

PROPER SHIPPING NAME: Paint

NOS TECHNICAL NAME: None

HAZARD CLASS: 3

SUBSIDIARY CLASS: None

UN NUMBER: UN1263

PACKING GROUP: II

MARINE POLLUTANT: None

USA-RQ, HAZARDOUS SUBSTANCE: None

USA-RQ, HAZARDOUS SUBSTANCE THRESHOLD SHIP WEIGHT: None

CANADA SCHEDULE XIII, 9.2: None

CANADA SCHEDULE XIII, 9.2 THRESHOLD SHIP WEIGHT: None

REF	SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS			CARCINOGEN*
	HAZARDOUS INGREDIENTS	PERCENT	CAS NUMBER	
01	METHYL ISOBUTYL KETONE	10- <20	108-10-1	
02	METHYL (N-AMYL) KETONE	10- <20	110-43-0	
03	N-BUTYL ACETATE	10- <20	123-86-4	
04	PHTHALOCYANINE PIGMENT BLUE 15	5 - <10	147-14-8	

* Carcinogens: O=OSHA; A=ACGIH; N=NTP; I=IARC

SARA TITLE III & CERCLA CLASSIFICATIONS

REF	SARA 102 RQ (LBS)	SARA 302 TPQ (LBS)	SARA 313	SARA 311/312			
				AC	CH	FL	PR RE
01	5000 lbs	NOT ESTAB	Y	Y	N	Y	N N
02	NOT ESTAB	NOT ESTAB	N	Y	N	Y	N N
03	5000 lbs	NOT ESTAB	N	Y	N	Y	N N
04	NOT ESTAB	NOT ESTAB	N	N	N	N	N N
04	NOT ESTAB	NOT ESTAB	N				(CU CMPD)
04	NOT ESTAB	NOT ESTAB	N				(AS CU)

SARA 311/312 CATEGORIES FOR THIS PRODUCT: ACUTE= Y, CHRONIC= N, FLAMMABILITY= Y, PRESSURE= N, REACTIVITY= N

OCCUPATIONAL EXPOSURE LIMITS HAVE BEEN ESTABLISHED FOR THE FOLLOWING MATERIALS:

REF	ACGIH		U.S. OSHA		
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-STEL	
01	50 ppm	75 ppm	50 ppm	75 ppm	
02	50 ppm	NOT ESTAB	100 ppm	NOT ESTAB	
03	150 PPM	200 ppm	150 ppm	200 ppm	
04	1 mg/m3	NOT ESTAB	1 mg/m3	NOT ESTAB	
04	NOT ESTAB	NOT ESTAB	NOT ESTAB	NOT ESTAB (CU CMPD)	
04	NOT ESTAB	NOT ESTAB	NOT ESTAB	NOT ESTAB (AS CU)	

[C- Ceiling Limit; S- Potential Skin Absorption; R- Respirable Dust]

REF ACGIH TLV - BASIS - CRITICAL EFFECT(S)

01	irritation; narcosis; liver; kidney
02	irritation
03	irritation
04	NOT ESTAB.
04	(CU CMPD) ...NOT ESTAB.
04	(AS CU) ...NOT ESTAB.

[ACGIH TLV BASIS - CRITICAL EFFECT(S): CNS-CENTRAL NERVOUS SYSTEM; CVS-CARDIOVASCULAR SYSTEM; CWP-COAL WORKER'S PNEUMOCONIOSIS; GI-GASTROINTESTINAL] [NOT ESTAB.= NOT ESTABLISHED = NOT APPLICABLE] [NOT ESTAB. = NOT ESTABLISHED = NOT APPLICABLE]

PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT

All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: Harmful if swallowed.

EYE CONTACT: Causes severe eye irritation.

SKIN CONTACT: May cause moderate skin irritation. May be absorbed through the skin.

INHALATION: Vapor and/or spray mist may be harmful if inhaled. Vapor irritates eyes, nose, and throat. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage.

CHRONIC OVEREXPOSURE: Avoid long-term and repeated contact.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eye watering, headaches, nausea, dizziness, and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

SECTION 4 - FIRST AID MEASURES

IMPORTANT FIRST AID INFORMATION: If ingestion, any type of overexposure or symptoms of overexposure occur during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

INGESTION: Gently wipe or rinse the inside of the mouth with water. Sips of water may be given. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

EYE CONTACT: Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

SKIN CONTACT: Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact a poison control center, emergency room, or physician as further treatment may be necessary.

INHALATION: Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

SECTION 5 - FIRE FIGHTING MEASURES

FLASHPOINT: 61 Degrees F (16 Degrees C) (PENSKEY-MARTENS CLOSED CUP)

FLAMMABLE LIMITS: Lower explosion limit (LEL): 1.4

Upper explosion limit (UEL): Not available

EXTINGUISHING MEDIA: Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IB flammable liquid fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

WASTE DISPOSAL METHOD: Waste material must be disposed of in accordance with federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7 - HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Do not store above 120 degrees F. (48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IB flammable liquids.

OTHER PRECAUTIONS: Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

EYE PROTECTION: Wear chemical-type splash goggles or full face shield when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

SKIN PROTECTION: Wear protective clothing to prevent skin contact. Apron and gloves should be constructed of: butyl rubber. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.

RESPIRATORY PROTECTION: Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its

limitations, and how it is to be properly fitted and used.

OTHER EQUIPMENT: Clean contaminated clothing and shoes.

VENTILATION REQUIREMENTS: Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

[FORMULA VALUES, NOT SALES SPECIFICATIONS]

BOILING RANGE: 230- 340Degrees F

SOLUBILITY IN WATER: .8 %

VAPOR PRESSURE: 9.0 mmHg

WEIGHT/GALLON (LBS): 8.43 (U.S.)

VAPOR DENSITY: Heavier than air

pH: Not determined

% VOLATILE/VOLUME: 43.210

% SOLIDS BY WEIGHT: 64.50

SPECIFIC GRAVITY: 1.012

EVAPORATION RATE(BuOAc=100): 102

ODOR/APPEARANCE: Viscous liquid with an odor characteristic of the solvents listed in Section 2.

SECTION 10 - STABILITY AND REACTIVITY

This product is normally stable but may undergo hazardous reactions at extremely high temperatures and pressures.

INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID): Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce the following hazardous decomposition products when exposed to extreme heat: carbon monoxide ; carbon dioxide ; chlorinated products ; oxides of copper ; hydrogen cyanide ; oxides of nitrogen ; Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) Ratings:

HMIS Rating		NFPA Rating	
HEALTH	2	HEALTH	2
FLAMMABILITY	3	FLAMMABILITY	3
REACTIVITY	1	INSTABILITY	1

Rating System:0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

Safe handling of this product requires that all of the information on the MSDS

be evaluated for specific work environments and conditions of use.

THIS IS THE END OF THE MSDS FOR: VOC920SP (00140257.002)

MATTHEWS PAINT COMPANY

LAKE VIEW CORPORATE PARK

8201 - 100TH STREET

PLEASANT PRAIRIE, WISCONSIN 53158

H\