



Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Jul-24-2009

Revision Date Jul-24-2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product code 17147
Product name Halftone Yellow (MTR)
Product description 1700 VersaPrint® UV Screen Ink

Manufacturer or supplier's details

UNITED STATES
Nazdar Company
8501 Hedge Lane Terrace
Shawnee, KS 66227
Tel: 1-913-422-1888
Tel: 1-800-677-4657
Fax: 1-913-422-2294

UNITED KINGDOM
Nazdar Limited
7 Barton Road
Heaton Mersey Industrial Estate
Stockport, Chesire SK4 3EG
Tel: +44 161 442 2111

Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887

Website: www.nazdar.com
MSDS Information: 1-913-422-1888 ext 2305
MSDS Contact: Regulatory Compliance
email: regcomp@nazdar.com

2. HAZARDS IDENTIFICATION

This product is a preparation. Health hazard information is based on its components.

Appearance Viscous liquid
Emergency Overview Irritant. Sensitizer.

Eyes Moderately irritating to the eyes. The liquid splashed in the eyes may cause irritation and reversible damage.

Skin Moderate skin irritation. Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation May cause irritation of respiratory tract. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Ingestion Ingestion may cause irritation to mucous membranes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS-No | Weight % |
|-----------------------|--------------|----------|
| Glycol ether acrylate | Trade Secret | 30 - 60 |
| N-vinylcaprolactam | 2235-00-9 | 10 - 30 |
| Acrylated Monomer | Trade Secret | 5 - 10 |
| Acrylated Monomer | Trade Secret | 5 - 10 |
| Photoinitiator | Trade Secret | 1 - 5 |
| Photoinitiator | Trade Secret | 1 - 5 |
| Photoinitiator | Trade Secret | 1 - 5 |

4. FIRST AID MEASURES

Eye Contact May produce an allergic reaction. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin Contact May cause allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.

Inhalation Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion May produce an allergic reaction. If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flammable Properties No information available

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers. To avoid thermal decomposition, do not overheat. Fire or intense heat may cause violent rupture of packages.

Specific Hazards Arising from the Chemical May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Methods for Cleaning Up Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.

Environmental Precautions Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed.

Storage Keep at temperatures between 9.9°C and 31.9°C. Keep container closed when not in use. Keep out of the reach of children. Keep away from direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Respiratory Protection

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

Eye Protection

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

Skin Protection

Wear protective gloves/clothing. Solvent-resistant apron and boots.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------------------------|--------------------------|--|----------------------------------|
| Appearance | Viscous liquid | Physical State | Liquid |
| Odor | Mild Sweet Acrylic | Odor Threshold | No information available |
| pH | No information available | Autoignition Temperature | No information available |
| Boiling point/Boiling Range | >149°C / >300°F | Melting Point/Range | No information available |
| Freezing Point/Range | No information available | Solubility | No information available |
| Evaporation Rate | No information available | Partition Coefficient (n-octanol/water) | No information available |
| Vapour Pressure | No information available | Vapour Density | Heavier than air |
| Flammability (solid, gas) | No information available | Flash Point | > 93°C / > 200°F |
| Flammability Limits in Air | | Method | Pensky Martens Closed Cup (PMCC) |
| Upper | No information available | Photochemically Reactive | No |
| Lower | No information available | Specific Gravity | 1.082 |
| Weight Per Gallon (lbs/gal) | 9.023 | VOC by volume | No information available |
| VOC by weight | 0.178 | VOC grams/liter (less water) | 1.921 |
| VOC lbs/gal (less water) | 0.016 | | |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to Avoid | Temperatures above 93°C. Keep away from direct sunlight. |
| Incompatible Products | Strong acids. Strong bases. Strong oxidizing agents. Reducing agents. |
| Hazardous Decomposition Products | Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO ₂). Carbon monoxide. |
| Possibility of Hazardous Reactions | None under normal processing. Do not store for longer periods at temperatures above 93°C. |

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------------------|--------------------|-----------------------|-----------------|
| Glycol ether acrylate | 4660 µL/kg (Rat) | 2540 µL/kg (Rabbit) | |
| Acrylated Monomer | 1030 mg/kg (Rat) | | |
| Acrylated Monomer | 4890 mg/kg (Rat) | 5 g/kg (Rabbit) | |

Chronic Toxicity

No information available

| | |
|------------------------------|---|
| Sensitisation | May cause sensitization of susceptible persons. |
| Mutagenic Effects | No information available |
| Reproductive Effects | No information available |
| Developmental Effects | No information available |

| | |
|-----------------------------|---|
| Teratogenicity | No information available |
| Chronic Effects | Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. |
| Target Organ Effects | No information available |

12. ECOLOGICAL INFORMATION

Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

| | |
|--|--------------------------|
| Persistence and Degradability | No information available |
| Bioaccumulation | No information available |
| Mobility in Environmental Media | No information available |

13. DISPOSAL CONSIDERATIONS

| | |
|-------------------------------|--|
| Waste Disposal Methods | Dispose of contents/container in accordance with local regulation. |
| Contaminated Packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. TRANSPORT INFORMATION

DOT

Printing Ink, Not Regulated

ICAO/IATA

Not classified as dangerous in the meaning of transport regulations

IMDG/IMO

Not classified as dangerous in the meaning of transport regulations

15. REGULATORY INFORMATION

International Inventories

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Component | CAS-No | Weight % | SARA 313 - Threshold Values |
|-----------------------|---------|----------|-----------------------------|
| Glycol ether acrylate | Mixture | 30 - 60 | 1.0 |

The above glycol ether acrylate is considered a reactive chemical in ultraviolet curable inks. Once initiated by a high dose of ultraviolet light, this glycol ether acrylate rapidly polymerizes (i.e. hardens) and becomes part of the ink film. The polymerization process of UV curable inks is measured in milliseconds.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

| Component | CAS-No | Weight % |
|-----------------------|---------|----------|
| Glycol ether acrylate | Mixture | 30 - 60 |

U.S. State Regulations**State Right-to-Know**

| Component | Minnesota | Florida | New Jersey | Pennsylvania | Massachusetts | Rhode Island |
|-----------------------|------------|------------|------------|--------------|---------------|--------------|
| Glycol ether acrylate | Not Listed | Not Listed | X | X | Not Listed | Not Listed |
| N-vinylcaprolactam | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Acrylated Monomer | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Acrylated Monomer | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Photoinitiator | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Photoinitiator | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Photoinitiator | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006

Does NOT contain a listed substance

| | | | | |
|--------------|---------------|---------------------|-------------------|------------|
| HMIS: | Health | Flammability | Reactivity | PPE |
| | 2 | 1 | 1 | X |

16. OTHER INFORMATION

Revision Date Jul-24-2009

Revision Summary New MSDS format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of MSDS