



Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Apr-22-2009

Revision Date Apr-22-2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product code 59LF132
Product name Lemon Yellow
Product description 59000 Series Enamel Plus Gloss Screen Ink

Manufacturer or supplier's details

UNITED STATES
Nazdar Company
8501 Hedge Lane Terrace
Shawnee, KS 66227
Tel: 1-913-422-1888
Tel: 1-800-677-4657
Fax: 1-913-422-2294

UNITED KINGDOM
Nazdar Limited
7 Barton Road
Heaton Mersey Industrial Estate
Stockport, Chesire SK4 3EG
Tel: +44 161 442 2111

Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887

Website: www.nazdar.com
MSDS Information: 1-913-422-1888 ext 2305
MSDS Contact: Regulatory Compliance
email: regcomp@nazdar.com

2. HAZARDS IDENTIFICATION

This product is a preparation. Health hazard information is based on its components.

Appearance Viscous liquid
Flammable Properties Combustible liquid and vapor.
Emergency Overview Harmful. Aspiration hazard. Harmful: may cause lung damage if swallowed.
Eyes May cause eye irritation.
Skin May cause skin irritation and/or dermatitis.
Inhalation Harmful by inhalation. Avoid breathing vapors or mists. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.
Ingestion Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Risk of serious damage to the lungs (by aspiration).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30
Barium sulfate	7727-43-7	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Ethyl benzene (contaminant)	100-41-4	< 0.5
Crystalline silica (cristobalite)	14464-46-1	< 0.5

- Component names which have the word (contaminant) are constituents contained in Aromatic Hydrocarbon ingredients and are an integral part of the ingredient and cannot be separated. The percentage listed for the contaminant is as contained in the Hydrocarbon ingredient. (Example: 100% Hydrocarbon, 10% Contaminant A, 3% Contaminant B)

4. FIRST AID MEASURES

Skin Contact Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Inhalation Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flammable Properties Combustible liquid and vapor.

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages.

Specific Hazards Arising from the Chemical Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Methods for Cleaning Up Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.

Environmental Precautions Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition. Take notice of the directions of use on the label.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	Weight %	ACGIH TLV	OSHA PEL	Ontario TWA EV
Barium sulfate	10 - 30	TWA: 0.5 mg/m ³ TWA: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³
Titanium dioxide	1 - 5	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³

Component	Weight %	ACGIH TLV	OSHA PEL	Ontario TWAEV
Ethyl benzene (contaminant)	< 0.5	TWA: 100 ppm STEL: 125 ppm	TWA: 435 mg/m ³ TWA: 100 ppm STEL: 125 ppm STEL: 545 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 540 mg/m ³
Crystalline silica (cristobalite)	< 0.5	TWA: 0.025 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³

Component	Weight %	NIOSH IDLH	Mexico OEL (TWA)
Barium sulfate	10 - 30		TWA: 0.5 mg/m ³
Titanium dioxide	1 - 5	5000 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
Ethyl benzene (contaminant)	< 0.5	800 ppm 10% LEL	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 545 mg/m ³ STEL: 125 ppm
Crystalline silica (cristobalite)	< 0.5	25 mg/m ³	TWA: 0.05 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Engineering Measures

Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Respiratory Protection

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

Eye Protection

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

Skin Protection

Wear protective gloves/clothing. Solvent-resistant apron and boots.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Viscous liquid	Physical State	Liquid
Odor	Characteristic	Odor Threshold	No information available
pH	No information available	Autoignition Temperature	No information available
Boiling point/Boiling Range	>149°C / >300°F	Melting Point/Range	No information available
Freezing Point/Range	No information available	Solubility	No information available
Evaporation Rate	No information available	Partition Coefficient (n-octanol/water)	No information available
Vapour Pressure	No information available	Vapour Density	Heavier than air
Flammability (solid, gas)	No information available	Flash Point	46°C / 115°F
Flammability Limits in Air		Method	Setaflash closed cup
Upper	No information available	Photochemically Reactive	No
Lower	No information available		
Weight Per Gallon (lbs/gal)	9.997	Specific Gravity	1.2
VOC by weight	26.171	VOC by volume	No information available
VOC lbs/gal	2.616	VOC grams/liter	313.501

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.

Hazardous Decomposition Products Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO₂). Carbon monoxide.

Possibility of Hazardous Reactions None under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated light	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	5.2 mg/L (Rat) 4 h
Titanium dioxide	10000 mg/kg (Rat)		
Ethyl benzene (contaminant)	3500 mg/kg (Rat)	15354 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h

Chronic Toxicity

Component	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Ethyl benzene (contaminant)	A3	Group 2B		X
Crystalline silica (cristobalite)	A2	Group 1		X

Legend:

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)

OSHA: (Occupational Safety & Health Administration)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

X - Present

Sensitisation

No information available

Mutagenic Effects

No information available

Reproductive Effects

No information available

Developmental Effects

No information available

Teratogenicity

No information available

Chronic Effects

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

Target Organ Effects

Eyes, Lungs, Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

Component	Freshwater Algae	Freshwater Fish	Water Flea
Petroleum distillates, hydrotreated light		96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static]	96 Hr LC50 Den-dronereides heteropoda: 4720 mg/L

Component	Freshwater Algae	Freshwater Fish	Water Flea
Ethyl benzene (contaminant)	72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L	96 Hr LC50 Oncorhynchus mykiss: 14.0 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.09 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 150.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 48.5 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static]	48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L

Persistence and Degradability	No information available
Bioaccumulation	No information available
Mobility in Environmental Media	No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods	Dispose of contents/container in accordance with local regulation.
Contaminated Packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

UN1210, Printing Ink, 3, III
In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

ICAO/IATA

UN1210, Printing Ink, 3, III

IMDG/IMO

UN1210, Printing Ink, 3, III

15. REGULATORY INFORMATION

International Inventories

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Ethyl benzene (contaminant)	100-41-4	< 0.5	0.1
Barium sulfate	7727-43-7	10 - 30	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

U.S. State Regulations**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Component	CAS-No	Weight %
Ethyl benzene (contaminant)	100-41-4	< 0.5
Toluene	108-88-3	< 0.0001
Benzene	71-43-2	< 0.0001
Ethyl alcohol	64-17-5	< 0.01
Quartz, crystalline silica	14808-60-7	< 0.001

State Right-to-Know

Component	Minnesota	Florida	New Jersey	Pennsylvania	Massachusetts	Rhode Island
Petroleum distillates, hydrotreated light	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Barium sulfate	Not Listed	Not Listed	X	X	X	X
Titanium dioxide	Not Listed	Not Listed	X	X	X	X
Ethyl benzene (contaminant)	Not Listed	Not Listed	X	X	X	X
Crystalline silica (cristobalite)	Not Listed	Not Listed	X	X	X	Not Listed

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

Component	WHMIS Classifications of Components
Barium sulfate	Uncontrolled product according to WHMIS classification criteria
Titanium dioxide	D2A
Ethyl benzene (contaminant)	B2, D2A, D2B
Crystalline silica (cristobalite)	D2A

Component	NPRI - National Pollutant Release Inventory
Petroleum distillates, hydrotreated light	Part 5 Substance
Ethyl benzene (contaminant)	Part 1, Group 1 Substance Part 4 Substance

REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006

Does NOT contain a listed substance

HMIS: Health 1* Flammability 2 Reactivity 0 PPE X

16. OTHER INFORMATION

Revision Date Apr-22-2009

Revision Summary New MSDS format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of MSDS

