



Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Apr-22-2009

Revision Date Apr-22-2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product code 59LF148
Product name Medium Green
Product description 59000 Series Enamel Plus Gloss Screen Ink

Manufacturer or supplier's details

UNITED STATES
Nazdar Company
8501 Hedge Lane Terrace
Shawnee, KS 66227
Tel: 1-913-422-1888
Tel: 1-800-677-4657
Fax: 1-913-422-2294

UNITED KINGDOM
Nazdar Limited
7 Barton Road
Heaton Mersey Industrial Estate
Stockport, Cheshire SK4 3EG
Tel: +44 161 442 2111

Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887

Website: www.nazdar.com
MSDS Information: 1-913-422-1888 ext 2305
MSDS Contact: Regulatory Compliance
email: regcomp@nazdar.com

2. HAZARDS IDENTIFICATION

This product is a preparation. Health hazard information is based on its components.

Appearance Viscous liquid
Flammable Properties Combustible liquid and vapor.
Emergency Overview Harmful. Aspiration hazard. Harmful: may cause lung damage if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Eyes May cause eye irritation.
Skin May cause skin irritation and/or dermatitis.
Inhalation Harmful by inhalation. Avoid breathing vapors or mists. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough.

Ingestion Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Risk of serious damage to the lungs (by aspiration).

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS-No | Weight % |
|---|--------------|----------|
| Petroleum distillates, hydrotreated light | 64742-47-8 | 10 - 30 |
| Barium sulfate | 7727-43-7 | 10 - 30 |
| Pigment Blue | Trade Secret | 1 - 5 |
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Naphthalene (contaminant) | 91-20-3 | < 0.5 |
| Ethyl benzene (contaminant) | 100-41-4 | < 0.5 |
| Crystalline silica (cristobalite) | 14464-46-1 | < 0.5 |

- Component names which have the word (contaminant) are constituents contained in Aromatic Hydrocarbon ingredients and are an integral part of the ingredient and cannot be separated. The percentage listed for the contaminant is as contained in the Hydrocarbon ingredient. (Example: 100% Hydrocarbon, 10% Contaminant A, 3% Contaminant B)

4. FIRST AID MEASURES

Skin Contact Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.

| | |
|--------------------|---|
| Eye Contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists. |
| Inhalation | Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately. |
| Ingestion | If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person. |

5. FIRE-FIGHTING MEASURES

| | |
|--|--|
| Flammable Properties | Combustible liquid and vapor. |
| Suitable Extinguishing Media | Foam. Carbon dioxide (CO ₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective Equipment and Precautions for Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages. |
| Specific Hazards Arising from the Chemical | Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------------|--|
| Personal Precautions | Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. |
| Methods for Cleaning Up | Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools. |
| Environmental Precautions | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |

7. HANDLING AND STORAGE

| | |
|-----------------|--|
| Handling | Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed. |
| Storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition. Take notice of the directions of use on the label. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Component | Weight % | ACGIH TLV | OSHA PEL | Ontario TWAEV |
|----------------|----------|--|--|---------------------------|
| Barium sulfate | 10 - 30 | TWA: 0.5 mg/m ³ TWA: 10 mg/m ³ | TWA: 5 mg/m ³ TWA: 10 mg/m ³ TWA: 15 mg/m ³ | TWA: 10 mg/m ³ |

| Component | Weight % | ACGIH TLV | OSHA PEL | Ontario TWAEV |
|-----------------------------------|----------|-------------------------------|---|---|
| Pigment Blue | 1 - 5 | TWA: 1 mg/m ³ | | |
| Titanium dioxide | 1 - 5 | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ TWA: 15 mg/m ³ | TWA: 10 mg/m ³ |
| Naphthalene (contaminant) | < 0.5 | TWA: 10 ppm Skin STEL: 15 ppm | TWA: 50 mg/m ³ TWA: 10 ppm STEL: 15 ppm STEL: 75 mg/m ³ | TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 78 mg/m ³ |
| Ethyl benzene (contaminant) | < 0.5 | TWA: 100 ppm STEL: 125 ppm | TWA: 435 mg/m ³ TWA: 100 ppm STEL: 125 ppm STEL: 545 mg/m ³ | TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 540 mg/m ³ |
| Crystalline silica (cristobalite) | < 0.5 | TWA: 0.025 mg/m ³ | TWA: 0.05 mg/m ³ | TWA: 0.05 mg/m ³ |

| Component | Weight % | NIOSH IDLH | Mexico OEL (TWA) |
|-----------------------------------|----------|--|---|
| Barium sulfate | 10 - 30 | | TWA: 0.5 mg/m ³ |
| Pigment Blue | 1 - 5 | 25 mg/m ³ except Hydrogen cyanide | TWA: 1 mg/m ³ TWA: 5 mg/m ³ STEL: 2 mg/m ³ |
| Titanium dioxide | 1 - 5 | 5000 mg/m ³ | TWA: 10 mg/m ³ STEL: 20 mg/m ³ |
| Naphthalene (contaminant) | < 0.5 | 250 ppm | TWA: 10 ppm TWA: 50 mg/m ³ STEL: 75 mg/m ³ STEL: 15 ppm |
| Ethyl benzene (contaminant) | < 0.5 | 800 ppm 10% LEL | TWA: 100 ppm TWA: 435 mg/m ³ STEL: 545 mg/m ³ STEL: 125 ppm |
| Crystalline silica (cristobalite) | < 0.5 | 25 mg/m ³ | TWA: 0.05 mg/m ³ |

NIOSH IDLH: Immediately Dangerous to Life or Health

Engineering Measures

Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Respiratory Protection

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

Eye Protection

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

Skin Protection

Wear protective gloves/clothing. Solvent-resistant apron and boots.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------------------------|--------------------------|--|--------------------------|
| Appearance | Viscous liquid | Physical State | Liquid |
| Odor | Characteristic | Odor Threshold | No information available |
| pH | No information available | Autoignition Temperature | No information available |
| Boiling point/Boiling Range | >149°C / >300°F | Melting Point/Range | No information available |
| Freezing Point/Range | No information available | Solubility | No information available |
| Evaporation Rate | No information available | Partition Coefficient (n-octanol/water) | No information available |
| Vapour Pressure | No information available | Vapour Density | Heavier than air |
| Flammability (solid, gas) | No information available | Flash Point | 46°C / 115°F |
| Flammability Limits in Air | | Method | Setaflash closed cup |
| Upper | No information available | Photochemically Reactive | No |
| Lower | No information available | | |
| Weight Per Gallon (lbs/gal) | 9.551 | Specific Gravity | 1.15 |
| VOC by weight | 31.209 | VOC by volume | 38.245 |
| VOC lbs/gal | 2.984 | VOC grams/liter | 357.54 |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to Avoid | Heat, flames and sparks. |
| Incompatible Products | Strong acids. Strong bases. Strong oxidizing agents. Reducing agents. |
| Hazardous Decomposition Products | Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO ₂). Carbon monoxide. |
| Possibility of Hazardous Reactions | None under normal processing. |

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|---------------------|---------------------------------------|-----------------------------------|
| Petroleum distillates, hydrotreated light | 5000 mg/kg (Rat) | 2000 mg/kg (Rabbit) | 5.2 mg/L (Rat) 4 h |
| Pigment Blue | 5000 mg/kg (Rat) | | |
| Naphtha (petroleum), heavy aromatic | 5000 mg/kg (Rat) | 2000 mg/kg (Rabbit) | 590 mg/m ³ (Rat) 4 h |
| Titanium dioxide | 10000 mg/kg (Rat) | | |
| Naphthalene (contaminant) | 490 mg/kg (Rat) | 2500 mg/kg (Rat) 20 g/kg (Rabbit) | 340 mg/m ³ (Rat) 1 h |
| Ethyl benzene (contaminant) | 3500 mg/kg (Rat) | 15354 mg/kg (Rabbit) | 17.2 mg/L (Rat) 4 h |

Chronic Toxicity

| Component | ACGIH | IARC | NTP | OSHA |
|-----------------------------------|-------|----------|------------------------|------|
| Titanium dioxide | | Group 2B | | X |
| Naphthalene (contaminant) | | Group 2B | Reasonably Anticipated | X |
| Ethyl benzene (contaminant) | A3 | Group 2B | | X |
| Crystalline silica (cristobalite) | A2 | Group 1 | | X |

Legend:

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)
OSHA: (Occupational Safety & Health Administration)

Reasonably Anticipated to be a Human Carcinogen
X - Present

| | |
|------------------------------|--|
| Sensitisation | No information available |
| Mutagenic Effects | No information available |
| Reproductive Effects | No information available |
| Developmental Effects | No information available |
| Teratogenicity | No information available |
| Chronic Effects | Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. |
| Target Organ Effects | Eyes, Gastrointestinal tract, Liver, Lungs, Respiratory system, Skin. |

12. ECOLOGICAL INFORMATION

Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

| Component | Freshwater Algae | Freshwater Fish | Water Flea |
|---|---|---|--|
| Petroleum distillates, hydrotreated light | | 96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static] | 96 Hr LC50 Den-dronereides heteropoda: 4720 mg/L |
| Pigment Blue | | 96 Hr LC50 Leuciscus idus: >1000 mg/L [semi-static] | |
| Naphtha (petroleum), heavy aromatic | 72 Hr EC50 Skeletonema costatum: 2.5 mg/L | 96 Hr LC50 Pimephales promelas: 19 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.34 mg/L; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static] | 48 Hr EC50 Daphnia magna: 0.95 mg/L |
| Naphthalene (contaminant) | 96 Hr EC50 Skeletonema costatum: 0.4 mg/L | 96 Hr LC50 Pimephales promelas: 1.99 mg/L [static] | 48 Hr EC50 water flea: 2.16 mg/L |
| Ethyl benzene (contaminant) | 72 Hr EC50 Selenastrum capricornutum: 4.6 mg/L; 96 Hr EC50 Selenastrum capricornutum: >438 mg/L | 96 Hr LC50 Oncorhynchus mykiss: 14.0 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.09 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 150.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 48.5 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static] | 48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L |

| | |
|--|--------------------------|
| Persistence and Degradability | No information available |
| Bioaccumulation | No information available |
| Mobility in Environmental Media | No information available |

| Component | log Pow |
|-------------------------------------|-----------|
| Naphtha (petroleum), heavy aromatic | 2.9 - 6.1 |

13. DISPOSAL CONSIDERATIONS

| | |
|-------------------------------|--|
| Waste Disposal Methods | Dispose of contents/container in accordance with local regulation. |
|-------------------------------|--|

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

UN1210, Printing Ink, 3, III

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

ICAO/IATA

UN1210, Printing Ink, 3, III

IMDG/IMO

UN1210, Printing Ink, 3, III

15. REGULATORY INFORMATION

International Inventories

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Component | CAS-No | Weight % | SARA 313 - Threshold Values |
|-----------------------------|-----------|----------|-----------------------------|
| Ethyl benzene (contaminant) | 100-41-4 | < 0.5 | 0.1 |
| Naphthalene (contaminant) | 91-20-3 | < 0.5 | 0.1 |
| Barium sulfate | 7727-43-7 | 10 - 30 | 1.0 |
| Pigment Blue | Mixture | 1 - 5 | 1.0 |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

U.S. State Regulations**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

| Component | CAS-No | Weight % |
|-----------------------------|------------|----------|
| Ethyl benzene (contaminant) | 100-41-4 | < 0.5 |
| Toluene | 108-88-3 | < 0.0001 |
| Benzene | 71-43-2 | < 0.0001 |
| Naphthalene (contaminant) | 91-20-3 | < 0.5 |
| Quartz, crystalline silica | 14808-60-7 | < 0.001 |

State Right-to-Know

| Component | Minnesota | Florida | New Jersey | Pennsylvania | Massachusetts | Rhode Island |
|---|------------|------------|------------|--------------|---------------|--------------|
| Petroleum distillates, hydrotreated light | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Barium sulfate | Not Listed | Not Listed | X | X | X | X |
| Pigment Blue | Not Listed | Not Listed | X | X | Not Listed | X |
| Naphtha (petroleum), heavy aromatic | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed | Not Listed |
| Titanium dioxide | Not Listed | Not Listed | X | X | X | X |
| Naphthalene (contaminant) | Not Listed | Not Listed | X | X | X | X |
| Ethyl benzene (contaminant) | Not Listed | Not Listed | X | X | X | X |

| | | | | | | |
|-----------------------------------|------------|------------|---|---|---|------------|
| Crystalline silica (cristobalite) | Not Listed | Not Listed | X | X | X | Not Listed |
|-----------------------------------|------------|------------|---|---|---|------------|

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

| Component | WHMIS Classifications of Components |
|-----------------------------------|---|
| Barium sulfate | Uncontrolled product according to WHMIS classification criteria |
| Titanium dioxide | D2A |
| Naphthalene (contaminant) | B4, D2A |
| Ethyl benzene (contaminant) | B2, D2A, D2B |
| Crystalline silica (cristobalite) | D2A |

| Component | NPRI - National Pollutant Release Inventory |
|---|---|
| Petroleum distillates, hydrotreated light | Part 5 Substance |
| Pigment Blue | Part 1, Group 1 Substance |
| Naphtha (petroleum), heavy aromatic | Part 5 Substance Part 4 Substance |
| Naphthalene (contaminant) | Part 1, Group 1 Substance Part 4 Substance |
| Ethyl benzene (contaminant) | Part 1, Group 1 Substance Part 4 Substance |

REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006

Does NOT contain a listed substance

| | | | | |
|--------------|---------------|---------------------|-------------------|------------|
| HMIS: | Health | Flammability | Reactivity | PPE |
| | 1* | 2 | 0 | X |

16. OTHER INFORMATION

Revision Date Apr-22-2009

Revision Summary New MSDS format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of MSDS