



## Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Mar-29-2010

Revision Date Mar-29-2010

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product code** 6001631288  
**Product name** Special 88 Opaque Gray  
**Product description** 8800 Series Color-Vue Membrane Screen Ink

#### Manufacturer or supplier's details

UNITED STATES  
Nazdar Company  
8501 Hedge Lane Terrace  
Shawnee, KS 66227  
Tel: 1-913-422-1888  
Tel: 1-800-677-4657  
Fax: 1-913-422-2294

UNITED KINGDOM  
Nazdar Limited  
7 Barton Road  
Heaton Mersey Industrial Estate  
Stockport, Cheshire SK4 3EG  
Tel: +44 161 442 2111

#### Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887

Website: [www.nazdar.com](http://www.nazdar.com)  
MSDS Information: 1-913-422-1888 ext 2305  
MSDS Contact: Regulatory Compliance  
email: [regcomp@nazdar.com](mailto:regcomp@nazdar.com)

### 2. HAZARDS IDENTIFICATION

*This product is a preparation. Health hazard information is based on its components.*

**Appearance** Viscous liquid  
**Flammable Properties** Combustible liquid and vapor.  
**Emergency Overview** Aspiration hazard. Harmful: may cause lung damage if swallowed. Irritant. May cause drowsiness and dizziness.

**Eyes** Moderately irritating to the eyes. Risk of serious damage to eyes. Avoid contact with eyes.  
**Skin** May cause skin irritation and/or dermatitis.  
**Inhalation** May cause irritation of respiratory tract. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
**Ingestion** Harmful if swallowed. Potential for aspiration if swallowed. Risk of serious damage to the lungs (by aspiration).

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Titanium dioxide	13463-67-7	30 - 60
Naphtha (petroleum), heavy aromatic	64742-94-5	10 - 30
Gamma Butyrolactone	96-48-0	10 - 30
2-Butoxyethanol	111-76-2	5 - 10
Naphthalene (contaminant)	91-20-3	1 - 5
Aluminum hydroxide	21645-51-2	1 - 5
Ethylene glycol monopropyl ether	2807-30-9	1 - 5
Carbon black	1333-86-4	< 1
1,2,4-Trimethylbenzene (contaminant)	95-63-6	< 0.5
Crystalline silica (cristobalite)	14464-46-1	< 0.5

- Component names which have the word (contaminant) are constituents contained in Aromatic Hydrocarbon ingredients and are an integral part of the ingredient and cannot be separated. The percentage listed for the contaminant is as contained in the Hydrocarbon ingredient. (Example: 100% Hydrocarbon, 10% Contaminant A, 3% Contaminant B)

### 4. FIRST AID MEASURES

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

<b>Skin Contact</b>	Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.
<b>Inhalation</b>	Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

## 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Combustible liquid and vapor.
<b>Suitable Extinguishing Media</b>	Foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
<b>Methods for Cleaning Up</b>	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.
<b>Environmental Precautions</b>	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition. Take notice of the directions of use on the label.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Ontario TWAEV	Mexico OEL (TWA)
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
2-Butoxyethanol	TWA: 20 ppm	TWA: 120 mg/m <sup>3</sup> TWA: 25 ppm Skin TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>	700 ppm	TWA: 20 ppm Skin	TWA: 120 mg/m <sup>3</sup> TWA: 26 ppm STEL: 360 mg/m <sup>3</sup> STEL: 75 ppm

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Ontario TWAEV	Mexico OEL (TWA)
Naphthalene (contaminant)	TWA: 10 ppm Skin STEL: 15 ppm	TWA: 50 mg/m <sup>3</sup> TWA: 10 ppm STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>	250 ppm	TWA: 10 ppm TWA: 52 mg/m <sup>3</sup> STEL: 15 ppm STEL: 78 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 75 mg/m <sup>3</sup> STEL: 15 ppm
Aluminum hydroxide	TWA: 1 mg/m <sup>3</sup>				
Ethylene glycol monopropyl ether				TWA: 25 ppm TWA: 110 mg/m <sup>3</sup> Skin	
Carbon black	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	1750 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>
1,2,4-Trimethylbenzene (contaminant)	TWA: 25 ppm			TWA: 25 ppm TWA: 123 mg/m <sup>3</sup>	TWA: 125 mg/m <sup>3</sup> TWA: 25 ppm STEL: 35 ppm STEL: 170 mg/m <sup>3</sup>
Crystalline silica (cristobalite)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	25 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>

**Engineering Measures**

Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

**Personal Protective Equipment****Respiratory Protection**

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

**Eye Protection**

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

**Skin Protection**

Wear protective gloves/clothing. Solvent-resistant apron and boots.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous liquid	<b>Physical State</b>	Liquid
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available	<b>Autoignition Temperature</b>	No information available
<b>Boiling point/Boiling Range</b>	>149°C / >300°F	<b>Melting Point/Range</b>	No information available
<b>Freezing Point/Range</b>	No information available	<b>Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available	<b>Partition Coefficient (n-octanol/water)</b>	No information available
<b>Vapour Pressure</b>	No information available	<b>Vapour Density</b>	Heavier than air
<b>Flammability (solid, gas)</b>	No information available	<b>Flash Point</b>	49°C / 120°F
<b>Flammability Limits in Air</b>		<b>Method</b>	Pensky Martens Closed Cup (PMCC)
<b>Upper</b>	No information available	<b>Photochemically Reactive</b>	Yes
<b>Lower</b>	No information available	<b>Specific Gravity</b>	1.415
<b>Weight Per Gallon (lbs/gal)</b>	11.796	<b>VOC by volume %</b>	44.906
<b>VOC by weight %</b>	44.277	<b>VOC grams/liter (less water)</b>	626.47
<b>VOC lbs/gal (less water)</b>	5.228		

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Products</b>	Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.

**Hazardous Decomposition Products** Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

**Possibility of Hazardous Reactions** None under normal processing.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium dioxide	10000 mg/kg ( Rat )		
Naphtha (petroleum), heavy aromatic	5000 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	590 mg/m <sup>3</sup> ( Rat ) 4 h
Gamma Butyrolactone	1540 mg/kg ( Rat )		2.68 mg/L ( Rat ) 4 h
2-Butoxyethanol	470 mg/kg ( Rat )	2270 mg/kg ( Rat ) 220 mg/kg ( Rabbit )	2.21 mg/L ( Rat ) 4 h 450 ppm ( Rat ) 4 h
Naphthalene (contaminant)	490 mg/kg ( Rat )	2500 mg/kg ( Rat ) 20 g/kg ( Rabbit )	340 mg/m <sup>3</sup> ( Rat ) 1 h
Aluminum hydroxide	5000 mg/kg ( Rat )		
Ethylene glycol monopropyl ether	3089 mg/kg ( Rat )	960 µL/kg ( Rabbit )	
Carbon black	15400 mg/kg ( Rat )	3 g/kg ( Rabbit )	
1,2,4-Trimethylbenzene (contaminant)	3400 mg/kg ( Rat ) 8970 mg/kg ( Rat )	3160 mg/kg ( Rabbit )	18 g/m <sup>3</sup> ( Rat ) 4 h

### Chronic Toxicity

Component	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
2-Butoxyethanol	A3			
Naphthalene (contaminant)		Group 2B	Reasonably Anticipated	X
Carbon black		Group 2B		X
Crystalline silica (cristobalite)	A2	Group 1		X

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B). In their evaluation of carbon black, IARC indicates exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

OSHA: (Occupational Safety & Health Administration)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Reasonably Anticipated to be a Human Carcinogen

X - Present

### Sensitisation

No information available

### Mutagenic Effects

No information available

### Reproductive Effects

No information available

### Developmental Effects

No information available

### Teratogenicity

No information available

### Chronic Effects

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

### Target Organ Effects

Blood, Central nervous system, Eyes, Hematopoietic System, Lungs, Liver, Kidney, Respiratory system, Skin.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

Component	Freshwater Algae	Freshwater Fish	Water Flea
Naphtha (petroleum), heavy aromatic	72 Hr EC50 Skeletonema costatum: 2.5 mg/L	96 Hr LC50 Pimephales promelas: 19 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.34 mg/L; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static]	48 Hr EC50 Daphnia magna: 0.95 mg/L
Gamma Butyrolactone	72 Hr EC50 Scenedesmus subspicatus: 360 mg/L; 96 Hr EC50 Scenedesmus subspicatus: 79 mg/L	96 Hr LC50 Leuciscus idus: 220-460 mg/L [static]	48 Hr EC50 Daphnia magna Straus: >500 mg/L
2-Butoxyethanol		96 Hr LC50 Lepomis macrochirus: 2950 mg/L	24 Hr EC50 water flea: 1720 mg/L; 24 Hr LC50 Daphnia magna: 1698-1940 mg/L
Naphthalene (contaminant)	96 Hr EC50 Skeletonema costatum: 0.4 mg/L	96 Hr LC50 Pimephales promelas: 1.99 mg/L [static]	48 Hr EC50 water flea: 2.16 mg/L
Carbon black			24 Hr EC50 Daphnia magna: >5600 mg/L
1,2,4-Trimethylbenzene (contaminant)		96 Hr LC50 Pimephales promelas: 7.72 mg/L [flow-through]	48 Hr EC50 Daphnia magna: 6.14 mg/L

**Persistence and Degradability** No information available  
**Bioaccumulation** No information available  
**Mobility in Environmental Media** No information available

Component	log Pow
Naphtha (petroleum), heavy aromatic	2.9 - 6.1
Gamma Butyrolactone	-0.566
2-Butoxyethanol	0.81

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** Dispose of contents/container in accordance with local regulation.

**Contaminated Packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

#### DOT

UN1210, Printing Ink, 3, III  
 In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

#### ICAO/IATA

UN1210, Printing Ink, 3, III

#### IMDG/IMO

UN1210, Printing Ink, 3, III

### 15. REGULATORY INFORMATION

#### International Inventories

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
2-Butoxyethanol	111-76-2	5 - 10	1.0
Ethylene glycol monopropyl ether	2807-30-9	1 - 5	1.0
Naphthalene (contaminant)	91-20-3	1 - 5	0.1

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	1 - 5
Naphthalene (contaminant)	91-20-3	1 - 5

**U.S. State Regulations****California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Component	CAS-No	Weight %
Naphthalene (contaminant)	91-20-3	1 - 5
Carbon black	1333-86-4	< 1

**State Right-to-Know**

Component	Minnesota	Florida	New Jersey	Pennsylvania	Massachusetts	Rhode Island
Titanium dioxide	Not Listed	Not Listed	X	X	X	X
Naphtha (petroleum), heavy aromatic	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Gamma Butyrolactone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
2-Butoxyethanol	Not Listed	Not Listed	X	X	X	X
Naphthalene (contaminant)	Not Listed	Not Listed	X	X	X	X
Aluminum hydroxide	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	X	X	Not Listed	Not Listed
Carbon black	Not Listed	Not Listed	X	X	X	X
1,2,4-Trimethylbenzene (contaminant)	Not Listed	Not Listed	X	X	X	X
Crystalline silica (cristobalite)	Not Listed	Not Listed	X	X	X	Not Listed

**Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

Component	WHMIS Classifications of Components
Titanium dioxide	D2A
2-Butoxyethanol	B3, D1A, D2B
Naphthalene (contaminant)	B4, D2A
Aluminum hydroxide	Uncontrolled product according to WHMIS classification criteria
Ethylene glycol monopropyl ether	B3, D1B, D2B
Carbon black	D2A
1,2,4-Trimethylbenzene (contaminant)	B3
Crystalline silica (cristobalite)	D2A

Component	NPRI - National Pollutant Release Inventory
Naphtha (petroleum), heavy aromatic	Part 5 Substance Part 4 Substance
Gamma Butyrolactone	Part 4 Substance
2-Butoxyethanol	Part 4 Substance Part 1, Group 1 Substance; Part 5 Substance
Naphthalene (contaminant)	Part 1, Group 1 Substance Part 4 Substance
Ethylene glycol monopropyl ether	Part 4 Substance
1,2,4-Trimethylbenzene (contaminant)	Part 1, Group 1 Substance; Part 5 Substance Part 5 Substance (except 1,2,4-Trimethyl benzene) Part 4 Substance

**REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006**

Does NOT contain a listed substance

<b>HMIS:</b>	<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>PPE</b>
	3*	2	0	X

**16. OTHER INFORMATION**

Revision Date Mar-29-2010

Revision Summary New MSDS format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of MSDS**