

MATERIAL SAFETY DATA SHEET

DATE OF LAST CHANGE: 05/04/06

DATE PRINTED.....: 05/04/06

MANUFACTURER'S NAME:

NAZDAR CHICAGO
1087 N. NORTH BRANCH ST.
CHICAGO
IL 60622 4292 USA

EMERGENCY TELEPHONE #: (800)424-9300
(U.S. and Canada)
EMERGENCY TELEPHONE #: (703)527-3887
(Outside U.S. and Canada, collect calls are accepted)
INFORMATION TELEPHONE #: (800)736-7636

SECTION 1 -- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT CODE.: 7248

TRADE NAME...: FLATTING PASTE

PRODUCT CLASS: SCREEN PRINTING RELATED MATERIAL

INK SERIES...:

- H M I S C O D E S -
HEALTH - 2*
FLAMMABILITY - 3
REACTIVITY - 0
PPE - X

SECTION 2 -- COMPOSITION, INFORMATION ON INGREDIENTS

CHEMICAL NAME; COMMON NAME; CAS NUMBER	PERCENT BY WEIGHT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE IN mmHg	NOTES
		-----ACGIH----- TLV	-----OSHA----- PEL		
* 2-PROPOXYETHANOL; ETHYLENE GLYCOL MONOPROPYL ETHER; CAS #: 2807-30-9	40-45	NOT ESTABLISHED	NOT ESTABLISHED	1.3 @ 20C	(1)
SILICA, AMORPHOUS; CAS #: 112926-00-8	25-30	10 mg/m3	6 mg/m3	N/A	(2)
RESIN MIXTURES; CAS #: NOT AVAILABLE	5-10	NOT ESTABLISHED	NOT ESTABLISHED	<1 @ 20C	
PETROLEUM DISTILLATE; AROMATIC HYDROCARBON; CAS #: 64742-95-6	5-10	NOT ESTABLISHED	NOT ESTABLISHED	3.0 @ 20C	
* 2-BUTOXYETHANOL; ETHYLENE GLYCOL MONOBUTYL ETHER; CAS #: 111-76-2	< 4	20 ppm	25 ppm Skin	0.6 @ 20C	
ISOPROPANOL; ISOPROPYL ALCOHOL; CAS #: 67-63-0	< 3	200 ppm STEL: 400 ppm	400 ppm STEL: 500 ppm	32 @ 20C	
* 1,2,4-TRIMETHYLBENZENE; PSEUDOCUMENE; CAS #: 95-63-6	< 3	25 ppm	25 ppm	<1 @ 20C	(3)
* TOLUENE; METHYLBENZENE; CAS #: 108-88-3	< 2	50 ppm	100 ppm STEL: 150 ppm	24 @ 20C	(4)

* SUBJECT TO REPORTING REQUIREMENT OF SECTION 313 OF TITLE III OF SARA (40 CFR PART 372).

- Supplier recommended exposure limit of 20 ppm TWA, no skin contact and 60 ppm STEL, no skin contact. This chemical is included on the list of Hazardous Air Pollutants (HAPs) from Title III of the Clean Air Act Amendments of 1990 (Glycol Ethers Category).
- When referencing TSCA, use Silica CAS# 7631-86-9. CAS# 112926-00-8 was created to help further categorize the family of Silica. It has not yet been listed on TSCA.
- The above ACGIH exposure limit is for Trimethylbenzene isomers CAS# 25551-13-7.
- This chemical is included on the list of Hazardous Air Pollutants (HAPs) from Title III of the Clean Air Act Amendments of 1990.

The recommended permissible exposure limits (PEL) indicated above reflect the levels adopted by OSHA in 1989. Although, some of the 1989 levels have since been vacated, the Nazdar Company recommends that the lower exposure levels be observed as reasonable worker protection.

SECTION 3 -- HAZARDS IDENTIFICATION

GENERAL HEALTH EFFECTS

THE FOLLOWING INFORMATION HAS BEEN DEVELOPED BASED UPON USING THE PRODUCT AS INTENDED BY THE MANUFACTURER. The potential health effects of this product are based on the hazards of its components. The use of this product in combination with other products may produce synergistic (additive) health effects. Cautionary labeling and material safety data sheets of all materials used with this product should be reviewed before use.

EYES

Eye contact with liquid, vapors or mists may cause severe irritation, including burning, tearing, redness or swelling and reversible eye damage.

SKIN

Skin contact may cause irritation. Symptoms may include dryness, chapping and redness. This material may be absorbed through the skin. Toxic if absorbed through the skin.

INHALATION

Inhalation may cause respiratory tract irritation.

INGESTION

Ingestion may cause gastrointestinal tract irritation. Ingestion of excessive quantities may cause irritation of the digestive tract, weakness and breathing difficulties.

CHRONIC EFFECTS/TARGET ORGANS

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Toluene has been associated with liver, kidney and brain damage in humans after intentional misuse by deliberately inhaling. Studies have shown that toxic effects from toluene overexposure during pregnancy may be harmful to the fetus. Overexposure to this material has been suggested as a cause of cardiac sensitization in humans.

ANIMAL STUDIES

2-Propoxyethanol has caused blood disorders resulting in kidney, liver, lung and spleen damage in lab animals. 2-Butoxyethanol has caused reproductive and blood disorders resulting in kidney, liver and lung damage in lab animals. Isopropyl alcohol causes harm to the fetus in lab animals. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Repeated exposure to toluene has been associated with high frequency hearing loss in lab animals. For animal studies, reference TSCA Section 4 Test Rule Results or contact the manufacturer for further details.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pregnant women and persons with pre-existing health disorders should consult their physician before using this product. Repeated and prolonged overexposure and/or individual sensitivity may increase the potential for and degree of adverse health effects. See Section 3 "Hazards Identification" for effects of certain hazardous ingredients.

ROUTES OF EXPOSURE

Primary exposure routes: Inhalation-Dermal (Contact/Absorption)-Ingestion

SECTION 4 -- FIRST AID MEASURES

EYES

After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If irritation persists have eyes examined and tested by medical personnel.

SKIN

In case of contact, immediately wash skin with a mild soap and plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Cool water is initially suggested to prevent the pores of the skin from opening. This will minimize both the area and time of skin contact. Lukewarm water may then be used to ensure all contaminants are removed. Skin should be monitored for reddening or chemical burns. Mild soap is suggested to help prevent abrading the skin or rubbing the chemicals into pores during cleansing. Get medical attention if irritation persists or significant contact has occurred. Thoroughly wash (or discard) clothing and shoes before reuse.

INHALATION

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention if breathing difficulty is experienced.

INGESTION

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

OTHER COMMENTS

No Data Available

SECTION 5 -- FIRE FIGHTING MEASURES

FLASH POINT

90 Degrees - 99 Degrees Fahrenheit (TCC)

OSHA FLAMMABILITY CLASSIFICATION (NFPA)
Class IC Flammable Liquid

LEL - LOWER EXPLOSIVE LIMIT / UEL - UPPER EXPLOSIVE LIMIT
1.1% volume in air / No Data Available

EXTINGUISHING MEDIA
Foam-CO2-Dry Chemical-Water Spray

FIRE AND EXPLOSION HAZARDS
Isolate from heat, electrical equipment, sparks, and open flame. Keep containers tightly closed. Vapors may be heavier than air and can travel to a source of ignition then flash back. Closed containers may explode when exposed to extreme heat.

FIRE FIGHTING EQUIPMENT
Full protective equipment including self-contained breathing apparatus (SCBA) is recommended to protect firefighters.

SPECIAL FIRE FIGHTING PROCEDURES
Water may be ineffective but may be used to cool containers. Fumes released on burning may be toxic and dangerous.

SECTION 6 -- ACCIDENTAL RELEASE MEASURES

RELEASE MANAGEMENT MEASURES
Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid contact or breathing vapors. Ventilate area. Contain release and remove with inert absorbent. Use non-sparking tools to place material in appropriate container for disposal. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. The National Response Center (800-424-8802) and local authorities should be contacted for any reportable spill/release.

SECTION 7 -- HANDLING AND STORAGE

HANDLING AND STORAGE METHODS
Use in a well ventilated area. Follow all MSDS/label precautions even after container is emptied; container may retain product residues. Store in closed containers in cool, dry, well ventilated area away from sources of ignition. Keep containers closed when not in use. Smoke in designated areas only. Avoid prolonged or repeated overexposure to this product. Keep out of reach of children. Follow label directions carefully. Do not take internally. Harmful or fatal if swallowed.

SECTION 8 -- EXPOSURE CONTROLS, PERSONAL PROTECTION

RESPIRATORY PROTECTION
If concentrations of hazardous ingredients exceed exposure limits listed in Section 2 an appropriate NIOSH (National Institute for Occupational Safety and Health) approved respirator with an organic vapor cartridge should be used. If material is handled under mist, spray or dust forming conditions, a P100 (99.97% efficiency) filter should be used in addition to the organic vapor cartridge. Protection provided by air-purifying respirators is limited. If no exposure limits are listed in Section 2, follow general safety guidelines in 29 CFR 1910.134 Respiratory Protection or other applicable respiratory standard.

SKIN PROTECTION
Use neoprene, nitrile or other gloves resistant to chemicals listed in Section 2. Contact a reputable safety supply company for appropriate gloves. Solvent resistant aprons are recommended. Prevent prolonged skin contact with contaminated clothing.

EYE PROTECTION
Use ANSI (American National Standards Institute) approved safety glasses, faceshield or splash proof goggles to prevent eye contact. Contact a reputable safety supply company for appropriate eye protection. The availability of an eye wash is highly recommended.

EXPOSURE GUIDELINES
See Section 2 "Composition, Information on Ingredients" for occupational exposure limits. Excessive concentrations of nuisance dusts or particulates not otherwise classified (PNOC) or regulated (PNOR) may reduce visibility and cause unpleasant deposits in the eyes, ears, and nasal passages. The TLV and PEL has been established for all non-toxic "nuisance dusts" that are not otherwise classified and refers to both organic and inorganic dusts. Exposure or generation of these dusts is not anticipated during normal printing operations. The use of dry pigments and powders, grinding or sanding of printed products may generate quantities of these particulates. Refer to Section 2 Composition, Information on Ingredients for exposure limits.

HYGIENIC PRACTICES
Wash with soap and water before eating, smoking or using toilet facilities. Separately wash or discard clothing and footwear before reuse. NEVER try to remove product from the skin by using solvent or thinner. Such action is likely to increase the possibility of undesirable effects. Remove contaminated clothing to prevent prolonged skin contact.

ENGINEERING CONTROLS
Use applicable engineering controls, work practices and personal protective equipment to ensure all concentrations are kept below the exposure limits listed in Section 2. Adequate controls should be implemented to ensure employee safety from fine mists which may be produced under some printing conditions.

OTHER PROTECTION
No Data Available

SECTION 9 -- PHYSICAL AND CHEMICAL PROPERTIES

**

APPEARANCE:
Viscous liquid

ODOR:
Characteristic

PHYSICAL STATE:
Liquid

pH
Not applicable

VAPOR PRESSURE
See Section 2 for individual ingredients.

VAPOR DENSITY
Heavier than air

BOILING POINT
Greater than 300 degrees Fahrenheit

FREEZING POINT
Not available

SOLUBILITY IN WATER
Not tested

EVAPORATION RATE
Slower than ether

VISCOSITY
Greater than water

PERCENT VOLATILE BY VOLUME: 70.65 %

WEIGHT PER GALLON: 9.31 lbs/gal

VOC: 648.12 g/L
5.40 lb/gal

PHOTOCHEMICALLY REACTIVE
No

Percent volatile = Percent VOC

SECTION 10 -- STABILITY AND REACTIVITY

CHEMICAL STABILITY
Stable

CONDITIONS TO AVOID
Avoid excessive heat, ignition sources, sparks and open flame.

INCOMPATIBILITY WITH OTHER MATERIALS
Strong acids/bases, oxidizing/reducing agents and reactive chemicals.

HAZARDOUS DECOMPOSITION PRODUCTS
May produce hazardous fumes when heated to decomposition e.g. carbon monoxide, carbon dioxide and other noxious gases.

HAZARDOUS POLYMERIZATION
Not anticipated during normal printing and storage conditions.

SECTION 11 -- TOXICOLOGICAL INFORMATION

EXPERIMENTAL TOXICITY DATA

Refer to Section 3 Hazards Identification for additional toxicological data. Experimental toxicity data on 2-propoxyethanol has given the following results: Oral LD50 Rat; 4890 mg/kg; Skin LD50 Rabbit; 940 mg/kg. Experimental toxicity data on petroleum distillate CAS# 64742-95-6 has given the following results: Oral LD50 Rat; 4700 mg/kg; Dermal LD50 Rabbit 4 ml/kg; Inhalation LC50 Rat; 3670 ppm 4 hours. Experimental toxicity data on 2-butoxyethanol has given the following results: Oral LD50 Rat; 1746 mg/kg; Intraperitoneal LD50 Rat; 550 mg/kg. Experimental toxicity data on isopropanol has given the following results: Oral LD50 Rat; 5840 mg/kg; Dermal LD50 Rabbit; 13 g/kg; Inhalation LC50 Rat; 450 ppm 4 hours; Human lethal dose 250 ml. Experimental toxicity data on toluene has given the following results: Oral LD 50 Rat; 5000 mg/kg; Inhalation LC50 Rat; 8800 ppm; Dermal LD50 Rabbit; 14 g/kg.

SECTION 12 -- ECOLOGICAL INFORMATION

ECOTOXICITY

Because this product may be a mixture of chemicals, some of which may be ecologically toxic, it is strongly suggested that it not be disposed of into the environment, i.e. soil, water courses, lakes, landfills, sewers, etc.

ENVIRONMENTAL FATE

No Data Available

SECTION 13 -- DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

This product is considered hazardous for disposal purposes by the U.S. Environmental Protection Agency Resource Conservation and Recovery Act (RCRA). Contact Nazdar's Regulatory Compliance Department or refer to the regulations located in 40 CFR Part 261 for additional waste disposal information, including appropriate hazardous waste codes. It is the responsibility of the user to determine if local, county, state, or provincial regulations may also apply to the disposal of this product and/or container. Empty containers may retain hazardous properties and should be disposed of in an environmentally safe manner in accordance with applicable regulations.

SECTION 14 -- TRANSPORT INFORMATION

TRANSPORT INFORMATION

DOT Proper Shipping Description: Printing Ink, 3, UN1210, PG III. Questions concerning transportation requirements should be directed to Nazdar's Regulatory Compliance Department 913-422-1735.

SECTION 15 -- REGULATORY INFORMATION

SARA TITLE III 313 INFORMATION

See Section 2 "Composition, Information on Ingredients" for applicable chemicals.

TOXIC SUBSTANCES CONTROL ACT STATUS

All ingredients in Section 2 are listed on the U.S. Environmental Protection Agency's Toxic Substances Control Act (TSCA) Inventory and the Canadian Domestic Substance List.

OTHER REGULATORY INFORMATION

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) - MSDS is compliant with Occupational Safety and Health Administration Hazard Communication Standard - 29 CFR 1910.1200. AMERICAN NATIONAL STANDARDS INSTITUTE - This MSDS follows the ANSI Z400.1-1998 format. WORKPLACE HAZARDOUS MATERIAL INFORMATION SYSTEM (WHMIS) - This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS CLASSIFICATION (CANADA):

B2 _ Flammable Liquids; D1A _ Material causing immediate and serious toxic effects, very toxic material; D2B _ Materials causing other toxic effects, toxic material;

SECTION 16 -- OTHER INFORMATION

DISCLOSURE

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind express or implied is made with respect to the information contained herein. The data in this MSDS relates only to the specific material designated herein and does not apply to use in combination with any other material or process.

DEFINITIONS

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CEILING: (TLV-Ceiling and PEL Ceiling Limit) The ceiling exposure limit or concentration not to be exceeded for even brief

times.

DOT: Department of Transportation

HMIS: The Hazardous Materials Identification System (HMIS) developed by the National Paint and Coatings Association (NPCA) to provide information on the acute health hazards, reactivity and flammability of products encountered in the workplace at room temperatures.

HMIS codes assigned for this product are only suggested ratings based on anticipated normal screen printing applications. The employer has the ultimate responsibility for assigning these ratings and should fully evaluate the MSDS, work practices and environmental conditions prior to assigning the appropriate ratings.

HMIS rating involves data interpretations that may vary from company to company.

HMIS Personal Protection Index of "X-Ask your supervisor" is given on this MSDS due to varying work conditions which may dictate different levels of protection. Please review this MSDS before determining appropriate protective equipment and beginning work.

IARC: International Agency for Research on Cancer

NFPA: National Fire Protection Association

NTP: National Toxicology Program

STEL: Short-Term Exposure Limit: ACGIH terminology for the short-term exposure limit or maximum concentration for a continuous exposure period of 15 minutes.

TLV: Threshold Limit Value. A term ACGIH uses to express the airborne concentration of a material to which most workers can be exposed during a normal daily and weekly work schedule without adverse effects.

TWA: Time-Weighted Average

VOC: Volatile Organic Compound