



Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Apr-24-2009

Revision Date Apr-24-2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product code 7252
Product name Super Opaque Black
Product description 7200 Series Lacquer Screen Ink

Manufacturer or supplier's details

UNITED STATES
Nazdar Company
8501 Hedge Lane Terrace
Shawnee, KS 66227
Tel: 1-913-422-1888
Tel: 1-800-677-4657
Fax: 1-913-422-2294

UNITED KINGDOM
Nazdar Limited
7 Barton Road
Heaton Mersey Industrial Estate
Stockport, Chesire SK4 3EG
Tel: +44 161 442 2111

Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887

Website: www.nazdar.com
MSDS Information: 1-913-422-1888 ext 2305
MSDS Contact: Regulatory Compliance
email: regcomp@nazdar.com

2. HAZARDS IDENTIFICATION

This product is a preparation. Health hazard information is based on its components.

Appearance Viscous liquid
Flammable Properties FLAMMABLE LIQUID AND VAPOR.
Emergency Overview Harmful. Irritant. May cause drowsiness and dizziness.

Eyes Severe eye irritant. The liquid splashed in the eyes may cause irritation and reversible damage.

Skin Harmful in contact with skin. May cause skin irritation and/or dermatitis. Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering. May be harmful if absorbed through skin.

Inhalation Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Ethylene glycol monopropyl ether	2807-30-9	10 - 30
2-Butoxyethanol	111-76-2	10 - 30
Isopropyl alcohol	67-63-0	5 - 10
Carbon black	1333-86-4	1 - 5
Toluene	108-88-3	1 - 5

4. FIRST AID MEASURES

Skin Contact Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Inhalation Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flammable Properties FLAMMABLE LIQUID AND VAPOR.

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages.

Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources of ignition. Risk of ignition. Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Methods for Cleaning Up Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.

Environmental Precautions Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition. Take notice of the directions of use on the label.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component	Weight %	ACGIH TLV	OSHA PEL	Ontario TWAEV
Ethylene glycol monopropyl ether	10 - 30			TWA: 25 ppm TWA: 110 mg/m ³ Skin
2-Butoxyethanol	10 - 30	TWA: 20 ppm	TWA: 120 mg/m ³ TWA: 25 ppm Skin TWA: 50 ppm TWA: 240 mg/m ³	TWA: 20 ppm Skin
Isopropyl alcohol	5 - 10	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 1225 mg/m ³ STEL: 500 ppm	TWA: 200 ppm STEL: 400 ppm
Carbon black	1 - 5	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³

Component	Weight %	ACGIH TLV	OSHA PEL	Ontario TWAEV
Toluene	1 - 5	TWA: 20 ppm	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 560 mg/m ³ STEL: 150 ppm TWA: 200 ppm Ceiling: 300 ppm	TWA: 20 ppm

Component	Weight %	NIOSH IDLH	Mexico OEL (TWA)
2-Butoxyethanol	10 - 30	700 ppm	TWA: 120 mg/m ³ TWA: 26 ppm STEL: 360 mg/m ³ STEL: 75 ppm
Isopropyl alcohol	5 - 10	2000 ppm 10% LEL	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 1225 mg/m ³ STEL: 500 ppm
Carbon black	1 - 5	1750 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
Toluene	1 - 5	500 ppm	TWA: 50 ppm TWA: 188 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Engineering Measures

Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment Respiratory Protection

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.

Eye Protection

Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.

Skin Protection

Wear protective gloves/clothing. Solvent-resistant apron and boots.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Viscous liquid	Physical State	Liquid
Odor	Characteristic	Odor Threshold	No information available
pH	No information available	Autoignition Temperature	No information available
Boiling point/Boiling Range	>149°C / >300°F	Melting Point/Range	No information available
Freezing Point/Range	No information available	Solubility	No information available
Evaporation Rate	No information available	Partition Coefficient (n-octanol/water)	No information available
Vapour Pressure	No information available	Vapour Density	Heavier than air
Flammability (solid, gas)	No information available	Flash Point	32°C / 90°F
Flammability Limits in Air		Method	Tag closed cup
Upper	No information available	Photochemically Reactive	No
Lower	No information available		
Weight Per Gallon (lbs/gal)	8.667	Specific Gravity	1.04
VOC by weight	58.399	VOC by volume	60.247
VOC lbs/gal	5.067	VOC grams/liter	607.104

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions.

Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO ₂). Carbon monoxide.
Possibility of Hazardous Reactions	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol monopropyl ether	3089 mg/kg (Rat)	960 µL/kg (Rabbit)	
2-Butoxyethanol	470 mg/kg (Rat)	2270 mg/kg (Rat) 220 mg/kg (Rabbit)	2.21 mg/L (Rat) 4 h 450 ppm (Rat) 4 h
Isopropyl alcohol	4396 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Carbon black	15400 mg/kg (Rat)	3 g/kg (Rabbit)	
Toluene	636 mg/kg (Rat)	8390 mg/kg (Rabbit) 12124 mg/kg (Rat)	12.5 mg/L (Rat) 4 h 26700 ppm (Rat) 1 h

Chronic Toxicity

Component	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3			
Carbon black		Group 2B		X

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B). In their evaluation of carbon black, IARC indicates exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

Legend:

ACGIH: (American Conference of Governmental Industrial Hygienists)
 IARC: (International Agency for Research on Cancer)
 OSHA: (Occupational Safety & Health Administration)

A3 - Animal Carcinogen
 Group 2B - Possibly Carcinogenic to Humans
 X - Present

Sensitisation	No information available
Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Chronic Effects	Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.
Target Organ Effects	Blood, Central nervous system, Eyes, Hematopoietic System, Kidney, Liver, Lymphatic System, Respiratory system, Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

Component	Freshwater Algae	Freshwater Fish	Water Flea
2-Butoxyethanol		96 Hr LC50 Lepomis macrochirus: 2950 mg/L	24 Hr EC50 water flea: 1720 mg/L; 24 Hr LC50 Daphnia magna: 1698-1940 mg/L

Component	Freshwater Algae	Freshwater Fish	Water Flea
Isopropyl alcohol	96 Hr EC50 Scenedesmus subspicatus: >1000 mg/L; 72 Hr EC50 Scenedesmus subspicatus: >1000 mg/L	96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]	48 Hr EC50 Daphnia magna: 13299 mg/L
Carbon black			24 Hr EC50 Daphnia magna: >5600 mg/L
Toluene	96 Hr EC50 Selenastrum capricornutum: >433 mg/L	96 Hr LC50 Pimephales promelas: 25 mg/L [flow-through] (1 day old); 96 Hr LC50 Oncorhynchus mykiss: 24.0 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 24.0 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 13 mg/L [static]	48 Hr EC50 water flea: 11.3 mg/L; 48 Hr EC50 water flea: 310 mg/L; 48 Hr EC50 Daphnia magna: 11.3 mg/L

Persistence and Degradability No information available
Bioaccumulation No information available
Mobility in Environmental Media No information available

Component	log Pow
2-Butoxyethanol	0.81
Isopropyl alcohol	0.05
Toluene	2.65

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of contents/container in accordance with local regulation.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

UN1210, Printing Ink, 3, III

ICAO/IATA

UN1210, Printing Ink, 3, III

IMDG/IMO

UN1210, Printing Ink, 3, III

15. REGULATORY INFORMATION

International Inventories

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Toluene	108-88-3	1 - 5	1.0
Ethylene glycol monopropyl ether	2807-30-9	10 - 30	1.0
2-Butoxyethanol	111-76-2	10 - 30	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Component	CAS-No	Weight %
Toluene	108-88-3	1 - 5
Ethylene glycol monopropyl ether	2807-30-9	10 - 30

U.S. State Regulations**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Component	CAS-No	Weight %
Toluene	108-88-3	1 - 5
Ethyl benzene (contaminant)	100-41-4	< 0.1
Naphthalene (contaminant)	91-20-3	< 0.0001
Benzene	71-43-2	< 0.0001
Carbon black	1333-86-4	1 - 5
Quartz, crystalline silica	14808-60-7	< 0.001

State Right-to-Know

Component	Minnesota	Florida	New Jersey	Pennsylvania	Massachusetts	Rhode Island
Ethylene glycol monopropyl ether	Not Listed	Not Listed	X	X	Not Listed	Not Listed
2-Butoxyethanol	Not Listed	Not Listed	X	X	X	X
Isopropyl alcohol	Not Listed	Not Listed	X	X	X	X
Carbon black	Not Listed	Not Listed	X	X	X	X
Toluene	Not Listed	Not Listed	X	X	X	X

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

Component	WHMIS Classifications of Components
Ethylene glycol monopropyl ether	B3, D1B, D2B
2-Butoxyethanol	B3, D1A, D2B
Isopropyl alcohol	B2, D2B (including 70%)
Carbon black	D2A
Toluene	B2, D2A, D2B

Component	NPRI - National Pollutant Release Inventory
Ethylene glycol monopropyl ether	Part 4 Substance
2-Butoxyethanol	Part 4 Substance Part 1, Group 1 Substance; Part 5 Substance
Isopropyl alcohol	Part 1, Group 1 Substance; Part 5 Substance Part 4 Substance
Toluene	Part 4 Substance Part 1, Group 1 Substance; Part 5 Substance

REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006

Does NOT contain a listed substance

HMIS:Health
2*Flammability
3Reactivity
0PPE
X**16. OTHER INFORMATION**

Revision Date

Apr-24-2009

Revision Summary

New MSDS format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of MSDS