

DATE OF LAST CHANGE: 7/28/2006

DATE PRINTED: 7/28/2006

Manufactured Exclusively for:  
Avery Dennison by:

NAZDAR SHAWNEE  
8501 HEDGE LANE TERRACE  
SHAWNEE  
KS 66227 USA

EMERGENCY TELEPHONE #: (800) 424-9300  
(U.S. and Canada)  
EMERGENCY TELEPHONE #: (703) 527-3887  
(Outside U.S. and Canada, collect calls are accepted)  
INFORMATION TELEPHONE #: (800) 677-4657

SECTION 1 -- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CODE: 7TS  
TRADE NAME: Avery Dennison 7TS Inks  
PRODUCT CLASS: 7 Year Durable Screen Ink  
INK SERIES:

- H M I S C O D E S -  
HEALTH: 2 \*  
FLAMMABILITY: 2  
REACTIVITY: 0  
PPE: X  
PHOTOCHEMICALLY REACTIVE: No

Item Description	WT lb/gal	VOC g/L	VOC lb/gal	% VOC volume	Item Description	WT lb/gal	VOC g/L	VOC lb/gal	% VOC volume
7TS12 Transparent Yellow	8.9	680	5.7	70	7TS13 Transparent Green	9.0	683	5.7	70
7TS16 Transparent Brown	8.9	687	5.7	70	7TS20 Transparent Orange	8.9	684	5.7	70
7TS22 Transparent Blue	9.0	665	5.5	68	7TS27 Overprint Clear	8.8	681	5.7	70
7TS52 Black	8.9	676	5.6	69	7TS60 Transparent Stop Sign Red	8.9	686	5.7	70
7TS75 White	11.3	609	5.1	62					

SECTION 2 -- COMPOSITION, INFORMATION ON INGREDIENTS

CHEMICAL NAME; COMMON NAME; CAS NUMBER	PERCENT BY WEIGHT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE IN mmHg	NOTES
		-----ACGIH----- TLV	-----OSHA----- PEL		
Resin Mixtures; # CAS: Not Available	20 - 35	Not Established	Not Established	< 1 @ 20C	
Cyclohexanone; Pimelic Ketone; # CAS: 108-94-1	15 - 30	20 ppm Skin	25 ppm Skin	2 @ 20C	
ACGIH STEL 50 ppm					
* 1-Methyl-2-Pyrrolidone; M-Pyrol; # CAS: 872-50-4	5 - 15	Not Established	Not Established	0.29 @ 20C	(1)
Dipropylene Glycol Dimethyl Ether; DMM Glycol Diether; # CAS: 111109-77-4	5 - 10	Not Established	Not Established	0.82 @ 25C	
Gamma Butyrolactone; Dihydro-2(3H)-Furanone; # CAS: 96-48-0	< 10	Not Established	Not Established	1.5 @ 20C	
* Diethylene Glycol Ethyl Ether Acetate; 2-(2-Ethoxyethoxy) Ethyl Acetate; # CAS: 112-15-2	< 10	Not Established	Not Established	0.5 @ 20C	(2)

Petroleum Distillate; Aromatic Hydrocarbon; # CAS: 64742-94-5	< 5	Not Established	Not Established	< 1 @ 20C	(3)
Aliphatic Dibasic Acid Esters; Dibasic Ester Mixture; # CAS: Not Established	< 5	Not Established	Not Established	0.2 @ 20C	(4)
* Ethyl Benzene; # CAS: 100-41-4	< 0.5	100 ppm STEL: 125 ppm	100 ppm STEL: 125 ppm	7.1 @ 20C	(5)
Titanium Dioxide; # CAS: 13463-67-7	0 - 35	10 mg/m3	10 mg/m3	N/A	
Pigments; Mixture; # CAS: Not Available	0 - 10	10 mg/m3	15 mg/m3 Total dust	N/A	(6)
Carbon Black; Pigment Black; # CAS: 1333-86-4	0 - 5	3.5 mg/m3	3.5 mg/m3	N/A	

\* SUBJECT TO REPORTING REQUIREMENT OF SECTION 313 OF TITLE III OF SARA (40 CFR PART 372).

- 1) Manufacturer's recommended exposure limit of 100 ppm.
- 2) This chemical is included on the list of Hazardous Air Pollutants (HAPs) from Title III of the Clean Air Act Amendments of 1990 (Glycol Ethers category).
- 3) Industry recommended exposure limit of 100 ppm.
- 4) Supplier recommended exposure limit of 10 mg/m3.
- 5) This chemical is included on the list of Hazardous Air Pollutants (HAPs) from Title III of the Clean Air Act Amendments of 1990.
- 6) The above ACGIH TLV exposure limit of 10 mg/m3 is for inhalable fraction. See Section 8 Exposure Controls, Personal Protection - Exposure Guidelines for more information on above exposure limits.

The recommended permissible exposure limits (PEL) indicated above reflect the levels adopted by OSHA in 1989. Although, some of the 1989 levels have since been vacated, the Nazdar Company recommends that the lower exposure levels be observed as reasonable worker protection.

### SECTION 3 - HAZARDS IDENTIFICATION

#### GENERAL HEALTH EFFECTS

THE FOLLOWING INFORMATION HAS BEEN DEVELOPED BASED UPON USING THE PRODUCT AS INTENDED BY THE MANUFACTURER. The potential health effects of this product are based on the hazards of its components. The use of this product in combination with other products may produce synergistic (additive) health effects. Cautionary labeling and material safety data sheets of all materials used with this product should be reviewed before use.

#### EYES

Eye contact with liquid, vapors or mists may cause severe irritation, including burning, tearing, redness or swelling and reversible eye damage.

#### SKIN

Skin contact may cause irritation.

Symptoms may include dryness, chapping, redness, skin burns and damage.

This material may be absorbed through the skin.

Toxic if absorbed through the skin.

#### INHALATION

Inhalation may cause respiratory tract irritation.

Symptoms may include central nervous system disorders such as headaches, dizziness, weakness and fatigue.

#### INGESTION

Ingestion may cause severe gastrointestinal tract irritation.

Symptoms may include headaches, nausea and vomiting.

Symptoms may include nervous system depression including drowsiness or unconsciousness.

Ingestion may cause vomiting. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

#### CHRONIC EFFECTS/TARGET ORGANS

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ethylbenzene is possibly carcinogenic to humans (IARC Group 2B).

#### ANIMAL STUDIES

Cyclohexanone has caused liver and kidney damage in animal tests.

1-Methyl-2-pyrrolidone (M-Pyrol) has been suggested as a cause of the following effects, after overexposure in laboratory animals, and may aggravate pre-existing disorders of these organs in humans; male and female reproductive fertility effects and damage to the blood forming system. M-Pyrol has been shown to cause birth defects in lab animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Dipropylene glycol dimethyl ether had liver, kidney and adrenal effects on lab animals and has been toxic to the fetus in lab animals at doses toxic to the mother. It did not cause birth defects in laboratory animals.

Diethylene glycol ethyl ether acetate has been suggested to cause kidney damage in lab animals.

Aliphatic dibasic acid esters (or its components) have been suggested as a cause of the following effects in lab animals, after overexposure, and may aggravate preexisting disorders of these organs in humans; mild, reversible liver effects, nasal damage.

For animal studies reference TSCA Section 4 Test Rule Results or contact the manufacturer for further details.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pregnant women and persons with pre-existing health disorders should consult their physician before using this product. Repeated and prolonged overexposure and/or individual sensitivity may increase the potential for and degree of adverse health effects. See Section 3 "Hazards Identification" for effects of certain hazardous ingredients.

#### ROUTES OF EXPOSURE

Primary exposure routes: Inhalation-Dermal (Contact/Absorption)-Ingestion.

---

### SECTION 4 - - FIRST AID MEASURES

---

#### EYES

After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If irritation persists have eyes examined and tested by medical personnel.

#### SKIN

In case of contact, immediately wash skin with a mild soap and plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Cool water is initially suggested to prevent the pores of the skin from opening. This will minimize both the area and time of skin contact. Lukewarm water may then be used to ensure all contaminants are removed.

Skin should be monitored for reddening or chemical burns. Mild soap is suggested to help prevent abrading the skin or rubbing the chemicals into pores during cleansing. Get medical attention if irritation persists or significant contact has occurred. Thoroughly wash (or discard) clothing and shoes before reuse.

#### INHALATION

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention if breathing difficulty is experienced.

#### INGESTION

If swallowed, do NOT induce vomiting. Call a Physician or poison control center immediately. Never give anything by mouth to an unconscious person.

---

### SECTION 5 - - FIRE FIGHTING MEASURES

---

#### FLASH POINT

114 Degrees

Fahrenheit

(PMCC)

#### OSHA FLAMMABILITY CLASSIFICATION (NFPA)

Class II Combustible Liquid

#### LEL - LOWER EXPLOSIVE LIMIT / UEL - UPPER EXPLOSIVE LIMIT

0.9% Volume in air / No Data Available

#### EXTINGUISHING MEDIA

Foam-CO2-Dry Chemical-Water Spray

#### FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Keep containers tightly closed. Vapors may be heavier than air and can travel to a source of ignition then flash back. Closed containers may explode when exposed to extreme heat.

#### FIRE FIGHTING EQUIPMENT

Full protective equipment including self-contained breathing apparatus is recommended to protect firefighters.

#### SPECIAL FIRE FIGHTING PROCEDURES

Water may be ineffective but may be used to cool containers. Fumes released on burning may be toxic and dangerous

---

### SECTION 6 - - ACCIDENTAL RELEASE MEASURES

---

#### RELEASE MANAGEMENT MEASURES

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid contact or breathing vapors. Ventilate area. Contain release and remove with inert absorbent. Use non-sparking tools to place material in appropriate container for disposal. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. The National Response Center (800-424-8802) and local authorities should be contacted for any reportable spill/release.

---

---

**SECTION 7 - - HANDLING AND STORAGE**

---

---

**HANDLING AND STORAGE METHODS**

Use in a well ventilated area. Follow all MSDS/label precautions even after container is emptied; container may retain product residues. Store in closed containers in cool, dry, well ventilated area away from sources of ignition. Keep containers closed when not in use. Smoke in designated areas only. Avoid prolonged or repeated overexposure to this product. Keep out of the reach of children. Follow label directions carefully. Do not take internally. Harmful or fatal if swallowed.

---

---

**SECTION 8 - - EXPOSURE CONTROLS, PERSONAL PROTECTION**

---

---

**RESPIRATORY PROTECTION**

If concentrations of hazardous ingredients exceed exposure limits listed in Section 2 an appropriate NIOSH (National Institute for Occupational Safety and Health) approved respirator with an organic vapor cartridge should be used. If material is handled under mist, spray or dust forming conditions, a P100 (99.97% efficiency) filter should be used in addition to the organic vapor cartridge. Protection provided by air-purifying respirators is limited. If no exposure limits are listed in Section 2, follow general safety guidelines in 29 CFR 1910.134 Respiratory Protection or other applicable respiratory standard.

**SKIN PROTECTION**

Use neoprene, nitrile or other gloves resistant to chemicals listed in Section 2. Contact a reputable safety supply company for appropriate gloves.

Solvent resistant aprons are recommended. Prevent prolonged skin contact with contaminated clothing.

**EYE PROTECTION**

Use ANSI approved safety glasses, faceshield or splash proof goggles to prevent eye contact. Contact a reputable safety supply company for appropriate eye protection. The availability of an eye wash is highly recommended.

**EXPOSURE GUIDELINES**

See Section 2 "Composition, Information on Ingredients" for occupational exposure limits.

Excessive concentrations of nuisance dusts or particulates not otherwise classified (PNOC) or regulated (PNOR) may reduce visibility and cause unpleasant deposits in the eyes, ears and nasal passages. The TLV and PEL has been established for all non-toxic "nuisance dusts" that are not otherwise classified and refers to both organic and inorganic dusts. Exposure or generation of these dusts is not anticipated during normal printing operations. The use of dry pigments and powders, grinding or sanding of printed products may generate quantities of these particulates. Refer to Section 2 Hazardous Ingredients for exposure limits.

**HYGIENIC PRACTICES**

Wash with soap and water before eating, smoking or using toilet facilities. Separately wash or discard clothing and footwear before reuse. Never try to remove ink from the skin by using solvent or thinner. Such action is likely to increase the possibility of undesirable effects. Remove contaminated clothing to prevent prolonged skin contact.

**ENGINEERING CONTROLS**

Use applicable engineering controls, work practices and personal protective equipment to ensure all concentrations are kept below the exposure limits listed in Section 2. Adequate controls should be implemented to ensure employee safety from fine mists which may be produced under some printing conditions.

---

---

**SECTION 9 - - PHYSICAL AND CHEMICAL PROPERTIES**

---

---

**APPEARANCE**

Viscous Liquid

**ODOR**

Characteristic

**PHYSICAL STATE**

Liquid

**pH**

Not applicable

**VAPOR PRESSURE**

See Section 2 for individual ingredients.

**VAPOR DENSITY**

Heavier than air

**BOILING POINT**

Greater than 300 degrees Fahrenheit

**FREEZING POINT**

Not available

**SOLUBILITY IN WATER**

Not tested

**EVAPORATION RATE**

Slower than ether

**VISCOSITY**

Greater than water

## NOTES

Percent volatile = Percent VOC

## SECTION 10 - - STABILITY AND REACTIVITY

## CHEMICAL STABILITY

Stable

## CONDITIONS TO AVOID

Avoid excessive heat, ignition sources, sparks and open flame.

## INCOMPATIBILITY WITH OTHER MATERIALS

Strong acids/bases, oxidizing/reducing agents and reactive chemicals.

## HAZARDOUS DECOMPOSITION PRODUCTS

May produce hazardous fumes when heated to decomposition e.g. carbon monoxide, carbon dioxide and other noxious gases.

## HAZARDOUS POLYMERIZATION

Not anticipated during normal printing and storage conditions.

## SECTION 11 - - TOXICOLOGICAL INFORMATION

## EXPERIMENTAL TOXICITY DATA

Refer to Section 3 Hazards Identification for additional toxicological data.

Experimental toxicity data on cyclohexanone has given the following results: Oral LD50 Rat: 1620 mg/kg; Dermal LD50 Rabbit: 1000 mg/kg; Inhalation TCLO Human: 75 ppm.

Experimental toxicity data on 1-Methyl 2-Pyrrolidone has given the following results: Oral LD50 Rat: 7000 mg/kg; Intraperitoneal LD50 Mouse: 15000 mg/kg

Experimental toxicity data on gamma butyrolactone has given the following results: Oral LD50 Rat: 1.8 g/kg.

Experimental toxicity data on petroleum distillate CAS# 64742-94-5 has given the following results: Oral LD50 Rat: 10 ml/kg; Dermal LD50 Rabbit 4 ml/kg; Inhalation LC50 Rat: 3800 mg/m<sup>3</sup> 4 hours.

## SECTION 12 - - ECOLOGICAL INFORMATION

## ECOTOXICITY

Because this product may be a mixture of chemicals, some of which may be ecologically toxic, it is strongly suggested that it not be disposed of into the environment, i.e. soil, water courses, lakes, landfills, sewers, etc.

## ENVIRONMENTAL FATE

No data available

## SECTION 13 - - DISPOSAL CONSIDERATIONS

## DISPOSAL METHODS

This product is considered hazardous for disposal purposes by the U.S. Environmental Protection Agency Resource Conservation and Recovery Act (RCRA). Contact Nazdar's Regulatory Compliance Department or refer to the regulations located in 40 CFR Part 261 for additional waste disposal information, including appropriate hazardous waste codes. It is the responsibility of the user to determine if local, county, state, or provincial regulations may also apply to the disposal of this product and/or the container. Empty containers may retain hazardous properties and should be disposed of in an environmentally safe manner in accordance with applicable regulations.

## SECTION 14 - - TRANSPORT INFORMATION

## TRANSPORT INFORMATION

DOT Proper Shipping Description: Printing Ink, 3, UN1210, PG III

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

Questions concerning transportation requirements should be directed to Nazdar's Regulatory Compliance Department 913-422-1735.

## SECTION 15 - - REGULATORY INFORMATION

## SARA TITLE III 313 INFORMATION

See Section 2 "Composition, Information on Ingredients" for applicable chemicals.

## TOXIC SUBSTANCES CONTROL ACT STATUS

All Ingredients in Section 2 are listed on the U.S. Environmental Protection Agency's Toxic Substances Control Act (TSCA) Inventory and the Canadian Domestic Substance List.

#### OTHER REGULATORY INFORMATION

OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION (OSHA) - MSDS is compliant with OSHA Hazard Communication Standard - 29 CFR 1910.1200. AMERICAN NATIONAL STANDARDS INSTITUTE - This MSDS follows the ANSI Z400.1-1998 format. WORKPLACE HAZARDOUS MATERIAL INFORMATION SYSTEM (WHMIS) - This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS CLASSIFICATION (CANADA)

B3 - Combustible Liquids;

D1B - Material causing immediate and serious toxic effects, toxic material;

D2A - Materials causing other toxic effects, very toxic material;

D2B - Materials causing other toxic effects, toxic material;

---

#### SECTION 16 - OTHER INFORMATION

---

#### DISCLOSURE

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind express or implied is made with respect to the information contained herein. The data in this MSDS relates only to the specific material designated herein and does not apply to use in combination with any other material or process.

#### DEFINITIONS

ACGIH: American Conference of Governmental Industrial Hygienists.

AIHA: American Industrial Hygiene Association

CEILING: (TLV-Ceiling and PEL Ceiling Limit) The ceiling exposure limit or concentration not to be exceeded for even brief times.

DOT: Department of Transportation

HMIS: The Hazardous Materials Identification System (HMIS) developed by the National Paint and Coatings Association (NPCA) to provide information on the acute health hazards, reactivity and flammability of products encountered in the workplace at room temperatures.

HMIS codes assigned for this product are only suggested ratings based on anticipated normal screen printing applications. The employer has the ultimate responsibility for assigning these ratings and should fully evaluate the MSDS, work practices and environmental conditions prior to assigning the appropriate ratings.

HMIS rating involves data interpretations that may vary from company to company.

HMIS Personal Protection Index of "X-Ask your supervisor" is given on this MSDS due to varying work conditions which may dictate different levels of protection. Please review this MSDS before determining appropriate protective equipment and beginning work.

IARC: International Agency for Research on Cancer

NFPA: National Fire Protection Association

NTP: National Toxicology Program

STEL: Short-Term Exposure Limit: ACGIH terminology for the short-term exposure limit or maximum concentration for a continuous exposure period of 15 minutes.

TLV: Threshold Limit Value. A term ACGIH uses to express the airborne concentration of a material to which most workers can be exposed during a normal daily and weekly work schedule without adverse effects.

TWA: Time-Weighted Average

VOC: Volatile Organic Compound