



## Material Safety Data Sheet

Prepared in accordance with ISO 11014-1/ANSI standard Z400.1-2004

Print Date Aug-25-2009

Revision Date Aug-25-2009

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product code** LWS1300KK  
**Product name** Black  
**Product description** Lyson® 1300 Series Piezo Inkjet Ink

#### Manufacturer or supplier's details

UNITED STATES  
Nazdar Company  
8501 Hedge Lane Terrace  
Shawnee, KS 66227  
Tel: 1-913-422-1888  
Tel: 1-800-677-4657  
Fax: 1-913-422-2294

UNITED KINGDOM  
Nazdar Limited  
7 Barton Road  
Heaton Mersey Industrial Estate  
Stockport, Chesire SK4 3EG  
Tel: +44 161 442 2111

#### Emergency Telephone Number

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887

Website: [www.nazdar.com](http://www.nazdar.com)  
MSDS Information: 1-913-422-1888 ext 2305  
MSDS Contact: Regulatory Compliance  
email: [regcomp@nazdar.com](mailto:regcomp@nazdar.com)

### 2. HAZARDS IDENTIFICATION

*This product is a preparation. Health hazard information is based on its components.*

**Appearance** Viscous liquid  
**Flammable Properties** Combustible liquid and vapor.  
**Emergency Overview** Irritant. May cause drowsiness and dizziness.

**Eyes** Moderately irritating to the eyes. Risk of serious damage to eyes. Avoid contact with eyes.  
**Skin** May cause skin irritation and/or dermatitis. May be harmful if absorbed through skin.  
**Inhalation** May cause irritation of respiratory tract. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Ethylene glycol monobutyl ether acetate	112-07-2	30 - 60
Diethylene Glycol Ethyl Ether Acetate	112-15-2	10 - 30
Gamma Butyrolactone	96-48-0	10 - 30
Cyclohexanone	108-94-1	5 - 10
Propylene glycol monomethyl ether acetate	108-65-6	1 - 5
Carbon black	1333-86-4	1 - 5

### 4. FIRST AID MEASURES

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

**Skin Contact** Wash off immediately with soap and plenty of water. Use a mild soap if available. Rinse immediately with plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation develops, get medical attention.

**Inhalation** Move to fresh air. If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion** If swallowed, DO NOT induce vomiting. Call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person.

## 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Combustible liquid and vapor.
<b>Suitable Extinguishing Media</b>	Foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from fire, sparks and heated surfaces. Keep container tightly closed. Cool containers / tanks with water spray. Fire or intense heat may cause violent rupture of packages.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. Burning produces obnoxious and toxic fumes.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Remove all sources of ignition. Heat, flames and sparks. Ventilate the area. Avoid breathing dust or vapor. Avoid contact with skin, eyes and clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
<b>Methods for Cleaning Up</b>	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Do not use sparking tools.
<b>Environmental Precautions</b>	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove and wash contaminated clothing before re-use. Discard contaminated shoes. When using do not smoke. Take notice of labels and material safety data sheets for the working chemicals. Do not take internally. Harmful or fatal if swallowed.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of the reach of children. Keep away from heat and sources of ignition. Take notice of the directions of use on the label.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Ontario TWAEV	Mexico OEL (TWA)
Ethylene glycol monobutyl ether acetate	TWA: 20 ppm			TWA: 20 ppm	
Cyclohexanone	TWA: 20 ppm Skin STEL: 50 ppm	TWA: 25 ppm TWA: 100 mg/m <sup>3</sup> Skin TWA: 50 ppm TWA: 200 mg/m <sup>3</sup>	700 ppm	TWA: 20 ppm STEL: 50 ppm Skin	TWA: 50 ppm TWA: 200 mg/m <sup>3</sup> STEL: 400 mg/m <sup>3</sup> STEL: 100 ppm
Propylene glycol monomethyl ether acetate				TWA: 50 ppm TWA: 270 mg/m <sup>3</sup>	
Carbon black	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	1750 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>

<b>Engineering Measures</b>	Use only with adequate ventilation. Use ventilation adequate to keep exposures below recommended exposure limits. See MSDS. In case of insufficient ventilation, wear suitable respiratory equipment.
-----------------------------	---

### Personal Protective Equipment

<b>Respiratory Protection</b>	Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Respirator with a vapour filter.
<b>Eye Protection</b>	Ensure that eyewash stations and safety showers are close to the workstation location. Avoid contact with eyes. Safety glasses with side-shields. Goggles. Face-shield.
<b>Skin Protection</b>	Wear protective gloves/clothing. Solvent-resistant apron and boots.
<b>General Hygiene Considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands before eating, drinking, or smoking. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wear suitable gloves and eye/face protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Viscous liquid	<b>Physical State</b>	Liquid
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available	<b>Autoignition Temperature</b>	No information available
<b>Boiling point/Boiling Range</b>	>149°C / >300°F	<b>Melting Point/Range</b>	No information available
<b>Freezing Point/Range</b>	No information available	<b>Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available	<b>Partition Coefficient (n-octanol/water)</b>	No information available
<b>Vapour Pressure</b>	No information available	<b>Vapour Density</b>	No information available
<b>Flammability (solid, gas)</b>	No information available	<b>Flash Point</b>	64°C / 147°F
<b>Flammability Limits in Air</b>		<b>Method</b>	Setaflash closed cup
<b>Upper</b>	No information available	<b>Photochemically Reactive</b>	No
<b>Lower</b>	No information available		
<b>Weight Per Gallon (lbs/gal)</b>	8.281	<b>Specific Gravity</b>	0.993
<b>VOC by weight</b>	93.679	<b>VOC by volume</b>	94.373
<b>VOC lbs/gal (less water)</b>	7.765	<b>VOC grams/liter (less water)</b>	930.497

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Products</b>	Strong acids. Strong bases. Strong oxidizing agents. Reducing agents.
<b>Hazardous Decomposition Products</b>	Thermal decomposition can lead to release of irritating gases and vapours. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol monobutyl ether acetate	1600 mg/kg ( Rat )	1480 mg/kg ( Rabbit )	
Diethylene Glycol Ethyl Ether Acetate	11 g/kg ( Rat )	15100 µL/kg ( Rabbit )	
Gamma Butyrolactone	1540 mg/kg ( Rat )		2.68 mg/L ( Rat ) 4 h
Cyclohexanone	800 mg/kg ( Rat )	948 mg/kg ( Rabbit )	10.7 mg/L ( Rat ) 4 h 8000 ppm ( Rat ) 4 h
Propylene glycol monomethyl ether acetate	8532 mg/kg ( Rat )	5000 mg/kg ( Rabbit )	
Carbon black	15400 mg/kg ( Rat )	3 g/kg ( Rabbit )	

**Chronic Toxicity**

Component	ACGIH	IARC	NTP	OSHA
Ethylene glycol monobutyl ether acetate	A3			
Cyclohexanone	A3			
Carbon black		Group 2B		X

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B). In their evaluation of carbon black, IARC indicates exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

ACGIH: (American Conference of Governmental Industrial Hygienists)  
IARC: (International Agency for Research on Cancer)  
OSHA: (Occupational Safety & Health Administration)

A3 - Animal Carcinogen  
Group 2B - Possibly Carcinogenic to Humans  
X - Present

<b>Sensitisation</b>	No information available
<b>Mutagenic Effects</b>	No information available
<b>Reproductive Effects</b>	No information available
<b>Developmental Effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Chronic Effects</b>	Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.
<b>Target Organ Effects</b>	Blood, Central nervous system, Eyes, Hematopoietic System, Liver, Kidney, Lymphatic System, Respiratory system, Skin.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

We have no quantitative data concerning the ecological effects of this product. Should not be released into the environment.

Component	Freshwater Algae	Freshwater Fish	Water Flea
Ethylene glycol monobutyl ether acetate	72 Hr EC50 Scenedesmus subspicatus: >500 mg/L		48 Hr EC50 water flea: 37 mg/L
Gamma Butyrolactone	72 Hr EC50 Scenedesmus subspicatus: 360 mg/L; 96 Hr EC50 Scenedesmus subspicatus: 79 mg/L	96 Hr LC50 Leuciscus idus: 220-460 mg/L [static]	48 Hr EC50 Daphnia magna Straus: >500 mg/L
Cyclohexanone	96 Hr EC50 Chlorella vulgaris: 20 mg/L	96 Hr LC50 Pimephales promelas: 8.9 mg/L	48 Hr EC50 water flea: 820 mg/L; 48 Hr EC50 Daphnia magna: 800 mg/L
Propylene glycol monomethyl ether acetate		96 Hr LC50 Pimephales promelas: 161 mg/L [static]	48 Hr EC50 Daphnia magna: >500 mg/L
Carbon black			24 Hr EC50 Daphnia magna: >5600 mg/L

<b>Persistence and Degradability</b>	No information available
<b>Bioaccumulation</b>	No information available
<b>Mobility in Environmental Media</b>	No information available

Component	log Pow
Ethylene glycol monobutyl ether acetate	1.51
Gamma Butyrolactone	-0.566
Cyclohexanone	0.86
Propylene glycol monomethyl ether acetate	0.43

**13. DISPOSAL CONSIDERATIONS**

<b>Waste Disposal Methods</b>	Dispose of contents/container in accordance with local regulation.
-------------------------------	--

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

**DOT**

Printing Ink, Not Regulated

**ICAO/IATA**

Not classified as dangerous in the meaning of transport regulations

**IMDG/IMO**

Not classified as dangerous in the meaning of transport regulations

## 15. REGULATORY INFORMATION

**International Inventories**

Listed on TSCA. For further information, please contact: Manufacturer, importer, supplier

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Ethylene glycol monobutyl ether acetate	112-07-2	30 - 60	1.0
Diethylene Glycol Ethyl Ether Acetate	112-15-2	10 - 30	1.0

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Component	CAS-No	Weight %
Ethylene glycol monobutyl ether acetate	112-07-2	30 - 60
Diethylene Glycol Ethyl Ether Acetate	112-15-2	10 - 30

**U.S. State Regulations****California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Component	CAS-No	Weight %
Carbon black	1333-86-4	1 - 5

**State Right-to-Know**

Component	Minnesota	Florida	New Jersey	Pennsylvania	Massachusetts	Rhode Island
Ethylene glycol monobutyl ether acetate	Not Listed	Not Listed	X	X	Not Listed	Not Listed
Diethylene Glycol Ethyl Ether Acetate	Not Listed	Not Listed	X	X	Not Listed	Not Listed
Gamma Butyrolactone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Cyclohexanone	Not Listed	Not Listed	X	X	X	X
Propylene glycol monomethyl ether acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Carbon black	Not Listed	Not Listed	X	X	X	X

**Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR

Component	WHMIS Classifications of Components
Ethylene glycol monobutyl ether acetate	B3
Diethylene Glycol Ethyl Ether Acetate	Uncontrolled product according to WHMIS classification criteria
Cyclohexanone	B3, D1B, D2B
Propylene glycol monomethyl ether acetate	B3
Carbon black	D2A

Component	NPRI - National Pollutant Release Inventory
Ethylene glycol monobutyl ether acetate	Part 4 Substance Part 5 Substance
Diethylene Glycol Ethyl Ether Acetate	Part 4 Substance Part 5 Substance
Gamma Butyrolactone	Part 4 Substance
Cyclohexanone	Part 4 Substance
Propylene glycol monomethyl ether acetate	Part 4 Substance Part 5 Substance

**REACH: Substances of Very High Concern (SVHC): Article 57 of Regulation (EC) No 1907/2006**

Does NOT contain a listed substance

**HMIS:**

<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>PPE</b>
3*	2	0	X

## 16. OTHER INFORMATION

Revision Date Aug-25-2009

Revision Summary New MSDS format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of MSDS**