

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM

SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE. DO NOT ENTER THE FIRE AREA WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE & EXPLOSION HAZARDS

CONDITIONS OF FLAMMABILITY: AVOID SOURCES OF IGNITION, FLAME, STATIC ELECTRICITY, HEAT OR ELECTRICAL SPARK.

SENSITIVITY TO MECHANICAL IMPACT: N.E.

SENSITIVITY TO STATIC DISCHARGE: CONTAINERS SHOULD BE GROUNDED^g WHEN POURING. ALL ELECTRICAL EQUIPMENT AND INSTALLATIONS SHOULD BE MADE AND GROUNDED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE. WORKERS ARE REQUIRED TO USE ONLY NON-FERROUS TOOLS AND WEAR NON-SPARKING SHOES IN AREAS WHERE EXPLOSION HAZARDS EXIST.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: EXCESSIVE HEAT
INCOMPATIBILITY (MATERIALS TO AVOID): AVOID CONTACT WITH: STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, NO_x
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - TOXICOLOGICAL PROPERTIES

THRESHOLD LIMIT VALUE: SECTION II

EFFECTS OF ACUTE OVEREXPOSURE

INHALATION - CAN CAUSE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION, FATIGUE OR UNCONSCIOUSNESS.
INGESTION - SEVERE GASTROINTESTINAL DISTURBANCES CAN OCCUR INCLUDING NAUSEA, VOMITING, ANOREXIA, AND CONSTIPATION. ASPIRATION OF THIS PRODUCT INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONIA WHICH MAY BE FATAL.
EYES - CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. CONJUNCTIVAL AND CORNEAL INJURY MAY ALSO RESULT.
SKIN - CAN CAUSE IRRITATION AND DRYING OF SKIN. MAY ALSO CAUSE DERMATITIS AND ULCERATIONS.

EFFECTS OF CHRONIC OVEREXPOSURE

INHALATION AND INGESTION - PROLONGED OVEREXPOSURE TO SOLVENTS CAN CAUSE KIDNEY, LIVER AND OTHER SYSTEMIC DAMAGE. EXPOSURE TO SOLVENTS FOR PROLONGED TIMES AT MODERATE LEVELS CAN AFFECT HIGHER BRAIN FUNCTIONS AND MENTAL CAPACITY.

OTHER PRECAUTIONS: CHRONIC OVEREXPOSURE TO, AND MISUSE OF, SOLVENTS HAS BEEN LINKED TO PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

SENSITIZATION: SEE OVEREXPOSURE EFFECTS
TERATOGENICITY: N.E.
MUTAGENICITY: N.E.

TOXICOLOGICAL SYNERGISTIC PRODUCTS: N.E.

SECTION VII - PREVENTIVE MEASURES

RESPIRATORY PROTECTION: ORGANIC VAPOR RESPIRATOR WITH PARTICULATE FILTER APPROVED BY NIOSH.

PROTECTIVE GLOVES: BUTYL RUBBER OR EQUIVALENT.

EYE PROTECTION: SPECTACLES WITH SIDE SHIELDS.

OTHER PROTECTIVE EQUIPMENT: NONE

VENTILATION

LOCAL EXHAUST: PREFERRED - PAINT SPRAY BOOTH, 150 FPM FACE VELOCITY.

SPECIAL: NONE

MECHANICAL (GENERAL): ACCEPTABLE FOR SMALL VOLUME APPLICATIONS.

OTHER: NONE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE ALL HEAT SOURCES, OPEN FLAMES, AND OTHER SOURCES OF IGNITION. ABSORB WITH SOLID ABSORBENT. SHOVEL (NON-FERROUS) INTO CONTAINERS. IF LARGE QUANTITIES ARE SPILLED, PERSONAL PROTECTIVE EQUIPMENT MAY BE REQUIRED.

WASTE DISPOSAL METHOD: DISPOSE AS PAINT WASTE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: SECURE CLOSURES AND KEEP CONTAINERS UPRIGHT TO PREVENT LEAKAGE. STORE IN COOL, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.

OTHER PRECAUTIONS: AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE, OR WELD WITHOUT NIOSH/MSHA-APPROVED MECHANICAL FILTER RESPIRATOR OR APPROPRIATE AND ADEQUATE VENTILATION. IF WORKERS ARE EXPOSED TO SPRAY APPLICATION OR ABRASIVE BLAST CLEANING, ENGINEERING AND ADMINISTRATIVE CONTROLS MUST BE USED TO MAINTAIN AN EXPOSURE LEVEL BELOW THE OSHA REQUIRED LEVEL, OR, USE A NIOSH/MSHA-APPROVED MECHANICAL FILTER RESPIRATOR FOR PROTECTION.

SPRAY APPLICATION: IF THE PRODUCT IS SPRAY APPLIED, USE A PARTICULATE RESPIRATOR. IF YOU CANNOT, OR, ARE UNSURE IF YOU KNOW HOW TO USE THIS PRODUCT IN A SAFE AND RESPONSIBLE MANNER, INCLUDING, BUT NOT LIMITED TO THE ABOVE PRECAUTIONS, DO NOT USE THIS PRODUCT.

SPECIAL SHIPPING INFORMATION: PAINT MUST BE SHIPPED IN METAL CONTAINERS AND PACKED IN STRONG OUTSIDE CARTONS (DOT-12B 30) WITH THE UN NUMBER (UN 1263), THE DESCRIPTION OF THE MATERIAL, AND THE FLASH POINT MARKED ON THE OUTSIDE PACKAGE.

SECTION VIII - FIRST AID MEASURES

INHALATION - IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR. IF NOT BREATHING, RESTORE BREATHING. GET MEDICAL HELP OR A PHYSICIAN IMMEDIATELY.

EYE CONTACT - FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. GET MEDICAL HELP OR A PHYSICIAN IMMEDIATELY.

SKIN CONTACT - REMOVE EXCESS MATERIAL WITH PAPER TOWELS OR RAGS. WASH WITH MILD SOAP AND WARM WATER. IF ANY REDNESS OR SWELLING PERSISTS, GET MEDICAL ATTENTION.

INGESTION - IF INGESTED, DO NOT INDUCE VOMITING. GET MEDICAL HELP OR A PHYSICIAN IMMEDIATELY.

SECTION IX - REGULATORY INFORMATION

SARA 313 / TITLE III: THIS PRODUCT LINE CONTAINS TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN. WE ACCEPT NO RESPONSIBILITY AND DISCLAIM ALL LIABILITY FOR ANY HARMFUL EFFECTS WHICH MAY BE CAUSED BY EXPOSURE TO OUR PRODUCTS. CUSTOMERS/USERS OF THIS PRODUCT MUST COMPLY WITH ALL APPLICABLE HEALTH AND SAFETY LAWS, REGULATIONS, AND ORDERS.

4