

MATERIALSAFETYDATASHEET

57231GNSGILIGHTPURPLE

Version Number 1.0
RevisionDate 06/12/2002

Page 1 of 6
PrintDate 12/12/2003

1.PRODUCTANDCOMPANYIDENTIFICATION

POLYONECORPORATION
2700PapinStreet,St.Louis,MO63103

NON-EMERGENCY TELEPHONE : ProductStewardship,(314)771-1800
Emergencytelephone number : **CHEMTREC1-800-424-9300(24hrsforspill,leak,fire,exposure oraccident).**

Productname : 57231GNSGILIGHTPURPLE
 Productcode : FO00001603
 ChemicalName : Mixture
 CAS-No. : Mixture
 ProductUse : IndustrialApplications

2.COMPOSITION/INFORMATIONONHAZARDOUSINGREDIENTS

Components	CAS-No.	Weight%
1,2-Benzenedicarboxylicacid,butyl phenylmethylester	85-68-7	1- 5
Silica,amorphous	7631-86-9	1- 5
Calciumcarbonate	1317-65-3	10- 30
Titaniumdioxide	13463-67-7	10- 30

3.HAZARDSIDENTIFICATION**EMERGENCYOVERVIEW**

Thismixturehasnotbeenevaluatedasawholeforhealtheffects.Informationprovidedonhealth effectsofthisproductisbasedontheindividualcomponents.However,somevaporsorcontaminants maybereleaseduponheatingandtheend-user(fabricator)musttakethenecessaryprecautions (mechanicalventilation,respiratoryprotection,etc.)toprotectemployeesfromexposure.See sections8and11forspecialprecautions.

POTENTIALHEALTHEFFECTS

RoutesofExposure: : Inhalation,Skincontact,Ingestion

Acuteexposure

Inhalation : Inhalationofairbornedropletsmaycauseirritationoftherespiratory tract.
 Ingestion : Maybeharmfulifswallowed.
 Eyes : Maycauseeye/skinirritation.
 Skin : Experienceshowsnounusualdermatitishazardfromroutinehandling.

MATERIAL SAFETY DATA SHEET

57231GNSGILIGHTPURPLE

Version Number 1.0

Page 2 of 6

RevisionDate 06/12/2002

PrintDate 12/12/2003

Chronic exposure : RefertoSection11forToxicologicalInformation.

Medical Conditions : Noneknown.

Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Movetofreshairincaseofaccidentalinhilationoffumesfrom overheatingorcombustion. Whensymptomspersist,orinallcases ofdoubt,seekmedicaladvice.

Ingestion : Donotinducevomitingwithoutmedicaladvice. Whensymptoms persist,orinallcasesofdoubt,seekmedicaladvice.

Eyes : Rinseimmediatelywithplentyofwaterforatleast15minutes. Ifeye irritationpersists,seekmedicalattention.

Skin : Washoffwithsoapandplentyofwater. Ifskinirritationpersists seekmedicalattention.

5. FIRE-FIGHTING MEASURES

Flashpoint : Nodataavailable.

Flammable Limits

Upperexplosionlimit : Nodataavailable.

Lowerexplosionlimit : Nodataavailable.

Autoignition temperature : Notapplicable.

Suitable extinguishing media : Carbondioxideblanket,drypowder,foam,Waterspray .

Special Fire Fighting Procedures : Fullfaceself-containedbreathingapparatus(SCBA)usedinpositive pressuremodeshouldbeworntopreventinhalationofairborne contaminants.

Unusual Fire/Explosion Hazards : MayemitHydrogenChloride(HCl)orCarbonMonoxide(CO)under fireconditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wearappropriatepersonalprotectionduringcleanup,suchas imperviousgloves,bootsandcoveralls.

Environmental precautions : Shouldnotbereleasedintotheenvironment. Theproductshouldnot beallowedtoenterdrains,watrecoursesorthesoil.

Methods for cleaning up : Soakupwithinertabsorbentmaterial(e.g.sand,silicagel,acid binder,universalbinder,sawdust). Packageallmaterialin appropriatecontainerfordisposal. RefertoSection13ofthisMSDS forproperdisposalmethods.

7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET

57231 GNSGILIGHT PURPLE

Version Number 1.0
 Revision Date 06/12/2002

Page 3 of 6
 Print Date 12/12/2003

Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective Measures : Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10mg/m ³	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5mg/m ³	PEL:	Respirable dust.	OSHA Z1
	15mg/m ³	PEL:	Total dust.	OSHA Z1
Silica, amorphous	20mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10mg/m ³	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15mg/m ³	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid	Evaporation rate	: Not established
Appearance	: Viscous, Liquid	Specific Gravity	: Not determined
Color	: PURPLE	Bulk density	: Not applicable.
Odor	: Very faint	Vapor pressure	: Not determined
Melting point/range	: Not applicable	Vapor density	: Not determined
Boiling Point:	: Not applicable	pH	: Not applicable.

MATERIAL SAFETY DATA SHEET

57231GNSGILIGHTPURPLE

Version Number 1.0

Page 4 of 6

RevisionDate 06/12/2002

PrintDate 12/12/2003

Watersolubility : Immiscible

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177°C (350°F), after 10 minutes at 204°C (400°F), and within 5 minutes at 232°C (450°F).**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin .
		Systemic effects	Liver, reproductive system .
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system .
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin .
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system .

LC50/LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg >10 gm/kg	rat rabbit

12. ECOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET

57231GNSGILIGHTPURPLE

Version Number 1.0

Page 5 of 6

RevisionDate 06/12/2002

PrintDate 12/12/2003

Persistenceanddegradability : Notreadilybiodegradable.

EnvironmentalToxicity : Environmentaltoxicityhasnotbeenestablishedforthismixtureasa whole.

BioaccumulationPotential : Nodataavailable.

Additionaladvice : Nodataavailable.

13.DISPOSAL CONSIDERATIONS

Product : Wherepossible,recyclingispreferredtodisposalorincineration. Thegeneratorofwastematerialhas theresponsibilityforproper waste classification,transportationanddisposalinaccordancewith applicablefederal,state/provincialandlocalregulations.

Contaminatedpackaging : Recyclingispreferredwhenpossible. Thegeneratorofwaste materialhas theresponsibilityforproperwaste classification, transportationanddisposalinaccordancewithapplicablefederal, state/provincialandlocalregulations.

14.TRANSPORT INFORMATION

U.S.D.O.T./CAT.D.G. Classification(Non-bulk ground) : Notregulatedfortransportation.

ICAO/IATA : Notregulatedfortransportation.

IMO/IMDG : Notregulatedfortransportation.

15.REGULATORY INFORMATION

US Regulations:

OSHA Status : Classifiedashazardousbasedoncomponents.

TSCA Status : AllcomponentsofthisproductarelistedontheTSCAinventoryor areexempt.

US.EPACERCLA Hazardous Substances(40CFR302)

ChemicalName	CAS-No.	%inProduct	RQforcomponent	RQfor Mixture/Product
1,2-Benzenedicarboxylic acid, butyl phenylmethylester	85-68-7	2.84	100lbs	3,519LB

57231GNSGILIGHTPURPLE

Version Number 1.0

RevisionDate 06/12/2002

Page 6 of 6

PrintDate 12/12/2003

California Proposition 65 : WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7440-38-2
7439-92-1
7631-86-9
85-68-7
75-01-4

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.