

WILFLEX REDUCER #4, SCREEN CLEANER

Product: REDUCER4

Revision Date: 2001/10/11

Section 1 : PRODUCT AND COMPANY IDENTIFICATION

Chemical family: Hydrotreated Distillates.

Supplier: Same as manufacturer.

Manufacturer: PolyOne – Kennesaw
8155 Cobb Center Drive
Kennesaw, GA 30152
USA.

**Manufacturer emergency
phone number:** 800-424-9300.

Section 2 : INGREDIENT INFORMATION

C.A.S.	Concentration %	Ingredient Name	T.L.V.	LD/50	LC/50
64742-47-8	100	PETROLEUM DISTILLATE	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE

Section 3 : HAZARD IDENTIFICATION

Route of entry: Inhalation, skin and eye contact.

Effects of acute exposure

Eye contact: May cause irritation.

Skin contact: May cause irritation.

Inhalation: Not available.

Ingestion: May be harmful if swallowed.

Effects of chronic exposure: No data on symptoms available.

Sensitization to product: Not available.

Carcinogenic effects: Not available.

Reproductive effects: Not available.

Teratogenicity: Not available.

Mutagenicity: Not available.

Synergistic materials: Not available.

Section 4 : FIRST AID MEASURES

Skin contact: Remove contaminated clothing.
Wash with mild soap and water.
Consult a physician if irritation persists.

Eye contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting upper and lower lids. Get prompt medical attention.
Use gently flowing water.

Inhalation: Remove victim to fresh air.
If irritation occurs, consult a physician.

Ingestion: Do not induce vomiting or give anything by mouth to an unconscious victim.
Seek medical attention.

Additional information: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any inaccuracies.

Section 5 : FIRE FIGHTING MEASURES

Flammability: Combustible.

Conditions of flammability: At temperatures at or above flash point.

Extinguishing media: Carbon dioxide, dry chemical, foam.
Water

Special procedures: Self-contained breathing apparatus required.
Firefighters should wear the usual protective gear.

Auto-ignition temperature: Not available.

Flash point (°C), method: 60.5

Lower flammability limit (% vol): Not available.

Upper flammability limit (% vol): Not available.

Explosion Data

Sensitivity to static discharge: Not available.

Sensitivity to mechanical impact: Not available.

Hazardous combustion products: Carbon monoxide.
Carbon dioxide.

Rate of burning: Not available.

Explosive power: Not available.

Section 6 : ACCIDENTAL RELEASE MEASURES

Leak/Spill: Eliminate all sources of ignition.
Absorb with inert material.
Dike area to prevent spreading.
Wear appropriate protective equipment.
Place in a closed container for disposal.

Section 7 : HANDLING AND STORAGE

Handling procedures and equipment: Avoid smoking, drinking, or eating during use.
Handle and open container with care.
Keep away from heat, sparks, and open flame.
Avoid breathing vapors/mists.
Wash clothing before re-use.
Wash thoroughly after handling.
Avoid contact with skin, eyes and clothing.

Storage requirements: Store in a well ventilated area.
Store away from incompatible materials.
Keep container closed when not in use.
Keep away from excessive heat.
Store in a cool, dry area in a closed container.
Store at temperatures below 37.7°C.

Section 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautionary Measures

Gloves/Type:



Wear protective gloves.

Respiratory/Type: None required under normal use.

Eye/Type:



Safety glasses or goggles.

Footwear/Type: Safety boots per local regulations.

Clothing/Type: As required to prevent skin contact.

Other/Type: Eye wash facility should be in close proximity.
Emergency shower should be in close proximity.

Ventilation requirements: Adequate ventilation.

Exposure limit of material: Not available.

Section 9 : PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid.

Appearance & odor: Viscous.

Odor threshold (PPM): Not available.

Vapour pressure (mm hg): < 1

Vapour density (air=1): Not available.

Volatiles (%)

By volume: Not available.

**Evaporation rate
(butyl acetate = 1):** Not available.

Boiling point (°C): Not available.

Freezing point (°C): Not available.

PH: Not available.

Specific gravity @ 20 °C: 0.772

Solubility in water (%): Not available.
Coefficient of water/oil dist.: Not available.
VOC: < 820 g/l

Section 10 : STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.
Conditions of reactivity: Excessive heat.
Hazardous polymerization: Not available.
Incompatible substances: Strong oxidizers.
Hazardous decomposition products: See hazardous combustion products.

Section 11 : TOXICOLOGICAL INFORMATION

LD50 of product, species & route: Not available.
LC50 of product, species & route: Not available.

Section 12 : ECOLOGICAL INFORMATION

Environmental toxicity: No data at this time.
Environmental fate: No data at this time.

Section 13 : DISPOSAL CONSIDERATIONS

Waste disposal: In accordance with municipal, provincial and federal regulations.

Section 14 : TRANSPORT INFORMATION

TDG classification: FLAMMABLE
LIQUIDS
N.O.S.
(PETROLEUM
NAPHTHA)
UN 1993
CLASS 3
PG III.
(in bulk only).
Petroleum Distillates
UN1268
Class 3
PG III.
(Air shipments).



Special shipping information: Not regulated.

Section 15 : REGULATORY INFORMATION

WHMIS classification:

B3



DSL status: Appears on DSL.

SARA (313) chemicals: Hydrotreated distillates (CAS# 64742-47-8).

Section 16 : OTHER INFORMATION

Supplier MSDS date: 2001/10/11

This MSDS was generated by *Conform-Plus* Application Service. Visit us at www.3dword.com.