



## Material Safety Data Sheet

### 1. Article and Corporate Identification

#### 1.1. Product:

EcoXtreme Ink, AI-YE

#### 1.2. Manufacturer/Distributor:

Manufacturer's name:

Roland DG Corporation

Address:

1-6-4 Shinmiyakoda Hamamatsu-shi

Shizuoka 431-2103

JAPAN

Phone:

+ 81-53-484-1224

Fax:

+ 81-53-484-1221

#### 1.3. Medical Emergency Number

Not Available

### 2. Composition Information

This is a solvent ink formulation

Ink Composition	CAS No.	% By Weight
Pigment	Listed	3-7%
Polymer	Listed	3-7%
Dispersant	Listed	1-3%
Ethylene glycol monobutyl ether acetate	112-07-2	76-90%
N-methyl pyrrolidone	872-50-4	3-7%

### 3. Hazard Identification

#### 3.1 Emergency Overview:

Ink component is a yellow liquid that cause eye, nose or throat irritation, and that effects anesthesia, if inhaled. Ink may flash, when under high temperature. Avoid contact with eyes or clothing. In the case of skin contact, wash with soap and water.

#### 3.2 Potential Health Effects:

**Eye:** Ink contact with eye will be irritating. See Section 11 for Toxicology.

**Skin:** Ink contact with skin may cause minimally irritation. See Section 11 for Toxicology.

**Inhalation:** Intentional exposure to ink vapors (mist) will cause respiratory irritation and anesthesia. See Section 11 for Toxicology.

**Ingestion:** May cause upset stomach. See Section 11 for Toxicology.



#### 4. First Aid Measures

- 4.1 Eyes: Immediately flush with room temperature, low pressure, clean water for at least 15 minutes. Seek medical attention if eye irritation continues.
- 4.2 Skin: Wash surface areas with soap and water. Wash soiled clothing before rewearing. Consult a physician if inflammation continues.
- 4.3 Inhalation: Remove subject to ventilated fresh air. If not breathing, give artificial respiration right away. If breathing is difficult, give oxygen. Seek medical attention.
- 4.4 Ingestion: Seek medical advice, and attention if stomach continues to be upset.

#### 5. Fire Fighting Measures

- 5.1 Flammability: Combustible liquid under Hazard Communication Standard (HCS, U.S.A.)  
See Section 9 for Flash Point.
- 5.2 Extinguishing Media: Water spray, dry chemical, carbon dioxide or alcohol foam.
- 5.3 Fire Fighting Instructions: Extinguish to use fire fighting media or plentiful fog water. Put protection wear without fail in case of fire fighting work; do not work in the leeward.

#### 6. Accidental Release Measures

- 6.1 Personal protections: Remove the person of the leeward. Keep away the person from periphery of the place of the leakage. Ventilate sufficiently during clean-up in case of inside of a house.
- 6.2 Methods for cleaning up: If a spill occurs, use sponges to wipe-up ink, then rinse area with damp cloth. Place waste in closed container for disposal. Do not dispose of waste to the sewer. Wash hands with soap and water.

#### 7. Precautions for Safe Handling and Use

- 7.1 Handling: Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink ink. Do not dismantle cartridge is dry before insertion into printer housing.
- 7.2 Storage: Do not store the cartridges in high or freezing temperatures. Keep cartridge out of direct sunlight. Do not store cartridges with oxidizing agents or explosives.
- 7.3 Specific use(s): Not specified.



## 8. Exposure Controls and Personal Protection

8.1 Engineering controls: Close system or local ventilation is recommended.

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

Substance(s)	EU: ELV	ACGIH: TLV	OSHA: PEL
Ethylene glycol mono- butyl ether acetate	Not listed	20ppm	Not listed
N-Methyl pyrrolidone	Not Listed	Not Listed	Not listed

- 8.2.1.1 Respiratory protection Not required suitable use as setting the cartridge on the printer; however, self-contained breathing apparatus or organic canister mask is sufficient when used for work.
- 8.2.1.2. Hand protection Not required under suitable use as setting the cartridge on the printer; however, wearing gloves is sufficient.
- 8.2.1.3 Eye protection Not required under suitable use as setting the cartridge on the printer; however, wearing safety goggles is sufficient.
- 8.2.1.4 Skin protection Not required under suitable use as setting the cartridge on the printer; however, wearing gloves is sufficient.
- 8.2.2 Environmental exposure control Not established.

## 9. Physical and Chemical Properties of Ink Formulation

### 9.1 General information

Appearance Yellow liquid  
Odor Solvent odor

### 9.2 Important health, safety and environmental information

pH: No data available  
Boiling point: 191 deg.C (Ethylene glycol mono butyl ether acetate)  
Melting point: -64.6 deg.C (Ethylene glycol mono butyl ether acetate)  
Flash point: 83 deg.C (Cleveland Open cup)  
Autoflammability: No data available  
Explosive properties: explosive limit -lower limits 0.8vol%(Ethylene glycol mono butyl ether acetate)  
-upper limits 8.5vol%(Ethylene glycol mono butyl ether acetate)  
Oxidizing properties: No data available  
Vapor Pressure: 40Pa @ 20deg.C (Ethylene glycol mono butyl ether acetate)  
Vapor density: 3.4(N-Methyl pyrrolidone) (Air=1)  
Specific gravity: 0.96 - 1.00g/cm<sup>3</sup> @ 25deg.C  
Solubility in Water: 1.1wt% @ 20deg.C (Ethylene glycol mono butyl ether acetate)  
Easily soluble (N-Methyl pyrrolidone)  
Solubility in fat: No data available  
Partition coefficient: No data available  
Viscosity: No data available

9.3 Other information Not specified



**12. Ecological Information**

- 12.1 Ecotoxicity: 1) Ethylene glycol mono- butyl ether acetate.  
No data available
- 2) N-Methyl pyrrolidone  
bluegill  $LC_{50}$ :832mg/l (22deg.C), bull trout  $LC_{50}$ :3048mg/l (22deg.C)
- 12.2 Mobility: No data available on the adverse effects of this ink on the environment
- 12.3 Persistence and degradability: Good
- 12.4 Bioaccumulative potential: No data available on the adverse effects of this ink on the environment
- 12.5 Other adverse effects: Disclosure of ink and abandonment have a possibility of affecting environment. Then, cautions are required for handling. It is necessary to cope with it so that especially a product or washing water may not flow to the ground, a river, and a drain.

**13. Disposal Considerations**

Disposal should be in accordance with federal, state, and local requirement.

**14. Transportation Information**

UN Class/UN Number: Not applicable

**15. Regulatory Considerations****US Regulation:**

TSCA Section 4(a) Final Test Rules Regulated

TSCA Section 8(a) Preliminary Assessment Information Rule (PAIR)

TSCA Section 8(a) Inventory Update Rule

TSCA Section 12(b) One-Time Export Notification Regulated

California Proposition 65

N-Methyl pyrrolidone

Not regulated

Ethylene glycol monobutyl ether acetate

N-Methyl pyrrolidone

N-Methyl pyrrolidone

Yellow Pigment

N-Methyl pyrrolidone

**EU Information**

Symbols and indication according to 1999/45/EC: Xn

**Wording of Risk and Safety Phrase:**

- R20/21 : Harmful by inhalation and in contact with skin.
- R36/38 : Irritating to eyes and skin.
- S24 : Avoid contact with skin.
- S41 : In case of fire and/or explosion do not breathe fumes.

 **Hazard: Xn**

**16. Other Information**

This "Material Safety Data Sheet" contains health, safety, and environmental information. It does not replace any precautionary language or use and disposal information which accompanies the product. The information contained herein is believed to be accurate at the time of precaution, but should only be used as a guide. It is subject to revision from time to time. SII Printek Inc does not warrant the completeness or accuracy of the information contained herein.