

MSDS# CP-RT

FUJIFILM SERICOL USA, INC.
 20 WEST 14TH AVENUE
 NORTH KANSAS CITY, MISSOURI 64116
 (816) 474-0650

HMIS RATINGS
 HEALTH-----*2
 FLAMMABILITY-----2
 REACTIVITY-----0

 * MATERIAL SAFETY DATA SHEET *

For screen printing inks as required under 29 CFR 1910.1200(g).

EMERGENCY PHONE NUMBER 816 587-8178
 PREPARER: CRAIG POGGENPOHL EHS MANAGER
 DATE OF PREPARATION 07/15/08/CP

REVISIONS:

SECTION I--PRODUCT IDENTIFICATION

PRODUCT CODE : CP-RT
 LABEL IDENTITY: CORROPLAS RETARDER
 PRODUCT CLASS : SCREEN INK REDUCER

SECTION II--HAZARDOUS INGREDIENTS

COMMON NAME (CAS REGISTRY #)	PERCENT BY WEIGHT	RECOMMENDED EXPOSURE LIMITS (PPM) ¹ ACGIH TLV-TWA OSHA PEL	VAPOR PRESSURE (mm Hg @ 20 C) ¹
SOLVENT NAPHTHA HVY AROM (64742-94-5)	TO 100	100 ²	0.5
NAPHTHALENE (91-20-3)	10	10 ³ (STEL 15)	0.5
1,2,4-TRIMETHYLBENZENE (95-63-6)	2	25	0.5

NA - NOT APPLICABLE NE - NOT ESTABLISHED UKN - UNKNOWN

¹ UNLESS NOTED OTHERWISE, THE UNITS ARE PPM AND mm Hg @ 20 C, RESPECTIVELY, FOR EXPOSURE LIMITS AND VAPOR PRESSURES.

² RECOMMENDED BY MANUFACTURER.

³ SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL ABSORPTION OF THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV AND/OR PEL ARE NOT INVALIDATED.

SECTION III -- PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING RANGE: 350-380 DEG.F.
 DENSITY: 7.47 LB./GAL.
 VOC CONTENT OF MATERIAL: 100% OR 896 GRAMS PER LITER.
 VOC CONTENT OF COATINGS LESS WATER AND LESS EXEMPT SOLVENTS: 896 G/L.
 SOLUBILITY IN WATER: < 5%
 VAPOR DENSITY IS HEAVIER THAN AIR.
 EVAPORATION RATE: SLOWER THAN DIETHYL ETHER.
 APPEARANCE AND ODOR: CLEAR, MOBILE LIQUID. AROMATIC ODOR.

SECTION IV -- PHYSICAL HAZARD DATA

MSDS# CP-RT

FLAMMABILITY CLASSIFICATIONS: OSHA: CLASS IIIA DOT: COMBUSTIBLE LIQUID.
CLOSED CUP FLASH POINT: 145 F. EXPLOSIVE LIMITS: LOWER: 0.8 UPPER: 7.0

EXTINGUISHING MEDIA: "CLASS B" FIRE EXTINGUISHERS USED IN ACCORDANCE
WITH MANUFACTURERS INSTRUCTIONS.

"ALCOHOL" FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE OR EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED.
ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAMES.
CLOSED CONTAINERS MAY RUPTURE OR EXPLODE WHEN EXPOSED TO EXTREME HEAT.
APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.
DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY
CONSTITUTE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.
OBTAIN MEDICAL ATTENTION.

SPECIAL FIREFIGHTING PROCEDURES: FULL PROTECTIVE EQUIPMENT IS
RECOMMENDED TO PROTECT FIRE FIGHTERS FROM ANY HAZARDOUS DECOMPOSITION
PRODUCTS.

WATER MAY BE UNSUITABLE FOR USE ON BURNING LIQUIDS. IF WATER MUST BE
USED, FOG NOZZLES ARE HIGHLY PREFERABLE. WATER MAY BE USED TO COOL
CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-
IGNITION, EXPLOSION, OR RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====
SECTION V -- EMERGENCY AND FIRST-AID PROCEDURES
=====

PRIMARY ROUTES OF ENTRY ARE DERMAL AND INHALATION.

FOR SWALLOWING: DRINK TWO GLASSES OF WATER TO DILUTE. DO NOT INDUCE
VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CONSULT
PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. BE
PREPARED TO PROVIDE THE ATTENDING PHYSICIAN WITH A COPY OF THIS DOCUMENT.

FOR SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH
MILD SOAP AND WARM WATER. CONSULT A PHYSICIAN IF THERE IS ANY
PERSISTING IRRITATION.

FOR INHALATION: REMOVE VICTIM TO A WELL VENTILATED AREA. GIVE OXYGEN
OR ARTIFICIAL RESPIRATION AS REQUIRED. TREAT SYMPTOMATICALLY AND
CONSULT PHYSICIAN.

FOR EYE CONTACT: FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST
FIFTEEN MINUTES. CONSULT PHYSICIAN FOR MEDICAL TREATMENT, IF NECESSARY.

SPECIAL NOTES TO ATTENDING PHYSICIAN: THERE IS NO SPECIFIC ANTIDOTE.
TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT CONTROL OF THE SYMPTOMS
AND THE CLINICAL CONDITION.

=====
SECTION VI -- SIGNS AND SYMPTOMS OF OVEREXPOSURE
=====

ACUTE EFFECTS:

SWALLOWING: MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT. SIGNS OF NERVOUS
SYSTEM DEPRESSION (E.G., DROWSINESS, DIZZINESS, LOSS OF COORDINATION, AND
FATIGUE). ASPIRATION HAZARD - THIS MATERIAL CAN ENTER LUNGS DURING
SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION AND DAMAGE.

SKIN ABSORPTION: PROLONGED OR WIDESPREAD CONTACT WITH SKIN MAY LEAD TO
ABSORPTION OF HARMFUL AMMOUNTS OF MATERIAL WITH ACCOMPANYING SIGNS AND
SYMPTOMS OF TOXICITY AS DESCRIBED FOR SWALLOWING.

INHALATION: MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT. SIGNS OF
NERVOUS SYSTEM DEPRESSION (E.G., HEADACHE, DROWSINESS, DIZZINESS, LOSS OF
COORDINATION, AND FATIGUE). RESPIRATORY SYMPTOMS ASSOCIATED WITH PRE-

MSDS# CP-RT

EXISTING LUNG DISORDERS (E.G., ASTHMA-LIKE CONDITIONS) MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

SKIN CONTACT: PROLONGED OR REPEATED CONTACT WITH SKIN MAY LEAD TO MODERATE IRRITATION, DEFATTING, AND DERMATITIS.

EYE CONTACT: CAN CAUSE PAINFUL STINGING OF EYES AND LIDS, TEARING, REDNESS, AND SWELLING.

MEDICAL CONDITIONS KNOWN TO BE AGGRAVATED BY OVEREXPOSURE: RESPIRATORY SYMPTOMS ASSOCIATED WITH PRE-EXISTING LUNG DISORDERS (E.G., ASTHMA-LIKE CONDITIONS). DERMATITIS.

CHRONIC EFFECTS: IN RAT AND MICE LIFETIME INHALATION STUDIES, NAPHTHALENE INCREASED NOSE AND LUNG TUMORS.

ADDITIONAL KNOWN HEALTH HAZARDS:
REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=====
SECTION VII -- REACTIVITY DATA
=====

THIS MIXTURE IS STABLE AND HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG ACIDS, STRONG BASES, STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, VARIOUS HYDROCARBONS, ETC.

CONDITIONS TO AVOID: EXTREME TEMPERATURES, SPARKS, OPEN FLAMES, STATIC ELECTRICITY OR ANY OTHER POSSIBLE IGNITION SOURCES.

=====
SECTION VIII -- SPILL OR LEAK PROCEDURES
=====

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: USING NON-SPARKING TOOLS, PLACE LEAKING CONTAINERS IN A WELL VENTILATED AREA. AVOID BREATHING VAPORS.

ELIMINATE ALL SOURCES OF HEAT, SPARKS, OR IGNITION.
NOTIFY PROPER AUTHORITIES IF PUBLIC WATERS OR SEWERS ARE CONTAMINATED.

WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL ORDINANCES. INQUIRE OF YOUR LOCAL ENVIRONMENTAL AGENCIES FOR THE EXACT LEGAL REQUIREMENTS IN YOUR AREA. REFER TO SECTIONS IV, V, VI, VII, AND IX OF THIS DOCUMENT BEFORE ATTEMPTING ANY CLEANUP.

=====
SECTION IX -- SAFE HANDLING AND USE INFORMATION
=====

RESPIRATORY PROTECTION: WHERE CONCENTRATIONS IN AIR MAY EXCEED THE LIMITS GIVEN IN SECTION II AND ENGINEERING, WORK PRACTICE OR OTHER MEANS OF EXPOSURE REDUCTION ARE NOT ADEQUATE, NIOSH/MSHA APPROVED RESPIRATORS MAY BE NECESSARY TO PREVENT OVEREXPOSURE.

VENTILATION REQUIREMENTS: LOCAL EXHAUST RECOMMENDED WHEN APPROPRIATE TO CONTROL EXPOSURE TO MIST OR AEROSOLS. GENERAL EXHAUST IS NORMALLY ADEQUATE TO MINIMIZE EXPOSURE TO VAPORS.

PROTECTIVE GLOVES: RUBBER OR NEOPRENE TO MINIMIZE SKIN CONTACT.

EYE PROTECTION: SAFETY GOGGLES OR FULL FACE SHIELD.

HYGIENIC SAFETY PRACTICES: WASH HANDS BEFORE EATING, USING TOBACCO PRODUCTS, OR USING THE WASHROOM. TOBACCO AND FOOD SHOULD BE CONSUMED IN

MSDS# CP-RT

DESIGNATED AREAS ONLY.

ADDITIONAL SAFETY EQUIPMENT: IMPERMEABLE APRONS AND BOOTS. SAFETY SHOWER AND EYE BATH SHOULD BE MADE AVAILABLE.

SECTION X -- SPECIAL PROCEDURES

TRANSPORTATION, STORAGE, AND HANDLING: AVOID CONDITIONS LISTED IN SECTION VII. AVOID PROLONGED STORAGE AT TEMPERATURES IN EXCESS OF 100 F.

OTHER PRECAUTIONS: NONE.

SECTION XI -- DISCLAIMER

SERICOL, INC. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ACCURACY OR RELIABILITY OF INFORMATION CONTAINED HEREIN, EXCEPT THAT SUCH INFORMATION IS, TO THE BEST OF SERICOLS' KNOWLEDGE AND BELIEF, ACCURATE AS OF THE DATE INDICATED ON THIS DOCUMENT. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SECTION XII -- PURCHASER'S OBLIGATIONS

SERICOL, INC. URGES THE CUSTOMER RECEIVING THIS MATERIAL SAFETY DATA SHEET TO STUDY IT CAREFULLY TO BECOME AWARE OF HAZARDS, IF ANY, OF THE PRODUCTS INVOLVED. IN THE INTEREST OF SAFETY, YOU SHOULD (1) NOTIFY YOUR EMPLOYEES, AGENTS, AND CONTRACTORS OF THE INFORMATION ON THIS SHEET, (2) FURNISH A COPY TO EACH OF YOUR CUSTOMERS FOR THIS PRODUCT, AND (3) REQUEST YOUR CUSTOMERS TO INFORM THEIR EMPLOYEES, CUSTOMERS, AND AGENTS, AS WELL.

SECTION XIII -- REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS: THE INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

THIS PRODUCT CONTAINS A TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE ANNUAL REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

CONTAINS: NAPHTHALENE
CAS# 91-20-3
10% BY WEIGHT.

1,2,4-TRIMETHYLBENZENE
CAS# 95-63-6,
2% BY WEIGHT.

THIS NOTIFICATION MUST NOT BE DETACHED FROM THE MATERIAL SAFETY DATA SHEET (MSDS) AND ANY COPYING AND REDISTRIBUTION OF THE MSDS SHALL INCLUDE COPYING AND REDISTRIBUTION OF THE NOTICE ATTACHED TO COPIES OF THE MSDS SUBSEQUENTLY REDISTRIBUTED.

STATE OF CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65): THIS PRODUCT CONTAINS NAPHTHALENE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

STATE OF CALIFORNIA: THIS PRODUCT IS CONSIDERED "PHOTOCHEMICALLY REACTIVE" BY DEFINITION OF RULE 102 OF THE SOUTH COAST AIR QUALITY

MANAGEMENT DISTRICT.