

MSDS# CP-TH

* MATERIAL SAFETY DATA SHEET *

For screen printing inks as required under 29 CFR 1910.1200(g).

FUJIFILM SERICOL USA, INC.
20 WEST 14TH AVENUE
NORTH KANSAS CITY, MISSOURI 64116
(816) 474-0650

HMIS RATINGS
HEALTH-----1
FLAMMABILITY-----2
REACTIVITY-----0

EMERGENCY PHONE NUMBER PREPARER: CRAIG POGGENPOHL DATE OF PREPARATION
(816) 587-8178 EHS MANAGER REVISED 04/18/08/CP

REVISIONS: SECTION XIII.

SECTION I--PRODUCT IDENTIFICATION

PRODUCT CODE: CP-TH
PRODUCT NAME: CORROPLAS THINNER
PRODUCT CLASS: SCREEN PRINTING INK REDUCER

SECTION II--HAZARDOUS INGREDIENTS

Table with 4 columns: COMMON NAME (CAS REGISTRY #), PERCENT BY WEIGHT, RECOMMENDED EXPOSURE LIMITS (PPM) (ACGIH TLV-TWA OSHA PEL), and VAPOR PRESSURE (MM HG @ 20 C). Rows include CUMENE, TRIMETHYLBENZENES, XYLENE, and PETROLEUM DISTILLATE.

NA - NOT APPLICABLE

NE - NOT ESTABLISHED

UKN - UNKNOWN

1 UNLESS NOTED OTHERWISE, THE UNITS ARE PPM AND mm hg @ 20 C, RESPECTIVELY, FOR EXPOSURE LIMITS AND VAPOR PRESSURES.

2 RECOMMENDED BY MANUFACTURER.

3 SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL ABSORPTION OF THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV AND/OR PEL ARE NOT INVALIDATED.

SECTION III -- PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING RANGE: 308-335 DEG. F @ 760 MM/HG.
DENSITY: 7.29 LB./GAL.
VOC CONTENT OF MATERIAL: 100% BY WEIGHT OR 875 GRAMS PER LITER.
VOC CONTENT OF COATING LESS WATER AND LESS EXEMPT SOLVENTS: 875 G/L.
SOLUBILITY IN WATER: SLIGHT
EVAPORATION RATE (ETHER=1): 25
VAPOR DENSITY (AIR=1): 4.15
APPEARANCE AND ODOR: CLEAR LIQUID, HYDROCARBON ODOR.

SECTION IV -- PHYSICAL HAZARD DATA

MSDS# CP-TH

FLAMMABILITY CLASSIFICATIONS: OSHA: CLASS II DOT: COMBUSTIBLE LIQUID
TAG CLOSED CUP FLASH POINT: 110 DEG. F.
EXPLOSIVE LIMITS: LOWER(% VOLUME): 1.0 UPPER(% VOLUME): 7.0.

EXTINGUISHING MEDIA: "CLASS B" FIRE EXTINGUISHERS USED IN ACCORDANCE
WITH MANUFACTURERS INSTRUCTIONS.

"ALCOHOL" FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE OR EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED.
ISOLATE FROM HEAT, SPARKS, AND OPEN FLAMES. CLOSED CONTAINERS MAY
RUPTURE WHEN EXPOSED TO EXTREME HEAT. WATER MAY BE USED TO COOL
UNRUPTURED CONTAINERS.

DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CONSTITUTE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY
APPARENT. OBTAIN MEDICAL ATTENTION.

SPECIAL FIREFIGHTING PROCEDURES: WATER MAY BE UNSUITABLE FOR USE ON
BURNING LIQUIDS. FULL PROTECTIVE EQUIPMENT IS RECOMMENDED TO PROTECT
FIRE FIGHTERS FROM ANY HAZARDOUS DECOMPOSITION PRODUCTS.
WATER SPRAY MAY BE INEFFECTIVE. IF WATER MUST BE USED, FOG NOZZLES ARE
HIGHLY PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO
PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN
EXPOSED TO EXTREME HEAT.

=====
SECTION V -- EMERGENCY AND FIRST-AID PROCEDURES
=====

PRIMARY ROUTES OF ENTRY ARE DERMAL AND INHALATION.

SWALLOWING: DO NOT INDUCE VOMITING. THIS MATERIAL IS AN ASPIRATION
HAZARD. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, PLACE ON LEFT SIDE
WITH THE HEAD DOWN. SEEK MEDICAL ATTENTION. IF POSSIBLE, DO NOT LEAVE
INDIVIDUAL UNATTENDED.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH MILD
SOAP AND WARM WATER. CONSULT A PHYSICIAN IF THERE IS ANY PERSISTING
IRRITATION.

INHALATION: IF RESPIRATORY SYMPTOMS OR OTHER SYMPTOMS OF EXPOSURE DEVELOP,
MOVE VICTIM AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF SYMPTOMS
PERSIST, SEEK IMMEDIATE MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING,
ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED. IF BREATHING DIFFICULTIES
DEVELOP, OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SEEK
IMMEDIATE MEDICAL ATTENTION.

EYE CONTACT: MOVE VICTIM AWAY FROM EXPOSURE TO VAPORS AND INTO FRESH AIR.
IF IRRITATION OR REDNESS DEVELOPS, SEEK MEDICAL ATTENTION. FOR DIRECT
CONTACT, HOLD EYELIDS APART AND FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER
FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

SPECIAL NOTES TO ATTENDING PHYSICIAN: THERE IS NO SPECIFIC ANTIDOTE.
TREATMENT OF OVEREXPOSURE SHOULD BE DIRECTED AT CONTROL OF THE SYMPTOMS
AND THE CLINICAL CONDITION.

=====
SECTION VI -- SIGNS AND SYMPTOMS OF OVEREXPOSURE
=====

ACUTE EFFECTS:

SWALLOWING: THIS MATERIAL HAS A LOW DEGREE OF TOXICITY. INGESTION OF
EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT AND SIGNS
OF NERVOUS SYSTEM DEPRESSION (E.G., DROWSINESS, DIZZINESS, LOSS OF
COORDINATION AND FATIGUE). ASPIRATION HAZARD - ONE OR MORE COMPONENTS OF
THIS MATERIAL CAN ENTER LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG

MSDS# CP-TH

INFLAMMATION AND DAMAGE.

SKIN ABSORPTION: CONTACT MAY RESULT IN SKIN ABSORPTION BUT SYMPTOMS OF TOXICITY ARE NOT ANTICIPATED BY THIS ROUTE ALONE UNDER NORMAL CONDITIONS OF USE. PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS MATERIAL.

INHALATION: THIS MATERIAL HAS A LOW DEGREE OF TOXICITY BY INHALATION. BREATHING HIGH CONCENTRATIONS OF VAPORS OR MISTS MAY CAUSE IRRITATION OF THE NOSE AND THROAT AND SIGNS OF NERVOUS SYSTEM DEPRESSION. RESPIRATORY SYMPTOMS ASSOCIATED WITH PRE-EXISTING LUNG DISORDERS (E.G., ASTHMA - LIKE CONDITIONS) MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

SKIN CONTACT: ONE OR MORE COMPONENTS OF THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DRYING AND CRACKING OF THE SKIN AND SKIN DAMAGE.

EYE CONTACT: ONE OR MORE COMPONENTS OF THIS MATERIAL IS AN EYE IRRITANT. DIRECT CONTACT WITH THE LIQUID OR EXPOSURE TO VAPORS OR MISTS MAY CAUSE STINGING, TEARING, REDNESS AND SWELLING.

CONDITIONS KNOWN TO BE AGGRAVATED BY OVEREXPOSURE: SKIN CONTACT AGGRAVATE AN EXISTING DERMATITIS.

CHRONIC EFFECTS: NONE KNOWN.

ADDITIONAL KNOWN HEALTH HAZARDS: REPORTS HAVE ASSOCIATED PROLONGED OR REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OF FATAL.

=====
SECTION VII -- REACTIVITY DATA
=====

THIS MIXTURE IS STABLE AND HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

CONDITIONS TO AVOID: EXTREME TEMPERATURES, SPARKS, OPEN FLAMES OR ANY OTHER IGNITION SOURCES.

=====
SECTION VIII -- SPILL OR LEAK PROCEDURES
=====

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED: USING NON-SPARKING TOOLS, PLACE LEAKING CONTAINERS IN A WELL VENTILATED AREA. ELIMINATE ALL SOURCES OF HEAT, SPARKS, OR IGNITION. NOTIFY PROPER AUTHORITIES IF PUBLIC WATERS OR SEWERS ARE CONTAMINATED. WEAR APPROPRIATE PROTECTIVE CLOTHING AND RESPIRATORY PROTECTION EQUIPMENT WHEN ENTERING THE SPILL AREA. SHUT OFF LEAK IF IT CAN BE DONE SAFELY. VENTILATE THE AREA. DIKE AND PUMP OFF LARGE SPILLS INTO SALVAGE OR STORAGE CONTAINERS. TAKE UP RESIDUE OR SMALL SPILLS WITH ABSORBENT MATERIAL SUCH AS CLAY OR VERMICULITE. SCOOP UP ALL CONTAMINATED SOIL AND DISPOSE OF IN SAME MANNER AS THE PRODUCT. WASTE DISPOSAL METHOD: AS A HAZARDOUS WASTE, THIS MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL ORDINANCES. INQUIRE OF YOUR LOCAL ENVIRONMENTAL AGENCIES FOR THE EXACT LEGAL REQUIREMENTS IN YOUR AREA. REFER TO SECTIONS IV, V, VI, VII AND IX OF THIS DOCUMENT BEFORE ATTEMPTING CLEANUP.

=====

MSDS# CP-TH

SECTION IX -- SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: WHERE CONCENTRATIONS IN AIR MAY EXCEED THE LIMITS GIVEN IN SECTION II AND ENGINEERING, WORK PRACTICE OR OTHER MEANS OF EXPOSURE REDUCTION ARE NOT ADEQUATE, NIOSH/MSHA APPROVED RESPIRATORS MAY BE NECESSARY TO PREVENT OVEREXPOSURE. VENTILATION REQUIREMENTS: LOCAL EXHAUST RECOMMENDED WHEN APPROPRIATE TO CONTROL EXPOSURE TO MIST OR AEROSOLS. GENERAL EXHAUST IS NORMALLY ADEQUATE TO MINIMIZE EXPOSURE TO VAPORS. PROTECTIVE GLOVES: RUBBER OR NEOPRENE TO MINIMIZE SKIN CONTACT. EYE PROTECTION: SAFETY GOGGLES OR FULL FACE SHIELD. HYGIENIC SAFETY PRACTICES: WASH HANDS BEFORE EATING, USING TOBACCO PRODUCTS, OR USING THE WASHROOM. TOBACCO AND FOOD SHOULD BE CONSUMED IN DESIGNATED AREAS ONLY. ADDITIONAL SAFETY EQUIPMENT: IMPERMEABLE APRONS AND BOOTS. SAFETY SHOWER AND EYE BATH SHOULD BE MADE AVAILABLE.

SECTION X -- SPECIAL PROCEDURES

TRANSPORTATION, STORAGE AND HANDLING: AVOID CONDITIONS LISTED IN SECTION VII. AVOID PROLONGED STORAGE AT TEMPERATURES IN EXCESS OF 100 F.

OTHER PRECAUTIONS: NONE.

SECTION XI -- DISCLAIMER

SERICOL, INC. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ACCURACY OR RELIABILITY OF INFORMATION CONTAINED HEREIN, EXCEPT THAT SUCH INFORMATION IS, TO THE BEST OF SERICOL'S KNOWLEDGE AND BELIEF, ACCURATE AS OF THE DATE INDICATED ON THIS DOCUMENT. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SECTION XII -- PURCHASER'S OBLIGATIONS

SERICOL, INC. URGES THE CUSTOMER RECEIVING THIS MATERIAL SAFETY DATA SHEET TO STUDY IT CAREFULLY TO BECOME AWARE OF HAZARDS, IF ANY, OF THE PRODUCTS INVOLVED. IN THE INTEREST OF SAFETY, YOU SHOULD (1) NOTIFY YOUR EMPLOYEES, AGENTS, AND CONTRACTORS OF THE INFORMATION ON THIS SHEET, (2) FURNISH A COPY TO EACH OF YOUR CUSTOMERS FOR THIS PRODUCT, AND (3) REQUEST YOUR CUSTOMERS TO INFORM THEIR EMPLOYEES, CUSTOMERS, AND AGENTS, AS WELL.

SECTION XIII -- REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS: THE INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

THIS PRODUCT CONTAINS A TOXIC CHEMICAL OR CHEMICALS SUBJECT TO THE ANNUAL REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

CONTAINS: 1,2,4-TRIMETHYLBENZENE, CAS# 95-63-6,
32% BY WEIGHT.

CUMENE, CAS# 98-82-8,
1.5% BY WEIGHT.

MSDS# CP-TH

XYLENE, CAS# 1330-20-7
3% BY WEIGHT.

THIS NOTIFICATION MUST NOT BE DETACHED FROM THE MATERIAL SAFETY DATA SHEET (MSDS) AND ANY COPYING AND REDISTRIBUTION OF THE MSDS SHALL INCLUDE COPYING AND REDISTRIBUTION OF THE NOTICE ATTACHED TO COPIES OF THE MSDS SUBSEQUENTLY REDISTRIBUTED.

STATE OF CALIFORNIA:

THIS PRODUCT IS CONSIDERED "PHOTOCHEMICALLY REACTIVE" BY DEFINITION OF RULE 102 OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT.

STATE OF CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65): THIS PRODUCT MAY CONTAIN TRACE QUANTITIES OF BENZENE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. MAY CONTAIN TRACE QUANTITIES OF TOLUENE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE REPRODUCTIVE TOXICITY.