



MATERIAL SAFETY DATA SHEET

For Spraylat Liquid Coatings and Associated Liquid Materials

1701 East 122nd Street
Chicago, IL 60633
(773) 646-5900
Fax: (773) 646-3743

716 South Columbus Avenue
Mount Vernon, NY 10550
(914) 699-3030
Fax: (914) 699-3035

3465 South La Cienega Blvd.
Los Angeles, CA 90016
(310) 559-2335
Fax: (310) 836-6094

3333 North Interstate 35
Gainesville, TX 76240
(940) 665-9590
Fax: (940) 665-8867

e-mail HSEcoordinator@Spraylat.com

PREPARED BY : Health, Safety and Environmental Coordinator

EMERGENCY PHONE:

1-800-424-9300

Chemtrec

INTERNATIONAL TRANSPORTATION ACCIDENTS:

1-703-527-3887

Chemtrec

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name : **20/30-185 PART A PRIMER SURFACER ACTIVATOR**

Date Printed : 01/03/03

Revision Date : 10/18/02

Revision Number : 1

Perceces : None

II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
Ethanol	64-17-5	40.01 - 50.00
n-Butyl alcohol	71-36-3	15.01 - 20.00
Toluene	108-88-3	15.01 - 20.00
Xylene	1330-20-7	5.01 - 10.00
Isopropanol	67-63-0	1.01 - 5.00
Methanol	67-56-1	1.01 - 5.00
Ethylbenzene	100-41-4	1.01 - 5.00

If ingredient percentages do not total 100%, the balance is due to rounding or applies to ingredient(s) deemed nonhazardous under 29 CFR 1910.1200 (Hazard Communication Standard).

III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2 *
FLAMMABILITY	3
REACTIVITY	0

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme * = Chronic Health Effects

Routes of Entry:

Inhalation, Ingestion, Skin contact, Eye contact, Absorption.

Medical Conditions Aggravated:

Liver disease, Skin disease including eczema and sensitization, Eye disease, Skin allergies, Kidney disease, Digestive tract disease, Lung disease.

Immediate (Acute) Health Effects:

Inhalation:

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful if inhaled. Harmful. Can cause systemic damage, see target organs below.

Contact:

Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact:

Irritating and may injure eye tissue if not removed promptly.

Skin Absorption: May cause irritation and minor systemic damage. Harmful if absorbed through the skin. Contains Methanol. May cause deterioration of the optic nerve if absorbed through the skin in large amounts.

Ingestion: Toxic if swallowed. May cause target organ failure and/or death. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

Target Organ Acute Toxicity: Eyes, Liver, Skin, Respiratory System, Blood, Reproductive System, Heart, Kidneys, Digestive Tract, Nervous System, Thyroid, Pituitary, Testes.

Long-Term (Chronic) Health Effects:

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Repeated or prolonged inhalation may cause toxic effects.

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact: Upon prolonged or repeated contact, can cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage. Contains methanol. Upon prolonged or repeated exposure, may cause deterioration of the optic nerve if large quantities are absorbed through the skin. Repeated absorption of large quantities may lead to blindness.

Carcinogenicity: IARC: Yes NTP: No OSHA: No

Target Organ Chronic Toxicity: Respiratory System, Nervous System, Eyes, Blood, Liver, Skin, Heart, Kidneys, Digestive Tract, Pituitary, Testes.

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney, lung and liver tumors. Testicular adenomas were increased as were thyroid effects in rats at 750 ppm. Pituitary effects were observed in female mice at 250 ppm. These effects were absent when exposure was below 75 ppm ethylbenzene. The study does not address the relevance of these results to humans.

IV. FIRST AID

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Eyes: Immediately flush eyes with plenty of luke warm water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

Skin Contact: Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.

Ingestion: Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

Notes to M.D. Acute massive exposure to toluene can cause transient hematuria and albuminuria. Cardiac arrhythmias can occur after massive inhalation.

FIRE FIGHTING MEASURES

Flammability Summary:

Flash Point: Highly Flammable 4 °C; 39 °F

Autoignition Temperature: 343 °C; 649 °F
 Autoignition Temperature:
 Lower Flammable/Explosive Limit, % in air: 1.1 Upper Flammable/Explosive Limit, % in air: 19.0

Fire Hazards: Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Container may explode in heat of fire. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire Fighting Instructions: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Even if material is water soluble, may not be practical to extinguish fire by water dilution. Do not point solid water stream directly into burning oil to avoid spreading. Use methods for the surrounding fire.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide.

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, and the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Spill Mitigation Procedures:

General Methods: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Air Release: Ventilate the area by opening door and/or turning on fans and blowers.

Water Release: Avoid runoff into storm sewers and ditches that lead to waterways. If runoff occurs, notify proper authorities as required, that a spill has occurred.

Land Spills: Do not flush to sewer.

VII. HANDLING AND STORAGE

Handling: Harmful or irritating; avoid overexposure to the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment.

Storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Keep away from sources of ignition. Store in a tightly closed container. Do not store near combustible materials.

VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT, AND EXPOSURE LIMITS

Engineering Controls: Local exhaust ventilation, process enclosures, or other engineering controls are important when handling or using this product to avoid overexposure. Engineering controls must be designed to meet any relevant OSHA chemical specific standards in 29 CFR 1910. Facilities storing or using this material should be equipped with an eyewash and safety shower.

Protective Equipment:

Respiratory Tract: If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

Eyes:

Wear safety glasses with side shields when handling this product. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield. Do not wear contact lenses. Have an eye wash station available.

1:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Do not wear surgical style latex gloves except to protect against incidental contact with the material. Use impervious gloves.

Protective Clothing:

Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
Ethanol	64-17-5	1000 ppm TWA	1000 ppm TWA; 1900 mg/m ³ TWA	3300 ppm IDLH (10 percent lower explosive limit)
n-Butyl alcohol	71-36-3	No TLV (C 50 ppm)	100 ppm TWA; 300 mg/m ³ TWA	1400 ppm IDLH (10 percent lower explosive limit)
Toluene	108-88-3	50 ppm TWA	200 ppm TWA C 300 ppm	Not determined.
Xylene	1330-20-7	100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m ³ TWA	900 ppm IDLH
Isopropanol	67-63-0	(400) ppm TWA; (983) mg/m ³ TWA (500) ppm STEL	400 ppm TWA; 980 mg/m ³ TWA	2000 ppm IDLH (10 percent lower explosive limit)
Methanol	67-56-1	200 ppm TWA 250 ppm STEL	200 ppm TWA; 260 mg/m ³ TWA	6000 ppm IDLH
Ethylbenzene	100-41-4	100 ppm TWA 125 ppm STEL	100 ppm TWA; 435 mg/m ³ TWA	800 ppm IDLH (10 percent lower explosive limit)

PHYSICAL DATA

Appearance:	Colorless Liquid.
Color:	Colorless
Odor:	Hydrocarbon Aromatic
pH:	N/A
Octanol/Water Coeff:	Not Determined.
Solubility in Water:	Partial.
Vapor Density:	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Evaporation Rate:	Slower than n-Butyl Acetate.
Specific Gravity/Density:	0.83 / 6.93 Lbs./G1.
V.O.C.	6.9 Lbs/G1 less water & exempt solvent; 828 g/l less water & exempt solvent; 6.6 Lbs/G1 as packed

The VOC content is determined by using a percent solids basis, less water and exempt solvents, for adhesives, coatings and inks and the calculations of EPA Reference Method 24 or equivalent ASTM method approved by the executive office.

Initial Boiling Point:	78 °C;	172 °F
Initial Freezing Point:	N/A	

X. STABILITY AND REACTIVITY

Stability Information:	Stable under normal conditions.
Conditions to Avoid:	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.,
Chemical Incompatibility:	Strong oxidizing agents, Strong acids.
Hazardous Decomposition Products:	Carbon dioxide, Carbon monoxide.

XI. TOXICOLOGICAL INFORMATION

Chemical Name	LD50/LC50
F ⁿ -butyl alcohol	Inhalation LC50 Rat : 20000 ppm/10H; Inhalation LC50 Mouse : 39 gm/m ³ /4H; Oral LD50 Rat : 7060 mg/kg; Oral LD50 Mouse : 3450 mg/kg
Butyl alcohol	Inhalation LC50 Rat : 8000 ppm/4H; Oral LD50 Rat : 790 mg/kg; Oral LD50 Mouse : 2680 mg/kg; Dermal LD50 Rabbit : 3400 mg/kg
Toluene	Inhalation LC50 Mouse : 5320 ppm/8H; Oral LD50 Rat : 5000 mg/kg; Dermal LD50 Rabbit : 14 g/kg
Xylene	Inhalation LC50 Rat : 5000 ppm/4H; Oral LD50 Rat : 4300 mg/kg; Dermal LD50 Rabbit : >1700 mg/kg

Isopropyl alcohol	Inhalation LC50 Rat : 16000 ppm/8H; Oral LD50 Rat : 5045 mg/kg; Oral LD50 Mouse : 3600 mg/kg; Dermal LD50 Rabbit : 12800 mg/kg
Methanol	Inhalation LC50 Rat : 64000 ppm/4H; Oral LD50 Rat : 5628 mg/kg; Oral LD50 Mouse : 7300 mg/kg; Dermal LD50 Rabbit : 15800 mg/kg
Benzene, ethyl-	Oral LD50 Rat : 3500 mg/kg; Dermal LD50 Rabbit : 17800 uL/kg

ECOLOGICAL INFORMATION

Overview:

Care should be taken to minimize releases of any industrial chemicals to the environment.

XIII. DISPOSAL CONSIDERATIONS

Waste Description for Spent Product:

Spent or discarded material is a hazardous waste.

Disposal Methods:

Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and clean-up materials in accordance with all federal, state, and local environmental regulations.

Potential EPA Waste Codes:

D001, .

Some Components Possibly Subjected to USEPA Land Disposal Restrictions:

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories.

n-Butyl alcohol	71-36-3
Toluene	108-88-3
Xylenes (o-, m-, p- isomers)	1330-20-7
Methanol	67-56-1
Ethyl benzene	100-41-4

XIV. TRANSPORTATION INFORMATION

Agency Basic Description and Label

DOT Paint, 3, UN1263, PG II; Label Required: Flammable Liquid.

Hazardous Substance

Butanol	final RQ = 5000 pounds (2270 kg); also listed as n-Butyl alcohol
Toluene	final RQ = 1000 pounds (454 kg); also listed as Benzene, methyl-
Xylenes (isomers and mixture)	final RQ = 100 pounds (45.4 kg); also listed as Xylene; also listed as Xylene (mixed); also listed as Benzene, dimethyl-
Methanol	final RQ = 5000 pounds (2270 kg); also listed as Methyl alcohol
Ethyl benzene	final RQ = 1000 pounds (454 kg)

XV. REGULATORY INFORMATION

ulation

SARA 313 Reportable : n-Butyl alcohol, Toluene, Xylene (mixed isomers), ., Methanol, Ethyl benzene

TSCA Inventory : All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.

M.S.D.S. Reportable HAP(s) : Toluene, Xylenes (isomers and mixture), Methanol, Ethyl benzene.

California Proposition 65 : The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65: "WARNING: This product contains chemical(s) known to the State of California to cause birth defects."

XVI. ADDITIONAL INFORMATION

Major References: VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.