



MATERIAL SAFETY DATA SHEET

For Spraylat Liquid Coatings and Associated Liquid Materials

1701 East 122nd Street
Chicago, IL 60633
(773) 646-5900
Fax: (773) 646-3743

716 South Columbus Avenue
Mount Vernon, NY 10550
(914) 699-3030
Fax: (914) 699-3035

3465 South La Cienega Blvd.
Los Angeles, CA 90016
(310) 559-2335
Fax: (310) 836-6094

3333 North Interstate 35
Gainesville, TX 76240
(940) 665-9590
Fax: (940) 665-8867

e-mail HSEcoordinator@Spraylat.com

PREPARED BY : Health, Safety and Environmental Coordinator

EMERGENCY PHONE:

1-800-424-9300

Chemtrec

INTERNATIONAL TRANSPORTATION ACCIDENTS:

1-703-527-3887

Chemtrec

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name : FM100 Field Master Gloss Modifier

Date Printed : 07/06/09
Revision Date : 09/09/08

Revision Number : 1
Supersedes : None

II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
p-Chlorobenzotrifluoride	98-56-6	20.01 - 25.00
Stoddard solvent	8052-41-3	20.01 - 25.00
Amorphous silica, silicon dioxide	112926-00-8	15.01 - 20.00
Xylene	1330-20-7	1.01 - 5.00
1,2,4-Trimethylbenzene	95-63-6	0.10 - 1.00
1,3,5-Trimethylbenzene	108-67-8	0.10 - 1.00
Ethylbenzene	100-41-4	0.10 - 1.00

If ingredient percentages do not total 100%, the balance is due to rounding or applies to ingredient(s) deemed nonhazardous under 29 CFR 1910.1200 (Hazard Communication Standard).

III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2 *
FLAMMABILITY	2
REACTIVITY	0

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme * = Chronic Health Effects

Routes of Entry:

Skin contact, Eye contact, Inhalation, Absorption.

Medical Conditions Aggravated:

Eye disease, Skin disease including eczema and sensitization, Kidney disease, Lung disease, Liver disease, Digestive tract disease.

Immediate (Acute) Health Effects:

Inhalation:

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Skin Contact:

Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact:

Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption:

Harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Ingestion:

Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide.

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, and the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Spill Mitigation Procedures:

General Methods:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. For liquid spills, dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Air Release:

Ventilate the area by opening door and/or turning on fans and blowers.

Water Release:

Retain all contaminated water for treatment.

Land Spills:

Avoid runoff into storm sewers and ditches that lead to waterways.

VII. HANDLING AND STORAGE

Handling:

Harmful or irritating; avoid overexposure to the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment.

Storage:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Keep away from sources of ignition.

VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT, AND EXPOSURE LIMITS

Engineering Controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. See table at the end of this Section VIII below for exposure limits.

Protective Equipment:

Respiratory Tract:

If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

Eyes:

Wear safety glasses with side shields when handling this product. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield. Do not wear contact lenses. Have an eye wash station available.

Skin:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Protective Clothing:

Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
p-Chlorobenzotrifluoride	98-56-6	No TLV	No PEL established	Not determined.
Stoddard solvent	8052-41-3	100 ppm TWA	500 ppm TWA; 2900 mg/m ³ TWA	20000 mg/m ³ IDLH
Amorphous silica, silicon dioxide	112926-00-8	10 mg/m ³ TWA	No PEL established	Not determined.
Xylene	1330-20-7	100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m ³ TWA	900 ppm IDLH
1,2,4-Trimethylbenzene	95-63-6	No TLV	No PEL established	Not determined.
1,3,5-Trimethylbenzene	108-67-8	No TLV	No PEL established	Not determined.
Ethylbenzene	100-41-4	100 ppm TWA 125 ppm STEL	100 ppm TWA; 435 mg/m ³ TWA	800 ppm IDLH

XVI. ADDITIONAL INFORMATION

Major References: VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION OR USE, INCLUDING USE OF THIS MATERIAL IN COMBINATION WITH OTHER MATERIALS OR PROCESSES. YOU THEREFORE SHOULD, AND THIS MATERIAL IS SUPPLIED ON THE CONDITION THAT YOU, PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF THE MATERIAL PRIOR TO USE, AND YOU ACCEPT RESPONSIBILITY FOR SATISFYING YOURSELF THAT THE MATERIAL IS SUITABLE AND THE COMPLETENESS OF THIS INFORMATION IS SUFFICIENT FOR YOUR USE. ALTHOUGH CERTAIN HAZARDS MAY BE DESCRIBED HEREIN, OTHER HAZARDS MAY ALSO EXIST. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA, OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, AND WE DISCLAIM LIABILITY FOR LOSS OR INJURY ARISING FROM YOUR USE OF THIS MATERIAL, DATA OR INFORMATION. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.