



MATERIAL SAFETY DATA SHEET

For 1 Shot/Chromatic Liquid Coatings and Associated Liquid Materials

One Shot, LLC

A Spraylat Company
5300 W. 5th Avenue
Gary, IN 46406
(219) 949-1684
Fax: (219) 949-1612

e-mail HSECoordinator@Spraylat.com

PREPARED BY : Health, Safety and Environmental Coordinator

EMERGENCY PHONE:	1-800-424-9300	Chemtrec
INTERNATIONAL TRANSPORTATION ACCIDENTS:	1-703-527-3887	Chemtrec

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name : **SPEED DRY UV ACRYLIC CLEAR SATIN (4015)**

Date Printed :	10/02/07	Revision Number :	4
Revision Date :	10/02/07	Supercedes :	10/02/07

II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	40.01 - 50.00
Methoxypropanol acetate	108-65-6	15.01 - 20.00
Fumed silica	112945-52-5	1.01 - 5.00

If ingredient percentages do not total 100%, the balance is due to rounding or applies to ingredient(s) deemed nonhazardous under 29 CFR 1910.1200 (Hazard Communication Standard).

III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2
FLAMMABILITY	2
REACTIVITY	0

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme * = Chronic Health Effects

Routes of Entry: Inhalation, Ingestion, Skin contact, Eye contact.

Immediate (Acute) Health Effects:

Inhalation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Can cause severe central nervous system depression (including unconsciousness).

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption: Harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Ingestion: Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

Long-Term (Chronic) Health Effects:

Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.		
Skin Contact:	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.		
Eye Contact:	Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.		
Skin Absorption	Upon prolonged or repeated exposure, minimal hazard in normal industrial use. May cause gastrointestinal discomfort.		
Carcinogenicity:	IARC: No	NTP: No	OSHA: No

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

IV. FIRST AID

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eyes:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists. As a good general hygienic rule, if clothing comes in contact with the product, the clothing should be laundered before re-use.
Ingestion:	Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

V. FIRE FIGHTING MEASURES**Flammability Summary:**

Flash Point:	42 °C;	108 °F
Autoignition Temperature:	227 °C;	440 °F

Lower Flammable/Explosive Limit, % in air:	1.0	Upper Flammable/Explosive Limit, % in air:	13.1
---	-----	---	------

Fire Hazards: Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire Fighting Instructions: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

Hazardous Combustion Products: Toxic fumes, Carbon dioxide, Carbon monoxide.

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Spill Mitigation Procedures:**General Methods:**

Prevent the spread of any spill to minimize harm to health and the environment if safe to do so. Wear proper personal protective equipment following the recommendations of Section VIII. For liquid spills, dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Air Release:

Ventilate the area by opening door and/or turning on fans and blowers.

Water Release:

Retain all contaminated water for treatment.

Land Spills:

Avoid runoff into storm sewers and ditches that lead to waterways.

VII. HANDLING AND STORAGE**Handling:**

Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse. Keep in air-tight containers- material is hygroscopic.

Storage:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Keep away from heat, sparks, and flame.

VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT, AND EXPOSURE LIMITS**Engineering Controls:**

Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet any relevant OSHA chemical specific standards in 29 CFR 1910. Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Protective Equipment:**Respiratory Tract:**

If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

Eyes:

Wear safety glasses with side shields when handling this product. Do not wear contact lenses. Wear chemical splash goggles if splashing or high-pressure system is used. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield.

Skin:

Not normally considered a significant skin irritant. Where use can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Protective Clothing:

Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	No TLV	No PEL established	Not determined.
Methoxypropanol acetate	108-65-6	No TLV	No PEL established	Not determined.
Fumed silica	112945-52-5	No TLV	Respirable Dust: 20 mppcf	Not determined.

IX. PHYSICAL DATA**Appearance:**

Colorless Liquid.

Color:

Colorless

pH:

N/A

Octanol/Water Coeff:

Not Determined.

Solubility in Water:

Low.

Vapor Density:

N/A

Evaporation Rate:

Slower than n-Butyl Acetate.

Specific Gravity/Density:

0.919 / 7.67 Lbs./G1.

V.O.C.

4.7 Lbs/G1 less water & exempt solvent;

564 g/l less water & exempt solvent;

4.7 Lbs/G1 as packed

The VOC content is determined by using a percent solids basis, less water and exempt solvents, for adhesives, coatings and inks and the calculations of EPA Reference Method 24 or equivalent ASTM method approved by the executive office.

Initial Boiling Point: 119 °C; 246 °F

X. STABILITY AND REACTIVITY

Stability Information: Stable under normal conditions.
Conditions to Avoid: Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Contamination., Elevated temperatures.
Chemical Incompatibility: Strong alkalis.
Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide, Toxic fumes.

XI. TOXICOLOGICAL INFORMATION

Chemical Name	LD50/LC50
Acetic acid, 2-methoxy-1-methylethyl ester	Oral LD50 Rat: 8532 mg/kg; Dermal LD50 Rabbit: >5 gm/kg
Silica, amorphous fumed	Oral LD50 Rat: 3160 mg/kg

XII. ECOLOGICAL INFORMATION

Overview: Care should be taken to minimize releases of any industrial chemicals to the environment.

XIII. DISPOSAL CONSIDERATIONS

Waste Description for Unused Product: Spent or discarded material is a hazardous waste.
Disposal Methods: Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and clean-up materials in accordance with all federal, state, and local environmental regulations.
Potential EPA Waste Codes: D001, .

Some Components Possibly Subjected to USEPA Land Disposal Restrictions:

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories. None expected.

XIV. TRANSPORTATION INFORMATION

Agency Basic Description and Label

DOT DOT by Land Transport: Not Regulated; DOT by Air and IATA (all modes): Paint, 3, UN1263, PG III, Label Required: Flammable Liquid

Hazardous Substance

None expected.

XV. REGULATORY INFORMATION

Regulation

SARA 313 Reportable : This product contains no Section 313 chemicals at or above de minimis values.

TSCA Inventory : All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.

M.S.D.S. Reportable HAP(s) : This product contains no HAP chemicals at or above de minimis values..

California Proposition 65 : The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65: "WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm."

SARA/CERCLA Section 302 : N/A

XVI. ADDITIONAL INFORMATION

Major References: VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION OR USE, INCLUDING USE OF THIS MATERIAL IN COMBINATION WITH OTHER MATERIALS OR PROCESSES. YOU THEREFORE SHOULD, AND THIS MATERIAL IS SUPPLIED ON THE CONDITION THAT YOU, PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF THE MATERIAL PRIOR TO USE, AND YOU ACCEPT RESPONSIBILITY FOR SATISFYING YOURSELF THAT THE MATERIAL IS SUITABLE AND THE COMPLETENESS OF THIS INFORMATION IS SUFFICIENT FOR YOUR USE. ALTHOUGH CERTAIN HAZARDS MAY BE DESCRIBED HEREIN, OTHER HAZARDS MAY ALSO EXIST. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA, OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, AND WE DISCLAIM LIABILITY FOR LOSS OR INJURY ARISING FROM YOUR USE OF THIS MATERIAL, DATA OR INFORMATION. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.