



## MATERIAL SAFETY DATA SHEET

*For Spraylat Liquid Coatings and Associated Liquid Materials*

1701 East 122nd Street  
Chicago, IL 60633  
(773) 646-5900  
Fax: (773) 646-3743

716 South Columbus Avenue  
Mount Vernon, NY 10550  
(914) 699-3030  
Fax: (914) 699-3035

3465 South La Cienega Blvd.  
Los Angeles, CA 90016  
(310) 559-2335  
Fax: (310) 836-6094

3333 North Interstate 35  
Gainesville, TX 76240  
(940) 665-9590  
Fax: (940) 665-8867

e-mail [HSEcoordinator@Spraylat.com](mailto:HSEcoordinator@Spraylat.com)

PREPARED BY : Health, Safety and Environmental Coordinator

EMERGENCY PHONE:

1-800-424-9300

Chemtrec

INTERNATIONAL TRANSPORTATION ACCIDENTS:

1-703-527-3887

Chemtrec

### I. CHEMICAL PRODUCT IDENTIFICATION

Product Name : **G4016 ANTI-GRAFFITI CLEAR GLOSS (Part A)**

Date Printed : 02/05/04  
Revision Date : 10/03/03  
Supercedes : None

Revision Number : 1

### II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
Methyl isoamyl ketone	110-12-3	20.01 - 25.00
Methyl isobutyl ketone	108-10-1	10.01 - 15.00
Methoxypropanol acetate	108-65-6	10.01 - 15.00
Acetyl acetone	123-54-6	1.01 - 5.00
Xylene	1330-20-7	1.01 - 5.00
Ethylbenzene	100-41-4	0.10 - 1.00

If ingredient percentages do not total 100%, the balance is due to rounding or applies to ingredient(s) deemed nonhazardous under 29 CFR 1910.1200 (Hazard Communication Standard).

### III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2 *
FLAMMABILITY	3
REACTIVITY	0

0 = Least    1 = Slight    2 = Moderate    3 = High    4 = Extreme    \* = Chronic Health Effects

Routes of Entry:

Inhalation, Absorption, Eye contact, Skin contact, Ingestion.

Medical Conditions Aggravated:

Eye disease, Skin disease including eczema and sensitization, Liver disease, Kidney disease, Digestive tract disease, Lung disease.

#### Immediate (Acute) Health Effects:

**Inhalation:**

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Vapors may cause systemic injury. The degree of injury will depend on the concentration and duration of exposure. Inhalation of high concentrations may result in central nervous system (CNS) depression, and in the production of methemoglobinemia, leading to cyanosis.

**Skin Contact:**

May cause skin irritation. Allergic reactions are possible. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Eye Contact:**

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Skin Absorption:** Harmful if absorbed through the skin. May cause severe irritation and systemic damage. A single exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

**Ingestion:** Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

**Target Organ Acute Toxicity:** Eyes, Skin, Respiratory System, CNS, Liver, Kidneys, PNS, Blood, Digestive Tract, Thyroid, Pituitary, Testes.

**Long-Term (Chronic) Health Effects:**

**Inhalation:** Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Prolonged or excessive inhalation may cause respiratory tract irritation. Upon prolonged or repeated exposure, vapors may lead to systemic damage to specific target organs. The degree of injury will depend on the concentration and duration of exposure.

**Skin Contact:** Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. Prolonged or repeated contact may cause irritation and burns, and may result in irritant or allergic dermatitis.

**Eye Contact:** Upon prolonged or repeated contact, can cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Skin Absorption:** Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Carcinogenicity:** IARC: Yes                      NTP: No                      OSHA: No

**Target Organ Chronic Toxicity:** Eyes, Skin, Respiratory System, CNS, Liver, Kidneys, PNS, Blood, Central nervous system stimulation, Digestive Tract, Pituitary, Testes.

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney, lung and liver tumors. Testicular adenomas were increased as were thyroid effects in rats at 750 ppm. Pituitary effects were observed in female mice at 250 ppm. These effects were absent when exposure was below 75 ppm ethylbenzene. The study does not address the relevance of these results to humans.

**IV. FIRST AID**

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

**Eyes:** Immediately flush eyes with plenty of luke warm water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**Ingestion:** Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

**V. FIRE FIGHTING MEASURES**

**Flammability Summary:**

<b>Flash Point:</b>	18 °C;	64 °F	
<b>Autoignition Temperature:</b>	191 °C;	376 °F	
<b>Lower Flammable/Explosive Limit, % in air:</b>	1.1	<b>Upper Flammable/Explosive Limit, % in air:</b>	13.1

**Fire Hazards:**

Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.

**Extinguishing Media:**

Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

**Fire Fighting Instructions:**

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

**Hazardous Combustion Products:**

Carbon dioxide, Carbon monoxide.

**VI. ACCIDENTAL RELEASE MEASURES****Health Consideration for Spill Response:**

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, and the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

**Spill Mitigation Procedures:****General Methods:**

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Large spill (an uncontrolled release): Evacuate and summon professional help. If you have a trained spill response team, they should contain the liquids to minimize migration and vapor generation, and ventilate the area.

**Air Release:**

Ventilate the area by opening door and/or turning on fans and blowers.

**Water Release:**

Retain all contaminated water for treatment.

**Land Spills:**

Avoid runoff into storm sewers and ditches that lead to waterways.

**VII. HANDLING AND STORAGE****Handling:**

Harmful or irritating; avoid overexposure to the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Keep in air-tight containers- material is hygroscopic. Remove contaminated clothing and wash before reuse.

**Storage:**

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Keep away from sources of ignition. Store in a tightly closed container.

**VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT, AND EXPOSURE LIMITS****Engineering Controls:**

Local exhaust ventilation, process enclosures, or other engineering controls are necessary when handling or using this product to avoid overexposure. Vapor concentrations should be monitored and controlled in accordance with 29 CFR 1910.1000. Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**Protective Equipment:****Respiratory Tract:**

If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

**Eyes:**

Wear safety glasses with side shields when handling this product. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

**Protective Clothing:** Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
Methyl isoamyl ketone	110-12-3	50 ppm TWA	100 ppm TWA; 475 mg/m <sup>3</sup> TWA	Not determined.
Methyl isobutyl ketone	108-10-1	50 ppm TWA 75 ppm STEL	100 ppm TWA; 410 mg/m <sup>3</sup> TWA	500 ppm IDLH
Methoxypropanol acetate	108-65-6	No TLV	No PEL established	Not determined.
Acetyl acetone	123-54-6	No TLV	No PEL established	Not determined.
Xylene	1330-20-7	100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	900 ppm IDLH
Ethylbenzene	100-41-4	100 ppm TWA 125 ppm STEL	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	800 ppm IDLH

## IX. PHYSICAL DATA

**Appearance:** Colorless Liquid.  
**Color:** Colorless  
**Odor:** Ketone  
**pH:** N/A  
**Octanol/Water Coeff:** Not Determined.  
**Solubility in Water:** Low.  
**Vapor Density:** Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.  
**Evaporation Rate:** Slower than n-Butyl Acetate.  
**Specific Gravity/Density:** 0.966 / 8.06 Lbs./G1.  
**V.O.C.** 4.2 Lbs/G1 less water & exempt solvent; 504 g/l less water & exempt solvent; 4.2 Lbs/G1 as packed

The VOC content is determined by using a percent solids basis, less water and exempt solvents, for adhesives, coatings and inks and the calculations of EPA Reference Method 24 or equivalent ASTM method approved by the executive office.

**Initial Boiling Point:** 117 °C; 243 °F  
**Initial Freezing Point:** N/A

## X. STABILITY AND REACTIVITY

**Stability Information:** Stable under normal conditions.  
**Conditions to Avoid:** Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.,  
**Chemical Incompatibility:** Strong alkalis.  
**Hazardous Decomposition Products:** Carbon dioxide, Carbon monoxide.

## XI. TOXICOLOGICAL INFORMATION

Chemical Name	LD50/LC50
2-Hexanone, 5-methyl-	Oral LD50 Rat: 3200 mg/kg; Oral LD50 Mouse: 2542 mg/kg; Dermal LD50 Rabbit: 10 mL/kg
2-Pentanone, 4-methyl-	Inhalation LC50 Mouse: 23300 mg/m <sup>3</sup> ; Oral LD50 Rat: 2080 mg/kg; Oral LD50 Mouse: 2671 mg/kg; Dermal LD50 Rabbit: >20 mL/kg
Acetic acid, 2-methoxy-1-methylethyl ester	Oral LD50 Rat: 8532 mg/kg; Dermal LD50 Rabbit: >5 gm/kg
2,4-Pentanedione	Oral LD50 Rat: 55 mg/kg; Oral LD50 Mouse: 951 mg/kg; Dermal LD50 Rabbit: 810 uL/kg
Xylene	Inhalation LC50 Rat: 5000 ppm/4H; Oral LD50 Rat: 4300 mg/kg; Dermal LD50 Rabbit: >1700 mg/kg
Benzene, ethyl-	Oral LD50 Rat: 3500 mg/kg; Dermal LD50 Rabbit: 17800 uL/kg

## XII. ECOLOGICAL INFORMATION

**Overview:** Care should be taken to minimize releases of any industrial chemicals to the environment.

## XIII. DISPOSAL CONSIDERATIONS

**Waste Description for Spent Product:** Spent or discarded material is a hazardous waste.  
**Disposal Methods:** Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and clean-up materials in accordance with all federal, state, and local environmental regulations.

Potential EPA Waste Codes: D001, .

**Some Components Possibly Subjected to USEPA Land Disposal Restrictions:**

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories.

Methylisobutyl ketone	108-10-1
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethyl benzene	100-41-4

**XIV. TRANSPORTATION INFORMATION****Agency Basic Description and Label**

DOT Paint, 3, UN1263, PG II; Label Required: Flammable Liquid.

**Hazardous Substance**

Methylisobutyl ketone	RQ = 5000 pounds (2270 kg); also listed as 4-Methyl-2-pentanone
Xylenes (isomers and mixture)	RQ = 100 pounds (45.4 kg); also listed as Xylene; also listed as Xylene (mixed); also listed as Benzene, dimethyl-
Ethyl benzene	RQ = 1000 pounds (454 kg)

**XV. REGULATORY INFORMATION****Regulation**

SARA 313 Reportable : Methyl isobutyl ketone, Xylene (mixed isomers), ethylbenzene

TSCA Inventory : All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.

M.S.D.S. Reportable HAP(s) : Methyl isobutyl ketone (Hexone), Xylenes (isomers and mixture), Ethyl benzene.

SARA/CERCLA Section 302 : N/A

**XVI. ADDITIONAL INFORMATION****Major References:** VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

*IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.*