



MATERIAL SAFETY DATA SHEET

For Spraylat Liquid Coatings and Associated Liquid Materials

1701 East 122nd Street
Chicago, IL 60633
(773) 646-5900
Fax: (773) 646-3743

716 South Columbus Avenue
Mount Vernon, NY 10550
(914) 699-3030
Fax: (914) 699-3035

3465 South La Cienega Blvd.
Los Angeles, CA 90016
(310) 559-2335
Fax: (310) 836-6094

3333 North Interstate 35
Gainesville, TX 76240
(940) 665-9590
Fax: (940) 665-8867

e-mail HSEcoordinator@Spraylat.com

PREPARED BY : Health, Safety and Environmental Coordinator

EMERGENCY PHONE:

1-800-424-9300

Chemtrec

INTERNATIONAL TRANSPORTATION ACCIDENTS:

1-703-527-3887

Chemtrec

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name : **G4018 ANTI-GRAFFITI CLEAR MATTE (Part A)**

Date Printed : 09/10/04
Revision Date : 10/03/03
Supersedes : None

Revision Number : 1

COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
Methyl n-amyl ketone	110-43-0	15.01 - 20.00
Amorphous silica, silicon dioxide	112926-00-8	10.01 - 15.00
Acetone	67-64-1	10.01 - 15.00
Methoxypropanol acetate	108-65-6	10.01 - 15.00
Acetyl acetone	123-54-6	1.01 - 5.00
Xylene	1330-20-7	1.01 - 5.00
Ethylbenzene	100-41-4	0.10 - 1.00

If ingredient percentages do not total 100%, the balance is due to rounding or applies to ingredient(s) deemed nonhazardous under 29 CFR 1910.1200 (Hazard Communication Standard).

III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2 *
FLAMMABILITY	3
REACTIVITY	0

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme * = Chronic Health Effects

Routes of Entry:

Eye contact, Absorption, Inhalation, Skin contact, Ingestion.

Medical Conditions Aggravated:

Eye disease, Skin disease including eczema and sensitization, Kidney disease, Liver disease, Lung disease, Digestive tract disease.

Immediate (Acute) Health Effects:

Inhalation:

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Vapors may cause systemic injury. The degree of injury will depend on the concentration and duration of exposure. High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Inhalation of high concentrations may result in central nervous system (CNS) depression, and in the production of methemoglobinemia, leading to cyanosis.

Skin Contact:

Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact:

Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption: Harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Ingestion: Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

Target Organ Acute Toxicity: Eyes, Skin, CNS, Respiratory System, PNS, Kidneys, Liver, Central nervous system stimulation, Blood, Digestive Tract, Thyroid, Pituitary, Testes.

Long-Term (Chronic) Health Effects:

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Prolonged or repeated inhalation may cause lung damage. Prolonged or repeated inhalation may cause kidney and lung damage. Upon prolonged or repeated exposure, vapors may lead to systemic damage to specific target organs. The degree of injury will depend on the concentration and duration of exposure.

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Eye Contact: Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Carcinogenicity: IARC: Yes NTP: No OSHA: No

Target Organ Chronic Toxicity: Respiratory System, Eyes, Skin, CNS, PNS, Kidneys, Liver, Central nervous system stimulation, Blood, Digestive Tract, Pituitary, Testes.

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney, lung and liver tumors. Testicular adenomas were increased as were thyroid effects in rats at 750 ppm. Pituitary effects were observed in female mice at 250 ppm. These effects were absent when exposure was below 75 ppm ethylbenzene. The study does not address the relevance of these results to humans.

IV. FIRST AID

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

V. FIRE FIGHTING MEASURES

Flammability Summary:

Flash Point:	-20 °C;	-4 °F
Autoignition Temperature:	333 °C;	631 °F
Lower Flammable/Explosive Limit, % in air:	1.1	Upper Flammable/Explosive Limit, % in air: 13.1

- Fire Hazards:** Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.
- Extinguishing Media:** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.
- Fire Fighting Instructions:** Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.
- Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide.

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, and the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Spill Mitigation Procedures:

General Methods:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Ensure clean-up measures are in compliance with OSHA (29 CFR 1910.120). Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Air Release:

Ventilate the area by opening door and/or turning on fans and blowers.

Water Release:

Retain all contaminated water for treatment.

Land Spills:

Avoid runoff into storm sewers and ditches that lead to waterways.

VII. HANDLING AND STORAGE

Handling:

Harmful or irritating; avoid overexposure to the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Use spark-proof tools and explosion-proof equipment. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Keep in air-tight containers- material is hygroscopic. Remove contaminated clothing and wash before reuse.

Storage:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Keep away from sources of ignition. Store in a tightly closed container.

VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT, AND EXPOSURE LIMITS

Engineering Controls:

Local exhaust ventilation, process enclosures, or other engineering controls are necessary when handling or using this product to avoid overexposure. Vapor concentrations should be monitored and controlled in accordance with 29 CFR 1910.1000. Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Protective Equipment:

Respiratory Tract:

If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

Eyes:

Wear safety glasses with side shields when handling this product. Do not wear contact lenses. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield.

Skin: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Protective Clothing: Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
Methyl n-amyl ketone	110-43-0	50 ppm TWA	100 ppm TWA; 465 mg/m3 TWA	800 ppm IDLH
Amorphous silica, silicon dioxide	112926-00-8	10 mg/m3 TWA	No PEL established	Not determined.
Acetone	67-64-1	500 ppm TWA 750 ppm STEL	1000 ppm TWA; 2400 mg/m3 TWA	2500 ppm IDLH
Methoxypropanol acetate	108-65-6	No TLV	No PEL established	Not determined.
Acetyl acetone	123-54-6	No TLV	No PEL established	Not determined.
Xylene	1330-20-7	100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m3 TWA	900 ppm IDLH
Ethylbenzene	100-41-4	100 ppm TWA 125 ppm STEL	100 ppm TWA; 435 mg/m3 TWA	800 ppm IDLH

IX. PHYSICAL DATA

Appearance: Clear Liquid.
Color: Clear
Odor: Ketone
Octanol/Water Coeff: N/A
Solubility in Water: Not Determined.
Vapor Density: Partial.
Evaporation Rate: Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Specific Gravity/Density: Slower than n-Butyl Acetate.
V.O.C. 1.04 / 8.68 Lbs./Gl.
 3.5 Lbs/Gl less water & exempt solvent; 420 g/l less water & exempt solvent; 2.9 Lbs/Gl as packed

The VOC content is determined by using a percent solids basis, less water and exempt solvents, for adhesives, coatings and inks and the calculations of EPA Reference Method 24 or equivalent ASTM method approved by the executive office.

The Federal EPA has delisted Acetone as a VOC. Even though this product contains Acetone (see Section II), the VOC listed above does not include Acetone in the VOC calculation. Individual states may have other regulations. Please check with your state.

Initial Boiling Point: 56 °C; 133 °F
Initial Freezing Point: N/A

X. STABILITY AND REACTIVITY

Stability Information: Stable under normal conditions.
Conditions to Avoid: Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.,
Chemical Incompatibility: Strong acids, Strong alkalis.
Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide.

XI. TOXICOLOGICAL INFORMATION

Chemical Name	LD50/LC50
2-Heptanone	Oral LD50 Rat: 1670 mg/kg; Oral LD50 Mouse: 730 mg/kg; Dermal LD50 Rabbit: 12600 uL/kg
Acetone	Inhalation LC50 Rat: 50100 mg/m3/8H; Inhalation LC50 Mouse: 44 gm/m3/4H; Oral LD50 Rat: 5800 mg/kg; Oral LD50 Mouse: 3 gm/kg
Acetic acid, 2-methoxy-1-methylethyl ester	Oral LD50 Rat: 8532 mg/kg; Dermal LD50 Rabbit: >5 gm/kg
2,4-Pentanedione	Oral LD50 Rat: 55 mg/kg; Oral LD50 Mouse: 951 mg/kg; Dermal LD50 Rabbit: 810 uL/kg
Xylene	Inhalation LC50 Rat: 5000 ppm/4H; Oral LD50 Rat: 4300 mg/kg; Dermal LD50 Rabbit: >1700 mg/kg
Benzene, ethyl-	Oral LD50 Rat: 3500 mg/kg; Dermal LD50 Rabbit: 17800 uL/kg

XII. ECOLOGICAL INFORMATION

Overview:

Care should be taken to minimize releases of any industrial chemicals to the environment.

XIII. DISPOSAL CONSIDERATIONS

**Site Description for Spent Product:
Disposal Methods:**

Spent or discarded material is a hazardous waste. Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and clean-up materials in accordance with all federal, state, and local environmental regulations.

Potential EPA Waste Codes:

D001, .

Some Components Possibly Subjected to USEPA Land Disposal Restrictions:

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories.

Acetone	67-64-1
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethyl benzene	100-41-4

XIV. TRANSPORTATION INFORMATION

Agency Basic Description and Label

DOT Paint, 3, UN1263, PG II; Label Required: Flammable Liquid.

Hazardous Substance

Acetone	RQ = 5000 pounds (2270 kg); also listed as 2-Propanone
Xylenes (isomers and mixture)	RQ = 100 pounds (45.4 kg); also listed as Xylene; also listed as Xylene (mixed); also listed as Benzene, dimethyl-
Ethyl benzene	RQ = 1000 pounds (454 kg)

XV. REGULATORY INFORMATION

Regulation

SARA 313 Reportable : Xylene (mixed isomers), ethylbenzene

TSCA Inventory : All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.

M.S.D.S. Reportable HAP(s) : Xylenes (isomers and mixture), Ethyl benzene.

SARA/CERCLA Section 302 : N/A

VI. ADDITIONAL INFORMATION

Major References: VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION OR USE, INCLUDING USE OF THIS MATERIAL IN COMBINATION WITH OTHER MATERIALS OR PROCESSES. YOU THEREFORE SHOULD, AND THIS MATERIAL IS SUPPLIED ON THE CONDITION THAT YOU, PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF THE MATERIAL PRIOR TO USE, AND YOU ACCEPT RESPONSIBILITY FOR SATISFYING YOURSELF THAT THE MATERIAL IS SUITABLE AND THE COMPLETENESS OF THIS INFORMATION IS SUFFICIENT FOR YOUR USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA, OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, AND WE DISCLAIM LIABILITY FOR LOSS OR INJURY ARISING FROM YOUR USE OF THIS MATERIAL, DATA OR INFORMATION. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.