



## MATERIAL SAFETY DATA SHEET

*For 1Shot/Chromatic® Liquid Coatings and Associated Liquid Materials*

### **One Shot, LLC**

A Spraylat Company  
5300 W. 5th Avenue  
Gary, IN 46406  
(219) 949-1684  
Fax: (219) 949-1612

e-mail HSEcoordinator@Spraylat.com

**PREPARED BY:** Health, Safety and Environmental Coordinator

<b>EMERGENCY PHONE:</b>	<b>1-800-424-9300</b>	<b>Chemtrec</b>
<b>INTERNATIONAL TRANSPORTATION ACCIDENTS:</b>	<b>1-703-527-3887</b>	<b>Chemtrec</b>

**Revision Date :** 10/10/2007      **Version:** 4.2      **Supersedes:** All Previous

### I. CHEMICAL PRODUCT IDENTIFICATION

**Product Name:** Chromatic® Industrial Enamels (4117101, 4117101HP, 4117101SP)  
Chromatic® Industrial Maintenance Coatings (4137002, 4138000, 4138005)

### II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

THE ITEMS LISTED BELOW ARE NOT CONTAINED IN ALL COLORS. SEE THE TABLE ON PAGE 2 TO DETERMINE WHICH COLORS CONTAIN THESE INGREDIENTS AND % WT.

INGREDIENT NAME	CAS #	%	INGREDIENT NAME	CAS #	%
Stoddard solvent	8052-41-3	<40	Ethylbenzene	100-41-4	< 1
Titanium dioxide	13463-67-7	<35	Light Aromatic Solvent Naphtha	64742-95-6	< 5
Light aliphatic solvent naphtha	64742-89-8	<10	Silicon Dioxide (amorphous)	7631-86-9	< 5
Naphtha (petroleum), heavy aromatic	64742-94-5	<10	Xylene	1330-20-7	< 5
Aluminum oxide	1344-28-1	< 5	1,2,4-Trimethylbenzene	95-63-6	< 1
Carbon black	1333-86-4	< 5	1,3,5-Trimethylbenzene	108-67-8	< 1
Chlorinated paraffins	63449-39-8	< 5	Naphthalene	91-20-3	< 1

### III. HAZARDS IDENTIFICATION

HMIS Hazard Rating	
<b>HEALTH</b>	2 *
<b>FLAMMABILITY</b>	2
<b>REACTIVITY</b>	0

0 = Least    1 = Slight    2 = Moderate    3 = High    4 = Extreme    \* = Chronic Health Effects

**Routes of Entry:**

Inhalation, Absorption, Ingestion, Skin contact, Eye contact.

**Medical Conditions Aggravated:**

Eye disease, Skin disease including eczema and sensitization, Kidney disease, Lung disease, Liver disease, Digestive tract disease.

**ADDITIONAL INGREDIENTS OF INDUSTRIAL ENAMELS AND INDUSTRIAL MAINTENANCE COATINGS -- Weight %**

Ingredients	4117101	4117101HP	4117101SP	4137002	4138000	4138005	CARCINOGENICITY		
							IARC	NTP	OSHA
1,2,4-Trimethylbenzene	< 1	< 1	.....	< 1	< 1	< 1	No	No	No
1,3,5-Trimethylbenzene	< 1	< 1	.....	< 1	< 1	< 1	No	No	No
Aluminum oxide	< 5	< 5	< 5	.....	.....	.....	No	No	No
Carbon black	.....	.....	.....	< 5	.....	.....	Yes	No	No
Chlorinated paraffins	< 5	.....	.....	.....	.....	.....	No	No	No
Ethylbenzene	< 1	< 1	< 1	< 1	< 1	< 1	Yes	No	No
Light aliphatic solvent naphtha	<10	.....	.....	.....	.....	.....	No	No	No
Light Aromatic Solvent Naphtha	.....	.....	.....	.....	< 5	.....	No	No	No
Naphtha (petroleum), heavy aromatic	.....	<10	.....	.....	.....	.....	No	No	No
Naphthalene	.....	< 1	.....	.....	.....	.....	Yes	No	No
Silicon Dioxide (amorphous)	< 5	< 5	< 5	.....	.....	.....	No	No	No
Stoddard solvent	<30	<40	<40	<40	<40	<40	No	No	No
Titanium dioxide	<35	<35	<35	<20	.....	<10	Yes	No	No
Xylene	< 5	< 5	< 5	.....	< 5	< 5	No	No	No

**Immediate (Acute) Health Effects:**

**Inhalation:**

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Can cause severe central nervous system depression (including unconsciousness).

**Skin Contact:**

Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Eye Contact:**

Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

**Skin Absorption:**

May cause irritation and minor systemic damage.

**Ingestion:**

Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

**Target Organ Acute Toxicity:**

Eyes, Skin, Respiratory System, Kidneys, Nervous System, Bone Marrow, Cardiovascular System, Lymphatic System, Blood, Liver, Digestive Tract, Thyroid, Pituitary, Testes.

**Long-Term (Chronic) Health Effects:**

**Inhalation:**

Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

**Skin Contact:**

Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Eye Contact:**

Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

**Skin Absorption:**

Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Carcinogenicity:**

See Table on page 2.

**Target Organ Chronic Toxicity:**

Respiratory System, Nervous System, Eyes, Skin, Kidneys, Lymphatic System, Blood, Liver, Digestive Tract, Pituitary, Testes.

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney, lung and liver tumors. Testicular adenomas were increased as were thyroid effects in rats at 750 ppm. Pituitary effects were observed in female mice at 250 ppm. These effects were absent when exposure was below 75 ppm ethylbenzene. The study does not address the relevance of these results to humans.

IARC has recently re-evaluated titanium dioxide as possibly carcinogenic to humans (Group 2B) based on animal studies. However, human studies available to date do not suggest that occupational exposure to titanium dioxide increases cancer risk. The ACGIH classifies titanium dioxide as A4 (not classifiable as a human carcinogen). NTP does not classify it as carcinogenic. IARC's evaluation shows inadequate evidence of carcinogenicity in humans, but sufficient evidence of carcinogenicity in experimental animals. The evidence shows that high concentrations of powdered and ultrafine titanium dioxide dust caused respiratory tract cancer in rats exposed by either natural inhalation or direct introduction into the lungs. However, the same results are observed in people working in dusty environments. Therefore, IARC extended this idea to workers with exposures to titanium dioxide dust, if there are insufficient dust control measures in place. Based on the IARC decision, Canadian officials have agreed that titanium dioxide is classifiable as WHMIS D2A (carcinogen), and that it is not necessary to wait for release of the full monograph. OSHA requires the status on US MSDSs to change within 90 days of publication in the IARC monograph volume 93.

This product contains pigments which may become a dust nuisance when removed by abrasive blasting, sanding or grinding.

#### IV. FIRST AID

<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. Seek medical attention if symptoms persist. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
<b>Eyes:</b>	Immediately flush eyes with plenty of luke warm water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
<b>Skin Contact:</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
<b>Ingestion:</b>	Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

#### V. FIRE FIGHTING MEASURES

<b>Flammability Summary:</b>	Combustible		
<b>Flash Point:</b>	41 °C/106 °F		
<b>Autoignition Temperature:</b>	226 °C; 439 °F		
<b>Lower Flammable/Explosive Limit, % in air:</b>	1.0	<b>Upper Flammable/Explosive Limit, % in air:</b>	7.0

<b>Fire Hazards:</b>	Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.
<b>Extinguishing Media:</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.
<b>Fire Fighting Instructions:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.
<b>Hazardous Combustion Products:</b>	Carbon dioxide, Carbon monoxide, Toxic fumes, Chlorine containing gases.

## VI. ACCIDENTAL RELEASE MEASURES

**Health Consideration for Spill Response:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including: the material spilled, the quantity of the spill, and the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

### Spill Mitigation Procedures:

**General Methods:**

Prevent the spread of any spill to minimize harm to health and the environment if safe to do so. Wear proper personal protective equipment following the recommendations of Section VIII. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

**Air Release:**

Ventilate the area by opening door and/or turning on fans and blowers.

**Water Release:**

Retain all contaminated water for treatment.

**Land Spills:**

Avoid runoff into storm sewers and ditches that lead to waterways.

## VII. HANDLING AND STORAGE

**Handling:**

Harmful or irritating; avoid overexposure to the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Remove contaminated clothing and wash before reuse. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

## VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE LIMITS

**Engineering Controls:**

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. See table at the end of this Section VIII below for exposure limits. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Engineering controls must be designed to meet any relevant OSHA chemical specific standards in 29 CFR 1910. Explosion proof exhaust ventilation should be used.

### Protective Equipment:

**Respiratory Tract:**

If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection is required to avoid overexposure when handling this product.

**Eyes:**

Wear safety glasses with side shields when handling this product. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield. Do not wear contact lenses. Have an eye wash station available.

**Skin:**

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

**Protective Clothing:**

Wear chemically resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
1,2,4-Trimethylbenzene	95-63-6	No TLV	No PEL established	Not determined.
1,3,5-Trimethylbenzene	108-67-8	No TLV	No PEL established	Not determined.
Aluminum hydroxide	21645-51-2	No TLV	No PEL established	Not determined.
Carbon black	1333-86-4	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWA	1750 mg/m <sup>3</sup> IDLH
Chlorinated paraffins	63449-39-8	No TLV	No PEL established	Not determined.
Ethylbenzene	100-41-4	100 ppm TWA 125 ppm STEL	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	800 ppm IDLH (10 percent lower explosive limit)
Light aliphatic solvent naphtha	64742-89-8	No TLV	No PEL established	Not determined.
Light Aromatic Solvent Naphtha	64742-95-6	No TLV	No PEL established	Not determined.
Naphtha (petroleum), heavy aromatic	64742-94-5	No TLV	No PEL established	Not determined.
Silicon Dioxide (amorphous)	7631-86-9	10 mg/m <sup>3</sup> TWA	Respirable Dust: 20 mppcf	3000 mg/m <sup>3</sup> IDLH
Solvent Naphtha (petroleum), medium aliphatic	64742-88-7	No TLV	No PEL established	Not determined.
Stoddard solvent	8052-41-3	100 ppm TWA	500 ppm TWA; 2900 mg/m <sup>3</sup> TWA	20,000 mg/m <sup>3</sup> IDLH
Titanium dioxide	13463-67-7	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> TWA (total dust)	Potential NIOSH carcinogen.
Xylene	1330-20-7	100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	900 ppm IDLH

## IX. PHYSICAL DATA

<b>Appearance:</b>	Liquid.
<b>pH:</b>	N/A
<b>Octanol/Water Coeff:</b>	Not Determined.
<b>Solubility in Water:</b>	Minimal.
<b>Vapor Density:</b>	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
<b>Evaporation Rate:</b>	Slower than n-Butyl Acetate.

PRODUCT#	4117101	4117101HP	4117101SP	4137002	4138000
DENSITY (LB/GAL)	10.6	10.3	10.6	8.7	8.4
V.O.C. (LB/GAL)‡	3.9	3.8	3.4	3.4	4.0

‡ The VOC content is determined by using a percent solids basis, less water and exempt solvents, for adhesives, coatings and inks and the calculations of EPA Reference Method 24 or equivalent ASTM method approved by the executive office.

<b>Initial Boiling Point</b>	119 ° C;	246 ° F
<b>Initial Freezing Point</b>	N/A	

## X. STABILITY AND REACTIVITY

<b>Stability Information:</b>	Stable under normal conditions.
<b>Conditions to Avoid:</b>	Contamination, High temperatures, Sparks, open flame, other ignition sources, and elevated temperatures.
<b>Chemical Incompatibility:</b>	Strong oxidizing agents, Chlorine.
<b>Hazardous Decomposition Products:</b>	Carbon dioxide, Carbon monoxide, Toxic fumes, Chlorine containing gases.

## XI. TOXICOLOGICAL INFORMATION

Chemical Name	LD50/LC50
Benzene, ethyl-	Oral LD50 Rat : 3500 mg/kg; Dermal LD50 Rabbit : 17800 uL/kg
Benzene, 1,2,4-trimethyl-	Inhalation LC50 Rat : 18 gm/m <sup>3</sup> /4H; Oral LD50 Rat : 5 gm/kg
Carbon black	Oral LD50 Rat : >15400 mg/kg; Dermal LD50 Rabbit : >3 gm/kg
Mesitylene	Inhalation LC50 Rat : 24 gm/m <sup>3</sup> /4H
Paraffin waxes and hydrocarbon waxes, chlorinated	Oral LD50 Rat : >21500 uL/kg; Dermal LD50 Rabbit : >10 mL/kg
Xylene	Inhalation LC50 Rat : 5000 ppm/4H; Oral LD50 Rat : 4300 mg/kg; Dermal LD50 Rabbit : >1700 mg/kg

## XII. ECOLOGICAL INFORMATION

**Overview:** Care should be taken to minimize releases of any industrial chemicals to the environment.

## XIII. DISPOSAL CONSIDERATIONS

<b>Waste Description for Spent Product:</b>	Spent or discarded material is a hazardous waste. The waste is ignitable.
<b>Disposal Methods:</b>	Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and clean-up materials in accordance with all federal, state, and local environmental regulations.

### Some Components Possibly Subjected to USEPA Land Disposal Restrictions:

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories.

Xylenes (o-, m-, p- isomers)	1330-20-7
Ethyl benzene	100-41-4

## XIV. TRANSPORTATION INFORMATION

<b>Agency</b>	<b>Basic Description and Label</b>
DOT	DOT by Land Transport: Not regulated.
	DOT by Air and IATA (all modes) All are Paint,3,UN1263,PGIII.

### Hazardous Substance

Xylenes (isomers and mixture)	final RQ = 100 pounds (45.4 kg); also listed as Xylene; also listed as Xylene (mixed); also listed as Benzene, dimethyl-
Ethyl benzene	final RQ = 1000 pounds (454 kg)

## XV. REGULATORY INFORMATION

### Regulation

SARA 313 Reportable :	Xylene (mixed isomers), Ethyl benzene, 1,2,4-Trimethylbenzene.
TSCA Inventory :	All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.
M.S.D.S. Reportable HAP(s) :	Xylenes (isomers and mixture), Ethyl benzene.
California Proposition 65:	The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65: "WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm."

## XVI. ADDITIONAL INFORMATION

**Major References:** VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

**IMPORTANT:** WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION OR USE, INCLUDING USE OF THIS MATERIAL IN COMBINATION WITH OTHER MATERIALS OR PROCESSES. YOU THEREFORE SHOULD, AND THIS MATERIAL IS SUPPLIED ON THE CONDITION THAT YOU, PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF THE MATERIAL PRIOR TO USE, AND YOU ACCEPT RESPONSIBILITY FOR SATISFYING YOURSELF THAT THE MATERIAL IS SUITABLE AND THE COMPLETENESS OF THIS INFORMATION IS SUFFICIENT FOR YOUR USE. ALTHOUGH CERTAIN HAZARDS MAY BE DESCRIBED HEREIN, OTHER HAZARDS MAY ALSO EXIST. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA, OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, AND WE DISCLAIM LIABILITY FOR LOSS OR INJURY ARISING FROM YOUR USE OF THIS MATERIAL, DATA OR INFORMATION. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.