



MATERIAL SAFETY DATA SHEET

For Spraylat Liquid Coatings and Associated Liquid Materials

1701 East 122nd Street Chicago, IL 60633 (773) 646-5900 Fax: (773) 646-3743	716 South Columbus Avenue Mount Vernon, NY 10550 (914) 699-3030 Fax: (914) 699-3035	3465 South La Cienega Blvd. Los Angeles, CA 90016 (310) 559-2335 Fax: (310) 836-6094	3333 North Interstate 35 Gainesville, TX 76240 (940) 665-9590 Fax: (940) 665-8867
--	--	---	--

e-mail: HSEcoordinator@Spraylat.com

PREPARED BY: HSE Coordinator

EMERGENCY PHONE: 1-800-424-9300 Chemtrec
INTERNATIONAL TRANSPORTATION ACCIDENTS: 1-703-527-3887 Chemtrec

Revision Date : 09/05/2007 **Version:** 5.1 **Supersedes:** All Previous

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name: LACRYL 800 SERIES (L-801, L-804, L-806, L-809, L-812, L-813, L-814, L-815, L-821, L-822, L-823, L-832, L-833, L-834, L-835, L-837, L-838, L-839, L-840, L-842, L-843, L-844, L-845, L-846, L-851, L-852, L-853, L-855, L-856, L-857, L-860, L-861, L-862, L-863, L-870, L-871, L-880, L-881, L-882, L-890, L-891, L-896, L-897, L-898)

II. COMPOSITION/INFORMATION ON INGREDIENTS - (EXPOSURE LIMITS - SEE SECTION VIII)

INGREDIENT NAME	CAS #	%
Ethylene glycol mono-n-butyl ether	111-76-2	< 40
Stoddard solvent	8052-41-3	< 20
Diethylene glycol monoethyl ether	111-90-0	< 15
Diethylene glycol mono-n-butyl ether	112-34-5	< 10
Ethylene glycol	107-21-1	< 5

ITEMS LISTED BELOW ARE NOT CONTAINED IN MOST COLORS. SEE TABLE STARTING ON PAGE 4 FOR WHICH COLORS CONTAIN THESE INGREDIENTS AND % WT.

Aluminum oxide	1344-28-1	-
Antimony Trioxide	1309-64-4	-
Barium Sulfate	7727-43-7	-
Carbon black	1333-86-4	-
Crystalline Silica (Respirable)	14808-60-7	-
Lead Chromate	7758-97-6	-
Lead (II) Sulfate	7446-14-2	-
Lead Molybdate	10190-55-3	-
Talc	14807-96-6	-
Titanium dioxide	13463-67-7	-

III. HAZARDS IDENTIFICATION

	HMIS
HEALTH	2 *
FLAMMABILITY	2
REACTIVITY	0

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme * = Chronic Health Effects

Routes of Entry: Inhalation, Absorption, Ingestion, Skin contact, Eye contact
Medical Conditions Aggravated: Liver disease, Skin disease including eczema and sensitization, Eye disease, Kidney disease, Respiratory disease including asthma and bronchitis, Digestive tract disease

Immediate (Acute) Health Effects:

Inhalation:

Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful. Can cause systemic damage, see target organs below.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Exposure to high levels of airborne or ingested lead may produce symptoms of anemia, insomnia, weakness, constipation, nausea and abdominal pain. Overexposure may cause damage to blood-forming, nervous, reproductive, intestinal and urinary systems. Toxic. Can cause systemic damage, see target organs below. Respiratory failure is possible at high doses.

Skin Contact:

Can cause minor skin irritation, defatting, and dermatitis.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Can cause moderate injury (reddening and swelling). Can cause severe irritation, defatting, and dermatitis. Irritation effects may last for hours or days but will not likely result in permanent damage.

Eye Contact:

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Contact may cause eye irritation and transient corneal damage.

Skin Absorption:

Harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Can be absorbed through the skin to cause kidney and liver damage.

Ingestion:

Harmful if swallowed. May cause systemic poisoning. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Ingestion of this product may result in central nervous system effects including headache, sleepiness, dizziness, slurred speech and blurred vision.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Toxic if swallowed. May cause systemic poisoning. May cause target organ failure and/or death. Large exposure may be fatal. Muscular weakness Tremors Loss of appetite Anemia Insomnia Irritating to mouth, throat, and stomach.

Target Organ Acute Toxicity:

Nervous System, Liver, Skin, Blood, Eyes, Kidneys, Respiratory System, Lymphoid System, Nose, Heart, Lungs

Products containing Lead (see Table, page 4) can affect the following Target Organs:

Nervous System, Eyes, Liver, Skin, Respiratory System, Blood, Reproductive System, Kidneys, Digestive Tract, Gingival Tissue, Lymphoid System, Nose, Heart, Lungs

Long-Term (Chronic) Health Effects:

Ingestion:

Harmful if swallowed. May cause systemic poisoning.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Upon prolonged or repeated exposure, may lead to a metallic taste in mouth.

Inhalation:

Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

Respiratory tract sensitization, characterized by asthma-like symptoms such as tightness in the chest, difficulty breathing, and wheezing may result from prolonged or repeated inhalation of dust/processing fumes of this product. Pulmonary edema (fluid buildup in the lungs) Ulceration and perforation of the nasal septum.

Skin Contact:

Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. Prolonged contact with this product may cause allergic skin sensitization reactions.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects:

May cause sensitization. Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Upon prolonged or repeated contact, may lead to a metallic taste in mouth.

Eye Contact: Upon prolonged or repeated contact, can cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects: Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Ingredients containing Lead (see Table, page 4) can cause the following additional effects: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Carcinogenicity: See Table starting on page 4.

Target Organ Chronic Toxicity: Respiratory System, Nervous System, Kidneys, Liver, Skin, Blood, Eyes, Nose, Heart, Lungs

Products containing Lead (see Table, page 4) can affect the following Target Organs: Nervous System, Eyes, Liver, Skin, Respiratory System, Blood, Reproductive System, Kidneys, Digestive Tract, Gingival Tissue, Lymphoid System, Nose, Heart, Lungs

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

NOTICE - This product contains pigments which may become a dust nuisance when removed by abrasive blasting, sanding or grinding.

Over exposure of laboratory animals to a high concentration (700 ppm for 7 hours) of ethylene glycol n-butyl ether caused systemic toxicity in the form of hemoglobinuria and lung, kidney and liver changes. Exposure of rats to a lower concentration (320 ppm) for five weeks caused hemolytic anemia and increased fragility of the red blood cells. However, dogs exposed to a higher concentration (400 ppm) for a longer period (12 weeks) showed only slight injury. Humans appear to be less susceptible, and toxicity may be more likely to occur as a result of skin absorption than from inhalation.

Products L-853 and L-857 contain Crystalline Silica (see Additional Ingredients, page 4): Cutting, sanding or grinding dried or cured material may release particles of crystalline silica (quartz). Exposure to airborne particles may cause lung damage including a risk of cancer. Chronic exposure may result in chest pain, difficulty breathing, lung damage and silicosis. (Silicosis is the permanent deposition of silica in lung tissue that results in lung damage.) There may exist a relationship between silicosis and certain cancers.

IARC has recently re-evaluated titanium dioxide as possibly carcinogenic to humans (Group 2B) based on animal studies. However, human studies available to date do not suggest that occupational exposure to titanium dioxide increases cancer risk. The ACGIH classifies titanium dioxide as A4 (not classifiable as a human carcinogen). NTP does not classify it as carcinogenic. IARC's evaluation shows inadequate evidence of carcinogenicity in humans, but sufficient evidence of carcinogenicity in experimental animals. The evidence shows that high concentrations of powdered and ultrafine titanium dioxide dust caused respiratory tract cancer in rats exposed by either natural inhalation or direct introduction into the lungs. However, the same results are observed in people working in dusty environments. Therefore, IARC extended this idea to workers with exposures to titanium dioxide dust, if there are insufficient dust control measures in place. Based on the IARC decision, Canadian officials have agreed that titanium dioxide is classifiable as WHMIS D2A (carcinogen), and that it is not necessary to wait for release of the full monograph. OSHA requires the status on US MSDSs to change within 90 days of publication in the IARC monograph volume 93.

ADDITIONAL INGREDIENTS OF LACRYL 800 SERIES

LACRYL 800 PRODUCT #	DENSITY LBS/GL	V.O.C. LBS/GL	WEIGHT PERCENT											
			CARBON BLACK	TALC	TITANIUM DIOXIDE	LEAD CHROMATE	LEAD SULFATE	LEAD MOLYBDATE	ANTIMONY TRIOXIDE	BARIUM SULFATE	ZINC CHROMATE	ALUMINUM FLAKE/OX	SILICA QUARTZ	
L-801	9.7	4.5		<10	<15									
L-804	9.6	4.4		<10	<15									
L-806	11.2	4.6		< 5	<40									
L-809	9.6	4.5		<10	<15		0.3							
L-812	9.3	5					13.5	0.9						
L-813	9.7	5		<10			8.2	3.9		0.4				
L-814	09.7	4.78		<15			8.0	3.8		0.4				
L-815	10.3	4.7		<10			10.3	7.8		0.3	< 5			
L-821	9.4	4.9		<10			12.3	1.0						
L-822	9.5	4.8		<10			12.2	1.0						
L-823	9.2	4.9		<10										
L-832	9	5.1												
L-833	9.4	4.9		<10			10.2	0.8						
L-834	9.1	4.9		< 5			6.4	0.5						
L-835	9.1	5		< 5			2.6	0.2						
L-837	8.9	5.3					7.2	0.6	0.6	0.2				
L-838	8.8	5.3					6.0	0.5	0.5	0.2				
L-839	9.5	4.8		<10			7.3	0.6	0.6	0.2				
L-840	8.9	5		<10										
L-842	9.5	5		<10			8.0	0.7						
L-843	8.3	5.3												
L-844	8.3	4.8												
L-845	8.6	6.4		< 5										
L-846	8.6	6.4		< 5										
L-851	9.4	4.8		<10										
L-852	9.4	4.8		<10										
L-853	9.4	4.8		<10										0.4
L-855	9.3	4.8	2	<15	< 5		3.3	0.2					< 5	

ADDITIONAL INGREDIENTS OF LACRYL 800 SERIES (continued)

LACRYL 800 PRODUCT #	DENSITY LBS/GL	V.O.C. LBS/GL	WEIGHT PERCENT										
			CARBON BLACK	TALC	TITANIUM DIOXIDE	LEAD CHROMATE	LEAD SULFATE	LEAD MOLYBDATE	ANTIMONY TRIOXIDE	BARIUM SULFATE	ZINC CHROMATE	ALUMINUM FLAKE/OX	SILICA QUARTZ
L-856	9.4	4.3	1.2	<10	< 5		2.5	0.2				< 5	
L-857	10.2	4.7	0.1	< 5								< 5	0.8
L-860	8.4	4.7											
L-861	8.3	4.9											
L-862	8.4	4.7											
L-863	9.1	3.7											
L-870	8.6	4.8											
L-871	8.8	4.9											
L-880	8.4	4.8	5.7										
L-881	8.6	5	4.4										
L-882	10.4	4.4	1.1										
L-890	8.3	4.6											
L-891	9.2	4.7		<20									
L-896	8.6	4.7										<15	
L-897	8	4.8										<10	
L-898	11.6	4.5		< 5	<30						4.9	<10	

Carcinogenicity:	IARC	Yes	No	Yes	Yes	No	No	Yes	No	Yes	No	Yes
	NTP	No	No	No	Yes	No	No	No	No	Yes	No	Yes
	OSHA	No	No	No	No	No	No	No	No	No	No	No

IV. FIRST AID

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eyes:	Immediately flush eyes with plenty of luke warm water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion:	Seek medical advice immediately. Provide ingredients information from Section II of this MSDS to the medical care provider. Contact your local Poison Control Center (listed in the telephone book), or dial the local "Emergency" (911) number for additional information. Do not induce vomiting unless instructed to do so by a physician or other competent medical personnel. Never give anything by mouth to an unconscious person.

V. FIRE FIGHTING MEASURES

Flammability Summary: Combustible

Flash Point: 39 ° C; 102 ° F

Autoignition Temperature: 204 ° C; 399 ° F

Lower Flammable/Explosive Limit, % in air: 0.8 **Upper Flammable/Explosive Limit, % in air:** 24.6

Fire Hazards: Can release vapors that form explosive mixtures at temperatures at or above the flash point. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or crush used containers. Do not expose containers or product to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Container may explode in heat of fire. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. This product, when dried or cured, may support combustion when subjected to sources of ignition or heat in sufficient amount.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire Fighting Instructions: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response: Exposure to the spilled material may be severely irritating or highly toxic. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Spill Mitigation Procedures:

General Methods: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Air Release: Ventilate the area by opening door and/or turning on fans and blowers.

Water Release: Avoid runoff into storm sewers and ditches that lead to waterways. If runoff occurs, notify proper authorities as required, that a spill has occurred.

Land Spills: Do not flush to sewer.

VII. HANDLING AND STORAGE

Handling: Toxic or severely irritating; avoid overexposure to the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment.

Storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed when not in use. Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition. Do not store near combustible materials. Limit quantity of material stored.

VIII. ENGINEERING CONTROLS, PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE LIMITS

Engineering Controls: Local exhaust ventilation, process enclosures, or other engineering controls are important when handling or using this product to avoid overexposure. Engineering controls must be designed to meet any relevant OSHA chemical specific standards in 29 CFR 1910. Explosion proof exhaust ventilation should be used. Facilities storing or using this material should be equipped with an eyewash and safety shower.

Protective Equipment:
Respiratory Tract: If general or local exhaust ventilation is not available or sufficient to reduce exposure to below acceptable levels, then respiratory protection may be required to avoid overexposure when handling this product. If a respirator is warranted, follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements.

Eyes: Wear chemically resistant safety glasses with side shields when handling this product. When the possibility exists for eye contact with splashing or spraying liquid, or airborne material, wear additional eye protection such as chemical splash goggles and/or face shield. Do not wear contact lenses. Have an eye wash station available.

Skin: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical breakthrough and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Protective Clothing: Wear resistant gloves and apron. (Consult your safety equipment supplier).

CHEMICAL NAME	CAS #	ACGIH TLV	OSHA PEL	IDLH
Aluminum oxide	1344-28-1	as Al: 10 mg/m ³ TWA (The value is for total dust containing no asbestos and < 1% crystalline silica)	total dust: 15 mg/m ³ TWA; respirable fraction: 5 mg/m ³ TWA	Not determined.
Barium Sulfate	7727-43-7	10 mg/m ³ TWA (The value is for the total dust containing no asbestos and <1% crystalline silica)	total dust: 15 mg/m ³ TWA; respirable fraction: 5 mg/m ³ TWA	Not determined.
Carbon black	1333-86-4	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	1750 mg/m ³ IDLH
Crystalline Silica (Respirable)	14808-60-7	0.1 mg/m ³ TWA (this TLV is for the respirable fraction of dust)	Respirable Dust: (10 mg/m ³)/(2 + %SiO ₂)	Potential NIOSH carcinogen. [25 mg/m ³ (cristobalite, tridymite); 50 mg/m ³ (quartz, tripoli)]
Diethylene glycol monoethyl ether	111-90-0	No TLV	No PEL established	Not determined.
Diethylene glycol mono-n-butyl ether	112-34-5	No TLV	No PEL established	Not determined.
Ethylene glycol mono-n-butyl ether	111-76-2	25 ppm TWA; 121 mg/m ³ TWA	50 ppm TWA; 240 mg/m ³ TWA	700 ppm IDLH
Lead Chromate	7758-97-6	As Cr: 0.012 mg/m ³ TWA; As Pb: 0.05 mg/m ³ TWA	As CrO ₃ : 0.1 mg/m ³ 8Hr-TWA; As Pb: 50 ug/m ³ 8Hr-TWA	Not determined.
Lead (II) Sulfate	7446-14-2	As Pb: 0.05 mg/m ³ TWA	As Pb: 50 ug/m ³ 8hr-TWA	Not determined.
Lead Molybdate	10190-55-3	0.05 mg/m ³	As Pb: 50 ug/m ³ 8hr-TWA; As Mo, Soluble Compounds: 5 mg/m ³ 8hr-TWA; As Mo, Insoluble Compounds, Total Dust: 15 mg/m ³ 8hr-TWA	Not determined.
Stoddard solvent	8052-41-3	100 ppm TWA; 525 mg/m ³ TWA	500 ppm TWA; 2900 mg/m ³ TWA	20,000 mg/m ³ IDLH
Talc	14807-96-6	2 mg/m ³ TWA (this TLV is for the respirable fraction of dust for Talc containing no asbestos and <1% crystalline silica)	Not containing asbestos; containing less than 1% quartz: 20 mppcf	1000 mg/m ³ IDLH
Titanium dioxide	13463-67-7	10 mg/m ³ TWA	total dust: 15 mg/m ³ TWA	Potential NIOSH carcinogen.
Toluene	108-88-3	50 ppm TWA; 188 mg/m ³ TWA	200 ppm TWA	500 ppm IDLH
Zinc Chromate, Basic	13530-65-9	As Cr: 0.01 mg/m ³ TWA	As CrO ₃ : 0.1 mg/m ³ 8hr-TWA	Not determined.

IX. PHYSICAL DATA

Appearance: Liquid
pH: N/A
Octanol/Water Coeff: Not Determined.
Solubility in Water: Partial
Vapor Pressure (mmHg): 1-10
Vapor Density: Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Evaporation Rate: Slower than n-Butyl Acetate.
Density: See Table starting on page 4.
V.O.C. See Table starting on page 4.
Initial Boiling Point 171 °C; 340 °F
Initial Freezing Point N/A

X. STABILITY AND REACTIVITY

Stability Information:	Stable under normal conditions.
Conditions to Avoid:	Contamination. Sparks, open flame, other ignition sources, and elevated temperatures.
Chemical Incompatibility:	Strong oxidizing agents, Strong alkalies
Hazardous Decomposition Products:	Carbon dioxide, Carbon monoxide, Toxic fumes, Toxic gases

XI. TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Carbon black	Oral LD50 Rat: >15400 mg/kg; Dermal LD50 Rabbit: >3 gm/kg
Carbonic acid, calcium salt (1:1)	Oral LD50 Rat : 6450 mg/kg
Ethanol, 2-(2-ethoxyethoxy)-	Oral LD50 Rat: 5500 mg/kg; Oral LD50 Mouse: 6600 mg/kg; Dermal LD50 Rabbit: 4200 uL/kg
Ethanol, 2-(2-butoxyethoxy)-	Oral LD50 Rat: 5660 mg/kg; Oral LD50 Mouse: 2400 mg/kg; Dermal LD50 Rabbit: 2700 mg/kg
Ethylene glycol	Inhalation LC50 Rat: 10876 mg/kg; Oral LD50 Rat: 4700 mg/kg; Oral LD50 Mouse: 5500 mg/kg; Dermal LD50 Rabbit: 9530 uL/kg
Lead Chromate	Oral LD50 Mouse: >12 gm/kg

XII. ECOLOGICAL INFORMATION

Overview : Care should be taken to minimize releases of any industrial chemicals to the environment.

XIII. DISPOSAL CONSIDERATIONS

Waste Description for Spent Product: Spent or discarded material is a hazardous waste.

Disposal Methods: Information in this MSDS is provided only as a guide. Consult with competent authority to determine proper waste disposal procedures. Clean up and dispose of waste and cleanup materials in accordance with all federal, state, and local environmental regulations.

Some Components Possibly Subjected to USEPA Land Disposal Restrictions:

When disposing of unused products or any waste, the preferred options are to send to a licensed reclaimer or to permitted incinerators. There may be some other ingredients subject to LDR categories. None expected.

XIV. TRANSPORTATION INFORMATION

Agency Basic Description and Label

DOT DOT by Land Transport: Not Regulated; DOT by Air and IATA (all modes): Paint, 3, UN1263, PG III Label Required: Flammable Liquid

Hazardous Substance

Lead sulfate	final RQ = 10 pounds (4.54 kg)
Ethylene glycol	final RQ = 5000 pounds (2270 kg)
Antimony trioxide	final RQ = 1000 pounds (454 kg)

XV. REGULATORY INFORMATION

Regulation

SARA 313 Reportable :	Ethanol, 2-butoxy-, Ethanol, 2-(2-ethoxyethoxy)-, Lead Compounds (Inorganic), Chromium Compounds (Chromium VI), Ethanol, 2-(2-butoxyethoxy)-, Zinc Compounds, Ethylene glycol, Antimony Compounds
TSCA Inventory :	All components of this product are listed in, or exempt from, the TSCA 8(b) Inventory.
M.S.D.S. Reportable HAP(s) :	Diethylene glycol monoethyl ether, Diethylene glycol mono-n-butyl ether, Ethylene glycol
California Proposition 65 :	The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65: "WARNING: This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm."

XVI. ADDITIONAL INFORMATION

Major References: VENDOR'S MSDS's, PAINT & COATINGS HANDBOOK, EPA'S LIST OF LISTS, AND OTHER PUBLISHED MATERIALS.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR YOUR GUIDANCE ONLY. MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION OR USE, INCLUDING USE OF THIS MATERIAL IN COMBINATION WITH OTHER MATERIALS OR PROCESSES. YOU THEREFORE SHOULD, AND THIS MATERIAL IS SUPPLIED ON THE CONDITION THAT YOU, PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF THE MATERIAL PRIOR TO USE, AND YOU ACCEPT RESPONSIBILITY FOR SATISFYING YOURSELF THAT THE MATERIAL IS SUITABLE AND THE COMPLETENESS OF THIS INFORMATION IS SUFFICIENT FOR YOUR USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA, OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE, AND WE DISCLAIM LIABILITY FOR LOSS OR INJURY ARISING FROM YOUR USE OF THIS MATERIAL, DATA OR INFORMATION. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HERE ARE GIVEN GRATIS. NO OBLIGATIONS NOR LIABILITIES FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.