



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 084
Product name Super Flash Spray Adhesive
Effective date 10-Jan-2008
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 1-630-628-3000
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Supersedes date 12-Nov-2007

2. Hazards Identification

Emergency overview Aerosol. EXTREMELY FLAMMABLE. Irritating to eyes, respiratory system and skin. CONTENTS UNDER PRESSURE. Pressurized container may explode when exposed to heat or flame.

OSHA regulatory status Prolonged exposure may cause chronic effects. This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

- Eyes** Contact may irritate or burn eyes. Eye contact may result in corneal injury.
- Skin** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
- Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.
- Ingestion** Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Conjunctivitis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Heptane	142-82-5	30 - 40
Acetone	67-64-1	20 - 30
Propane	74-98-6	10 - 15
n-Butane	106-97-8	8 - 10
Pentane	109-66-0	3 - 5
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

- Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
- Skin contact** Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.
- Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion	Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Notes to physician	Symptoms may be delayed.
General advice	Call a physician if symptoms develop or persist.

5. Fire Fighting Measures

Flammable properties	Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire. Water may be ineffective.
Protection of firefighters	
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Personal precautions	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.
Methods for cleaning up	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Heptane	142-82-5	400 ppm	500 ppm	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Pentane	109-66-0	600 ppm	Not established	Not established

OSHA Components	CAS #	TWA	STEL	Ceiling
Heptane	142-82-5	500 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Pentane	109-66-0	1000 ppm	Not established	Not established

Engineering controls Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal protective equipment

Eye / face protection Wear chemical goggles.
Skin protection Wear appropriate chemical resistant gloves.
Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
General hygiene considerations When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance Not available
Color Tan.
Odor Solvent.
Physical state Liquid.
Form Aerosol.
Flammability (Flame Extension) 18 in
Flammability (HOC) 43.72 kJ/g estimated
Flash back Yes
Pressure 35 - 45 @ 70F
Solubility None
Flash point -156 °F (-104.4 °C) estimated
Boiling point 91.4 °F (32.8 °C) estimated
Specific gravity 0.7041 estimated
pH Not applicable

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.
Conditions to avoid Heat, flames and sparks.
Hazardous decomposition products May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LD50: 6857 mg/kg estimated, Rat, Oral
 Acute LD50: 39024 mg/kg estimated, Rat, Dermal
 Acute LC50: 289 mg/l/4h estimated, Rat, Inhalation
Sensitization Not expected to be hazardous by OSHA criteria.
Local effects Contact may irritate or burn eyes. Components of the product may be absorbed into the body through the skin.
Chronic effects Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.
Neurological effects Hazardous by OSHA criteria.
Mutagenicity Not expected to be hazardous by OSHA criteria.
Reproductive effects Not expected to be hazardous by OSHA criteria.
Teratogenicity Not expected to be hazardous by OSHA criteria.
Epidemiology Hazardous by OSHA criteria.
Further information Symptoms may be delayed.

12. Ecological Information

Ecotoxicity LC50 216 mg/L, Fish, 96.00 Hours,
EC50 48000 mg/L, Daphnia, 48.00 Hours,
Components of this product have been identified as having potential environmental concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
Disposal instructions Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	2.1
Transport Category	2



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Heptane	142-82-5	Present
n-Butane	106-97-8	Present
Pentane	109-66-0	Present
Propane	74-98-6	Present

16. Other Information**HMIS® ratings**

Health: 1*
 Flammability: 4
 Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

10-Jan-2008