



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 208
Product name Toner Aide
Effective date 28-Dec-2007
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Supersedes date 13-Nov-2007

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame.

Cancer hazard. Irritating to skin. Irritating to eyes. Irritating to respiratory system.
Prolonged exposure may cause chronic effects.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Inhalation. Skin contact.

Eyes Causes eye irritation.

Skin This product may be harmful if it is absorbed through the skin. Irritating to skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Kidney.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects Blood. Central nervous system. Heart. Liver. Respiratory system.
Unconsciousness. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Narcosis. Cyanosis. Liver enlargement. Jaundice. Defatting of the skin. Irritation.

Potential environmental effects Components of this product are hazardous to aquatic life.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	20 - 30
n-Butyl Acetate	123-86-4	20 - 30
Trichloroethylene	79-01-6	15 - 20
Propane	74-98-6	10 - 15
Acetone	67-64-1	10 - 15
Mineral Spirits	8052-41-3	3 - 5
2-Butoxyethanol	111-76-2	3 - 5
Non-hazardous and other components below reportable levels		1 - 2.5

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Ingestion	Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General advice

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Call a physician if symptoms develop or persist.

5. Fire Fighting Measures

Flammable properties	Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire. Water may be ineffective.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
Specific hazards	Fire may produce irritating, corrosive and/or toxic gases.

6. Accidental Release Measures

Personal precautions	Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Should not be released into the environment.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage**Handling**

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not breathe gas/fumes/vapor/spray. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 2 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection**Exposure limits****ACGIH**

Components	CAS #	TWA	STEL	Celling
n-Butane	106-97-8	1000 ppm	Not established	Not established
n-Butyl Acetate	123-86-4	150 ppm	200 ppm	Not established
Trichloroethylene	79-01-6	50 ppm	100 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Mineral Spirits	8052-41-3	100 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Celling
n-Butyl Acetate	123-86-4	150 ppm	Not established	Not established
Trichloroethylene	79-01-6	100 ppm	Not established	200 ppm
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Mineral Spirits	8052-41-3	500 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye / face protection**

Wear chemical goggles.

Skin protection

Wear appropriate chemical resistant clothing. Protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Color	clear colorless
Odor	fruity
Physical state	Liquid.
Form	Aerosol.
Flammability (HOC)	29.46 kJ/g estimated
Flash back	Yes
Pressure	43 - 53 psig @ 70F
Solubility	Negligible

Material name: Toner Aide

Material ID: 610 Revision date: 28-DEC-2007 Print date: 28-DEC-2007

MSDS US

3 / 6

Flash point	-156 °F (-104.4 °C) estimated
Boiling point	114.8 °F (46.1 °C) estimated
Specific gravity	0.7485 estimated
pH	Not applicable

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	This product is incompatible with nitrates.
Hazardous decomposition products	Irritants. Toxic gas. May include oxides of nitrogen.

11. Toxicological Information

Acute effects	Acute LD50: 5643 mg/kg estimated, Rat, Oral Acute LD50: 7786 mg/kg estimated, Rat, Dermal Acute LC50: 71 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Liver toxicity. Blood disorder may occur after ingestion. Irritating to eyes. Irritating to skin. Irritating to respiratory system. Components of the product may be absorbed into the body through the skin.
Chronic effects	Hazardous by OSHA criteria. This product may be harmful if it is absorbed through the skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Subchronic effects	Kidney injury may occur. Blood disorder may occur after prolonged inhalation. Blood disorder may occur after prolonged skin contact.
Carcinogenicity	Hazardous by OSHA criteria.
Neurological effects	Hazardous by OSHA criteria.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.
Epidemiology	Hazardous by OSHA criteria.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicity	LC50 56.39 mg/L estimated, Fish, 96.00 Hours, EC50 11.15 mg/L estimated, Daphnia, 48.00 Hours, IC50 613 mg/L estimated, Algae, 72.00 Hours,
Environmental effects	Harmful to aquatic life.

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F D040: Waste Trichloroethylene
Disposal instructions	Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS, toxic, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	NOT a LTD QTY
Item	5TF
Labels required	2.1 +6.1
Transport Category	1



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Hazard class	2.1
Subsidiary hazard class	6.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

n-Butyl Acetate: 5000.0000
Trichloroethylene: 100.0000
Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

2-Butoxyethanol	111-76-2	Present
Acetone	67-64-1	Environmental hazard
Mineral Spirits	8052-41-3	Present
n-Butane	106-97-8	Present
n-Butyl Acetate	123-86-4	Environmental hazard
Propane	74-98-6	Present
Trichloroethylene	79-01-6	Environmental hazard

16. Other Information**HMIS® ratings**

Health: 2*
Flammability: 3
Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

28-Dec-2007