

ITEM NUMBER: 383 - WEB TYPE ADHESIVE 13 OZ
 VERSION 2 EFFECTIVE DATE: 10/23/02 SUPERCEDES: 04/22/02 PREPARED BY: Ron Cepa
 Section(s) Revised: HMIS , II, III, IV, V, VI
 IDENTITY (As Used On Label and List): WEB TYPE ADHESIVE 13 OZ

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS): - Health = 2*, Fire = 4, Reactivity = 0 Protective Equipment = B
 (Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, * = Chronic Hazard)

SECTION I
 SPRAYWAY, INC. TELEPHONE NUMBER FOR INFORMATION : 630-628-3000
 484 VISTA
 ADDISON DATE PRINTED : 6/06/03 NAME OF PREPARER : Ron Cepa

IL 60101
 SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names	CAS #	SARA SEC 313	ACGIH TLV-TWA/STEL	OSHA PEL-TWA/STEL	% By Wt.
Acetone	67-64-1	No	750 ppm/1000 ppm	1000 ppm/ NE	15-25
Cyclohexane	110-82-7	Yes	300 ppm/ NE	300 ppm/ NE	15-25
n-Pentane	109-66-0	No	600 ppm/ NE	1000 ppm/ NE	1-5
Propane	74-98-6	No	2500 ppm/ NE	1000 ppm/ NE	10-20
Liquefied petroleum gas mixture	See below	No	See below ingredient data		10-20
Propane	74-98-6	No	2500 ppm/ NE	1000 ppm/ NE	-
n-Butane	106-97-8	No	800 ppm/ NE	NE / NE	-

Balance of ingredients are non-hazardous or below reportable levels.

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 116 @ 130F / 55 @ 70F Specific Gravity (H2O=1): 0.6994 pH: NA
 Solubility/Water: Negligible Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND
 Appearance and Odor: Aerosol spray with solvent odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.
 Flashpoint: <0F (Propellant); >-56F (Concentrate)
 Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5
 Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.
 Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
 Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
 Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA
 Incompatibility (Materials to Avoid): Oxidizing agents, acids, bases.

