

ITEM NUMBER: 676 - CARPET STAIN REMOVER 18 OZ
VERSION 1 EFFECTIVE DATE: 05/15/01 SUPERCEDES: 00/00/00 PREPARED BY: Ron Cepa
IDENTITY (As Used On Label and List): CARPET STAIN REMOVER 18 OZ

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS): - Health = 2, Fire = 2, Reactivity = 0, Protective Equipment = B
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, \* = Chronic Hazard)

SECTION I
SPRAYWAY, INC. TELEPHONE NUMBER FOR INFORMATION : 630-628-3000
484 VISTA
ADDISON DATE PRINTED : 11/26/03 NAME OF PREPARER : REGULATORY COMPLIANCE

IL 60101
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Table with 6 columns: Chemical Names, CAS #, SARA Title III SEC 313, ACGIH TLV/TWA, OSHA PEL, % By Wt.
Rows include: 2-Butoxyethanol, Liquefied petroleum gas mixture, Propane, n-Butane

Balance of ingredients are non-hazardous or below reportable levels.
\* Skin

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 120-130 @ 130F Specific Gravity (H2O=1): 0.9463
Solubility/Water: Completely Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): <1
Appearance and Odor: Aerosol spray with characteristic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is not required to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.
Flashpoint: <0F (Propellant); >154F (Concentrate)e
Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5
Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA: NA
Incompatibility (Materials to Avoid): None. dizers; hydrochloric acid.
Hazardous Decomposition Products: Carbon monoxide, hydrocarbon vapors, rocarbon vapors, smoke.
Conditions to Avoid: Keep away from heat, sparks, and flames. Dropping of containers may cause bursting.



NG-- Negligible NA-- Not Applicable NE-- Not Established UN-- Unavailable ND-- Not Determined

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.

EFFECTIVE DATE: 05/15/01 SUPERCEDES: 00/00/00 PREPARED BY: Ron Cepa

