

M A T E R I A L S A F E T Y D A T A S H E E T
(MSDS)

MSDS707 707 707

ITEM NUMBER: 707 - # 7 0 7 V I N Y L A P P L I C A T I O N 1 7 O Z .

IDENTITY (As Used On Label and List): #707 VINYL APPLICATION 17 OZ.

E M E R G E N C Y M E D I C A L Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (NFPA): - Health = 1, Fire = 4, Reactivity = 0, Protective Equipment = *B
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

--*-*-* SECTION I

SPRAYWAY, INC.
484 VISTA
ADDISON

TELEPHONE NUMBER FOR INFORMATION : 630-628-3000

DATE PRINTED : 2/28/00*

IL 60101

NAME OF PREPARER : Ron Cepa

--*-*-* SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names	Exposure Limits (LD50-Oral Rat)	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Specially Denatured Alcohol (CAS# 64-17-5)	13.7g/kg	---	1000ppm	1000ppm	15-20
Acetone (CAS# 67-64-1)	9.7g/kg	Yes	750	1000	5-10
Isopropyl Alcohol (CAS# 67-63-0)	2.7g/kg	---	400	400	<5.0
Dimethyl Ether (CAS# 115-10-6)/ Liquified Petroleum Gas (CAS# 68476-85-7)	---	---	1000	ND	30.0

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.
Components Listed As A Suspected Carcinogen: None

--*-*-* SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 100-110@130F Specific Gravity (H2O=1): <1.0
Solubility/Water: Miscible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
Appearance and Odor: Clear yellow solution, sharp penetrating odor

--*-*-* SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be flammable as described in 16CFR 1500.45.
Flammable Limits - % Volume In Air (Propellant): LEL: 3.4 UEL: 18.0
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

--*-*-* SECTION V - REACTIVITY DATA