

ITEM NUMBER: 870 - VANDALISM SPRAY 18 OZ.
Version 3 EFFECTIVE DATE: 6/30/04 SUPERCEDES: 3/03/00 ORIGINAL PREPARER: SUE HEISER

IDENTITY (As Used On Label and List): VANDALISM SPRAY 18 OZ.

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS(R)): Health = 2*, Fire = 2, Reactivity = 0, Protective Equipment = B
(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, * = Chronic)

SECTION I
SPRAYWAY, INC. TELEPHONE NUMBER FOR INFORMATION : 630-628-3000
484 VISTA DATE PRINTED : 1/05/05 NAME OF PREPARER : REGULATORY COMPLIANCE
ADDISON

IL 60101
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Table with 6 columns: Chemical Names, Exposure Limits (LD50-Oral Rat), SARA Title III SEC 313, ACGIH TLV/TWA, OSHA PEL, % By Wt.
Rows include Dichloromethane, Tetrachloroethylene, Toluene, and Liquefied Petroleum Gas.

*Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.
Components Listed As A Suspected Carcinogen: Methylene chloride is listed as an animal carcinogen by NTP.
perchloroethylene - IARC & NTP. This product contains chemicals known to the State of California to cause cancer
a irth defects or other reproductive harm.

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 78@130F Specific Gravity (H20=1): <1 pH: NA
Solubility/Water: Negligible Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND
Appearance and Odor: Heavy, coarse wet spray, strong methylene chloride and toluene odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be flammable as described in 16CFR 1500.45.
Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2
Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct
flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA
Incompatibility (Materials to Avoid): Oxidizing agents, heat and open flame.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen chloride, phosgene and
additional toxic chemicals may be formed in small amounts.
Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or
s' is. Dropping of containers may cause bursting.

